

Solidtone Oil Wood Stain Preservative

Covers the Wood Grain While
Still Exhibiting the Beauty of the
Wood's Texture.

ANALYSIS

Non Volatile	50.08
Volatile	49.92
	100.00*

COMPOSITION of NON-VOLATILE

Polymerized Linseed Oil	22.46
Soya Alkyd Resin	16.80
Soya Modified Polyurethane	
Resin Type I	3.51
Silicates & Silica	51.30
Folpet	0.70
Bis(Tributyltin) Oxide	1.03
Additives	2.80
Driers	1.40
	100.00*

COMPOSITION OF VOLATILE

Aromatic Hydrocarbons	100.00
FD031081.5	

IMPORTANT EXAMINE CONTENTS FOR PROPER COLOR MATCH BEFORE APPLICATION

Valspar cannot assume
responsibility for
mis-matches or color
variations after
application.

NOTE

Clear base ready for
use only after the tinting
colorant has been
added.

Directions for Use

Apply this product only as directed on this label. It is in violation of Federal law to use this product in a manner inconsistent with its labeling.

1 Where to Use:

Exterior application only. Natural Solidtone Oil Stain is richly pigmented and formulated to provide an opaque, velvet flat finish that preserves the wood and repels damaging moisture. Apply only to new or previously stained, unsealed, vertical surfaces, such as siding and fences. Not recommended for horizontal surfaces, such as decks. Do not use on abrasive plywood, outdoor furniture or on surfaces which are in direct contact with the ground. Top coating with clears should be avoided as this will seal the surface preventing future stain penetration.

2 Prepare the Surface:

The surface to be stained must be clean and dry. Previously unsealed, stained surfaces, should be free of any flaking stain, chalk, or dirt. Mildew must be killed and removed with a solution of one part fresh household bleach with three parts water. Rinse thoroughly with clean water and allow to dry completely before application of stain. CAUTION - Follow directions on bleach label. Protect skin and eyes. Do not prime surface prior to staining as this product is self priming.

3 Applying the Product:

Stir well before use and occasionally during use, with a circular lifting motion. Apply liberally, by brush, roller, or spray in a uniform film, avoiding runs or sags. Thinning is not recommended, however, if necessary, use mineral spirits sparingly. Not recommended for application with temperatures below 40° Fahrenheit. Do not apply in hot sunlight. Dries under normal conditions, for recoat in 6-8 hours, dries thoroughly in 24 hours. Clean tools and paint applicators with mineral spirits.

4 Spreading Capacity:

Varies depending on texture and porosity of the surface. Up to 400 square feet per gallon on smooth surfaces; 100 to 300 square feet per gallon on very porous or rough surfaces.

PRECAUTIONARY STATEMENTS — HAZARDS TO HUMANS AND DOMESTIC ANIMALS.

WARNING! Keep Out Of Reach Of Children. Contains Petroleum Distillate. Harmful or fatal if swallowed. Do not use or store near heat or open flame.

Use only in well ventilated area. Do not breathe vapor or spray mist. Do not get in eyes, or on skin or clothing! Wear rubber gloves and protective clothing when applying or handling freshly treated lumber.

FIRST AID: If on skin, wash with soap and water. Remove and wash contaminated clothing before reuse. If in eyes, immediately flood with water several minutes. Call a physician. If swallowed, do not induce vomiting. Call a physician.

Environmental Hazards: This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of waste.

Physical or Chemical Hazards: Combustible product. Do not use or store near heat or open flame.

Storage and Disposal: Do not use or store inside the home. Do not reuse empty container. Wrap container and put in trash collection. Keep away from food and feed.



Consumer Brands

The Valspar Corporation

MINNEAPOLIS, MINNESOTA 55415