In Accon

Polyurethane Fortified

Water Repellent

Retards Rot, Mildew, Warping, Swelling

Fade Resistant

Semi-Transparent
Oil Wood Stain

ANALYSIS

Pigment 0.3%	
Silicales	100.0
Vehicle 99.7%	
Soya Arkyd Resin	91
Urethane Alkyd Resin	2.2
Tributy'tin Oxide	0.5
Bodied Linseed Oil	39
Tung Oil	39
N (Trichiaromethyi)	
"hiophtha imide"	0.3
Driers	0.3
Addit ex	3.0
Anghatic	
Hydror groons	73 7
دان إطابانيَّانِ	3 •
FD033183 1	100 0%

IMPORTANT EXAMINE CONTENTS FOR PROPER COLOR MATCH BEFORE APPLICATION

Valspar cannot assume responsibility for mis-matches or color variations after application

NOTE

Clear base ready for use only after the fir-ig colorant has been added

Directions For Use

Apply this product only as directed on this label. It is in violation of federal law to use this product in a manner inconsistent with its labeling.

1 Where to Use:

Exterior application only. Natural Semi-Transparent Oil Wood Stain and Preservative is a lightly pigmented wood stain especially formulated to permit the natural beauty and texture of the wood to show. It protects as it beatuities and can be used outdoors only on all new or bare wood surfaces such as Rough Sawn Siding, Shakes, Shingles, Fencing. Not for use on abraded plywood.

Clear finishes should not be applied as it will seal the surface, preventing stain recoating when necessary.

2 Prepare the Surface:

Ready-to-stain surfaces should be thoroughly clean and dry before stain is applied. Any dirt, dust, loose material should be removed. Do not prime. Natural Oil Wood Stain and Preservative is self-priming.

3 Applying the Product:

Mix thoroughly before and during application to insure a uniform finish. Stir with a circular lifting motion. Stain only when temperature is above 40° F, and other conditions are favorable. Apply liberally as it comes from the can. Do not add thinners. Dries to touch in 3 to 4 hours. Clean applicators and tools with mineral spirits. Color will vary depending on type of wood and amount of stain used. Stain a test panel first to determine final color and appearance.

4 Spreading Capacity:

Up to 250 300 square feet per gallon, one coat depending on surface texture and porosity

PRECAUTIONARY STATEMENTS — HAZARDS TO HUMANS AND DOMESTIC ANIMALS.

WARNING! Keep Out Of Reach Of Children. Contains Petroleum Distillate. Harmful or fatal if swallowed. Do not use or store near heat or open flame.

Use only in well ventilated area. Do not breathe vapor or spray mist. Do not get in eyes, or on skin or clothing! Wear rubber gloves and protective clothing when applying or handling freshly treated lumber.

FIRST AID: If on skin, wash with soap and water. Remove and wash contaminated clothing before reuse. If in eyes, immediately flood with water several minutes. Call a physician. If swallowed, do not induce vomiting. Call a physician

Environmental Hazards: This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of waste.

Physical or Chemical Hazards: Combustible product. Do not use or store near heat or open flame.

Storage and Disposal: Do not use or store inside the home. Do not reuse empty container. Wrap container and put in trash collection. Keep away from food and feed.





Semi-Transparent Oil Wood Stain and **Preservative**

128 Fl. Oz.

(1 Gallon)

Color and Number 3.785 Liters

Tetal worth Fungicide Fo

COMBOOMED See Back Panel for Additional Precautic

EPA Reg. No. 8177-EPA Est. No. 8177-IL

Bis (Tributy ltin) C:

Folpet (N. Etricklen methyl thiophthali

Inert Ingredient

Statements

Resists Film at hy mildew.



Semi-Transparent Oil Wood Stain and Preservative

- Fade Resistant | Self Priming
 - Will Never Peel or Blister

LABEL ANALYSIS WILL VARY WITH COLOR.

ACCEPTED with COMMENTS to EPA Letter Dance

MAR BIT TERS

8177-36

Directions For Use

Apply this product only as directed on this tabel. It is in violation of federal law to use this product in a manner inconsistent with its labeling.

1 Where to Use:

Exterior application only. Natural Semi-Transparent Oil Wood Stain and Preservative is a lightly pigmented wood stain especially formulated to permit the natural beauty and texture of the wood to show. It protects as it beautifies and can be used outdoors only on all new or bare wood surfaces except on abraded plywood, such as Rough Sawn Siding, Shakes, Shingles, Fencing.

Clear finishes should not be applied as it will seal the surface, preventing stain recoating when necessary.

2 Propere the Surface:

Ready-to-stain surfaces should be thoroughly clean and dry before stain is applied. Any dirt, dust, loose material should be removed. Do not prime. Natural Oil Wood Stain and Preservative is self-priming.

3 Applying the Product:

Mix thoroughly before and during application to insure a uniform finish. Stir with a circular lifting motion. Stain only when temperature is above 40°F and other conditions are favorable. Apply liberally as it comes from the can. Do not add thinners. Dries to touch in 3 to 4 hours. Clean applicators and tools with mineral spirits. Color will vary depending on type of wood and amount of stain used. Stain a test panel first to determine final color and appearance.

4 Spreading Capacity:

Up to 250-300 square feet per gallon, one coat, depending on surface texture and porosity.

PRECAUTIONARY STATEMENTS — HAZARDS TO HUMANS AND DOMESTIC ANIMALS.

WARNING! Keep Out Of Reach Of Children. Contains Petroleum Distillate. Harmful or fatal if swallowed. Do not use or store near heat or open flame.

Use only in well ventilated area. Do not breathe vapor or spray mist. Do not get in eyes, or on skin or clothing! Wear rubber gloves and protective clothing when applying or handling freshly treated lumber.

FIRST AID: If on skin, wash with soap and water. Remove and wash contaminated clothing before reuse. If in eyes, immediately flood with water several minutes. Call a physician. If swallowed, do not induce vomiting. Call a physician.

Environmental Hazards: This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of waste.

Physical or Chemical Hazards: Combustible product. Do not use or store near heat or open flame.

Storage and Disposal: Do not use or store inside the home. Do not reuse empty, container. Wrap container and put in trash collection. Keep away from food and feed.

CONSUMER COATINGS DIVISIONS THE VALSPAR CORPORATION MARIEAPOLIS, MIN \$5415

51

		TEPA REGISTRATION NO.	DATE OF ISSUANCE	
U.S. ENVIRONMENTAL PROTECTION A OFFICE OF PESTICIDES PROGR			DATE OF ISSUANCE	
REGISTRATION DIVISION (NH 467	7,	TERM OF ISSUANCE		
NOTICE OF PESTICIDE: THE PART OF THE PART	THAT I M	NAME OF PESTICIDE PHODU	Ť	
(Under the Federal Insecticide, Fun- and Rodenticide Act, as amende				
NAME AND ADDRESS OF REGISTRANT (Include	ZIP code)	_ 		
r		$\frac{7}{18}$	1 91348	
		<u></u> .		
_		_		
NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.				
On the basis of information furnished by the the Federal Insecticide, Fungicide, and Roc		above named pesticide is hereb	y Registered/Reregistered under	
A copy of the tabeling accepted in connecti	on with this Rep	istration/Reregistration is retu	rned herewith,	
Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.				
· ·				
j				
i				
1				
ATTACHMENT IS APPLICABLE				
SIGNATURE OF APPROVING OFFICIAL		· · · · · · · · · · · · · · · · · · ·	DATE	

EPA Form 8570-6 (Rev. 5-76)

PREVIOUS EDITION MAY BE USED UNTIL SUPPLY IS EXHAUSTED.

•

- c. Under apricots, qualify the "Shothole" claim so as to indicate whether this pertains to the "Coryneum" or "Coccomyces" fungal disease.
- d. Under grapes, change the domage to "3 to 4 teaspoons per gallon" and indicate that the last two applications are to be made just after bloom and again 10 days later.
- 3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Henry : 1. Jacoby Product Manager (21) Pungicide-Herbloide Branch Registration Division (TS-767)

Enclosure