

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

1054 PM21
8177-36

215090
345
17

MAR 22 1988

Mr. Brian C. Heath
The Valspar Corporation
1101 Third Street South
P.O. Box 1461
Minneapolis, MN 55440

Dear Mr. Heath:

SUBJECT: Valspar Semi-Transparent Oil Wood Stain And
Preservative Clear Base 6515
EPA Registration No. 8177-36
Valspar's Submissions Dated September 25, 1986;
May 25, and December 17, 1987; January 6, and
February 5, 1988

There is no objection to the use of the alternate formulation re-
quested in Valspar's letter of February 5, 1988.

This accepted label is the basic label for all additional brand
names prescribed in the registrant's letter of December 17, 1987.

The labeling referred to above, submitted in connection with registra-
tion under the Federal Insecticide, Fungicide, and Rodenticide Act,
is acceptable subject to the comments listed below. Five copies of the
finished labeling must be submitted.

1. Verify the calculations on the Confidential Statement of Formula
(CSF) for the following paint pigments and resubmit the
corrected CSFs:
 - a. 4707 Buckthorn, item # 17;
 - b. 4704 Crimson Redwood, 4712 White Tint, 4713 Adobe Brown, 4716
Natural Cedar, 4717 Natural Redwood for the "Mineral Spirits"
components,
 - c. 4709 Briarwood, for the Duramex 2622 component.
2. The statement "Contains Petroleum Distillates" must be near the
ingredient statement.

CONCURRENCES

SYMBOL	TS-767C						
SURNAME	Tomu						
DATE	3/21/88						

3. Under "Directions for Use", add a statement indicating that the product must not be used for treating wood to be in contact with soil.
4. Under "Environmental Hazards", add the statement "Do not contaminate water when disposing of equipment washwaters".

Sincerely yours,

Lois A. Rossi
Product Manager 21
Fungicide/Herbicide Branch
Registration Division (TS-767C)

cc: J. Satagaj, Atty

RD/FHB/PM-21:htt:3/21/88

BEST AVAILABLE COPY

Valspar

NATURAL WOOD



Polyurethane
Fortified

Water Repellent

Eycoods Federal Spec.
J.W. 5720, 37

Retards Rot, Mildew,
Warping, Swelling

Fade Resistant

KEEP OUT OF REACH
OF CHILDREN

**WARNING
COMBUSTIBLE**

See Back Panel for
Additional Precautionary
Statements

EPA Reg. No. 8177-
EPA Est. No. 8177-IL-1

Semi-Transparent
**Oil Wood Stain and
Preservative**

128 FL. OZ.

(1 Gallon) Color and Number 3.785 Liters

Active Ingredients	
Bis(Tributyltin)oxide	0.5%
Felpet (N-[Trichloro- methyl]thiophthalimide)*	0.30%
Inert Ingredient	99.20%
Total	100.00%

*with Fungicide Felpet
Resists film attack
by mildew.

Subm dated 1/6/88

Valspar NATURAL OIL WOOD STAIN AND PRESERVATIVE

Semi-Transparent Oil Wood Stain and Preservative

- Fade Resistant...Self Priming
- Will Never Peel or Blister

LABEL
ANALYSIS
WILL VARY
WITH
COLOR.

ACCEPTED
COMMENTS
EPA Letter Dated:

MAR 31 1983

Under the Federal
Fungicide, and Insecticide
Act, 1946 (7 U.S.C. 135)
is registered under
EPA Reg. No. 8177-36

Directions For Use

Apply this product only as directed on this label. It is in violation of federal law to use this product in a manner inconsistent with its labeling.

1 Where to Use:

Exterior application only. Natural Semi-Transparent Oil Wood Stain and Preservative is a lightly pigmented wood stain especially formulated to permit the natural beauty and texture of the wood to show. It protects as it beautifies and can be used outdoors only on all new or bare wood surfaces except on abraded plywood, such as Rough Sawn Siding, Shakes, Shingles, Fencing.

Clear finishes should not be applied as it will seal the surface, preventing stain recoating when necessary.

2 Prepare the Surface:

Ready-to-stain surfaces should be thoroughly clean and dry before stain is applied. Any dirt, dust, loose material should be removed. Do not prime. Natural Oil Wood Stain and Preservative is self-priming.

3 Applying the Product:

Mix thoroughly before and during application to insure a uniform finish. Stir with a circular lifting motion. Stain only when temperature is above 40°F. and other conditions are favorable. Apply liberally as it comes from the can. Do not add thinners. Dries to touch in 3 to 4 hours. Clean applicators and tools with mineral spirits. Color will vary depending on type of wood and amount of stain used. Stain a test panel first to determine final color and appearance.

4 Spreading Capacity:

Up to 250-300 square feet per gallon, one coat, depending on surface texture and porosity.

ACCEPTED
MAR 22 1988
Under the Federal Insecticide, Fungicide, and Rodenticide Act, 1946 (7 U.S.C. 135) is registered under EPA Reg. No. 8177-36

PRECAUTIONARY STATEMENTS — HAZARDS TO HUMANS AND DOMESTIC ANIMALS.

WARNING! Keep Out Of Reach Of Children. Contains Petroleum Distillate. Harmful or fatal if swallowed. Do not use or store near heat or open flame.

Use only in well ventilated area. Do not breathe vapor or spray mist. Do not get in eyes, or on skin or clothing! Wear rubber gloves and protective clothing when applying or handling freshly treated lumber.

FIRST AID: If on skin, wash with soap and water. Remove and wash contaminated clothing before reuse. If in eyes, immediately flood with water several minutes. Call a physician. If swallowed, do not induce vomiting. Call a physician.

Environmental Hazards: This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of waste.

Physical or Chemical Hazards: Combustible product. Do not use or store near heat or open flame.

Storage and Disposal: Do not use or store inside the home. Do not reuse empty container. Wrap container and put in trash collection. Keep away from food and feed.

CONSUMER COATINGS DIVISION
THE VALSPAR CORPORATION
MINNEAPOLIS, MN 55416

BEST AVAILABLE COPY