

**Colony**

**Exterior Application • Will Never Peel Or Blister • Preserves and Protects Wood's Natural Beauty**

**Exterior  
Oil Stain  
Preservative  
*Semi-Transparent***



**TINT BASE 4711-N**


**120 FL. OZ. (3 3/4 QTS.)  
3.543 LITERS**

NOT RECOMMENDED  
 Recommended for exterior use only



## COLONY STAIN & WOOD PRESERVATIVE

Retards rot and mildew. Water repellent. Exterior application only. Permits the natural beauty and texture of wood to show.



### Wood's Natural Beauty • Repels Water

**KEEP OUT OF REACH OF CHILDREN!**  
**WARNING!**  
**COMBUSTIBLE!**  
**CONTAINS PETROLEUM DISTILLATES**

See Back Panel for Additional  
 Precautionary Statements

EPA Reg.No. 8177-36

EPA Est.No. 8177-IL-1

Active Ingredients	
Bis (Mibutyltin) Oxide.....	0.50%
Folpet (N-(Trichloro	
methoxy) thiophthalimide)*.....	0.30%
Inert Ingredient.....	99.20%
	100.00%

\*With Fungicide Folpet  
 Resists Film Attack by Mildew

120 FL. OZ. (3 3/4 QTS)  
 3.543 LITERS

### DIRECTIONS FOR USE

Apply this product only as directed. It is a violation of federal law to use this product in a manner inconsistent with its labeling.

### WHERE TO USE

Use on all new or bare exterior wood such as siding, shingles and fencing. Do not use on abraded plywood, meets spec. TT-W-572b,3.7. Do not top coat with clear finishes. Not for surfaces in contact with the soil.

### COVERAGE

Approximately 250-300 square feet per gallon depending on porosity.

### DRY TIME

Dries to touch in 3 to 4 hours.

### SURFACE PREPARATION

Make sure surface is clean and dry, free of loose material. Do not prime.

### APPLICATION

Stir thoroughly before and during application. Apply liberally as it comes from the can. Do not apply when temperature is below 40°F. Clean tools with mineral spirits.

ANALYSIS 47-4711-8  
 Pigment 8.3%

Silicates.....	100.0%
	100.0%
Vehicle 91.7%	
Alkyd Resin.....	73.7%
Hydrocarbons.....	3.1%
Dispersants.....	9.1%
Says Alkyd Resin.....	
Says Med.....	
Polyurethane Resin.....	2.2%
(Type II).....	0.9%
Triethyltin Oxide.....	3.9%
Buffed Linseed Oil.....	3.9%
Tung Oil.....	0.3%
Others.....	0.3%
(Methyltin) Thiophthalimide.....	0.3%
Thiophthalimide.....	3.0%
Additives.....	108.6%

### PRECAUTIONARY STATEMENTS — HAZARDS TO HUMANS AND DOMESTIC ANIMALS.

**WARNING! Keep Out Of Reach Of Children.**  
 Harmful or fatal if swallowed. Do not use or store near heat or open flame.

Causes substantial but temporary eye injury. May cause an allergic skin reaction. Harmful if swallowed or inhaled. Do not get in eyes, on skin, or on clothing. Use only in well ventilated area. Avoid breathing sanding dust, vapor or spray mist. Wear rubber gloves, protective clothing, and goggles or face shield when applying or handling freshly treated lumber. Wash thoroughly with soap and water after handling. Remove contaminated clothing and separately launder clothing before reuse.

**STATEMENTS OF PRACTICAL TREATMENT:** If in eyes: Immediately flush with water for several minutes. Call a physician. If swallowed: Promptly drink a large quantity of milk, egg whites, gelatin solution, or if these are not available, drink large quantities of water. Do not drink alcohol. Do not induce vomiting. Call a physician. If on skin: Wash with soap and water. Remove and wash contaminated clothing before reuse.

**Environmental Hazards:** This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of equipment wash waters.

**Physical or Chemical Hazards:** Combustible product. Do not use or store near heat or open flame.

**Storage and Disposal:** Do not use or store inside the home. Do not reuse empty container. Wrap container and put in trash collection. Keep away from food and feed.



## Colony PAINTS

Division of The Ralston Corporation

KANSAS CITY 64127 • BALTIMORE 21230 • HOUSTON 77009 • LOS ANGELES 90031



Exterior Application • Repels Moisture • Protects Wood Against Warping •

# Exterior Clear Wood Preservative

4791-N

2

Not for use on  
bare wood or metal surfaces



## COLONY CLEAR WOOD PRESERVATIVE

Penetrates wood, fights rot and mildew and repels water. Protects against warping. For use on new or bare unsealed exterior wood surfaces such as siding, shakes, shingles and fencing. Can be primed and painted.



Prevents Warping • Preserves and Protects

**KEEP OUT OF REACH OF CHILDREN!**  
**WARNING!**  
**COMBUSTIBLE!**  
**CONTAINS PETROLEUM DISTILLATES**

See Back Panel for Additional Precautionary Statements

EPA Reg.No. 8177-36  
EPA Est.No. 8177-IL-1

Active Ingredients  
Bis (Tributyltin) Oxide..... 0.50%  
Folpet (N-[Trichloro methyl] thiophthalimide)\*..... 0.30%  
Inert Ingredient..... 99.20%  
100.00%

\*With Fungicide Folpet  
Resists Film Attack by Mildew

128 FL. OZ. (1 GAL.)  
3.785 LITERS

ANALYSIS 47-4791-B

Non-Volatile	16.1%
Volatile	83.9%
	100.0%
Composition of Non-Volatile	
Solvents	1.8%
Says Alloy Resin	51.6%
Redox Linseed Oil	21.8%
Tributyltin Oxide	3.4%
Others	0.6%
NE Trichloromethyl Thiophthalimide	2.3%
Additives	18.5%
	100.0%
Composition of Volatile	
Aliphatic Hydrocarbons	98.1%
Aromatics	1.9%
	100.0%

### DIRECTIONS FOR USE

Apply this product only as directed. It is a violation of federal law to use this product in a manner inconsistent with its labeling.

### WHERE TO USE

All new, bare and unsealed wood such as siding, shakes, shingles and fencing. Not for surfaces in contact with the soil.

### COVERAGE

Approximately 250-300 square feet per gallon depending on porosity.

### DRY TIME

Dries to touch in 3-4 hours. Allow 24-48 hours before painting.

### SURFACE PREPARATION

Make sure surface is clean and dry, free of loose material. New wood with surface glaze must be sanded to allow for penetration.

### APPLICATION

Stir thoroughly before and during application. Apply liberally by a brush, roller, spray or dip. Soak end grain thoroughly. Do not apply when temperature is below 40°F. If to be painted, use an alkyd primer before applying finish coat.

### PRECAUTIONARY STATEMENTS — HAZARDS TO HUMANS AND DOMESTIC ANIMALS.

**WARNING! Keep Out Of Reach Of Children.** Harmful or fatal if swallowed. Do not use or store near heat or open flame.

Causes substantial but temporary eye injury. May cause an allergic skin reaction. Harmful if swallowed or inhaled. Do not get in eyes, on skin, or on clothing. Use only in well ventilated area. Avoid breathing sanding dust, vapor or spray mist. Wear rubber gloves, protective clothing, and goggles or face shield when applying or handling freshly treated lumber. Wash thoroughly with soap and water after handling. Remove contaminated clothing and separately launder clothing before reuse.

**STATEMENTS OF PRACTICAL TREATMENT:** If in eyes: Immediately flush with water for several minutes. Call a physician. If swallowed: Promptly drink a large quantity of milk, egg whites, gelatin solution, or if these are not available drink large quantities of water. Do not drink alcohol. Do not induce vomiting. Call a physician. If on skin: Wash with soap and water. Remove and wash contaminated clothing before reuse.

**Environmental Hazards:** This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of equipment wash waters.

**Physical or Chemical Hazards:** Combustible product. Do not use or store near heat or open flame.

**Storage and Disposal:** Do not use or store inside the home. Do not reuse empty container. Wrap container and put in trash collection. Keep away from food and feed.



**Colony PAINTS**

Division of The Reliance Corporation

KANSAS CITY 64127 • BALTIMORE 21230 • HOUSTON 77060 • LOS ANGELES 90008