

SEP 26 1990

The Valspar Corporation
P.O. Box 625
Raritan, NJ 08869-0625

Attention: R.E. Chamberlin

Gentlemen:

Subject: Valspar Marine Coatings Sovaklor Coastal
Super Service Antifouling 59-R-27
EPA Registration No. 8177-40
Your Submission Dated April 25, 1989
EPA Received Date April 26, 1989

The labeling referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, is acceptable subject to the comments listed below.

1. Place the "Directions For Use" heading and Misuse statement above the "Physical or Chemical Hazards" heading.
2. Under the "Statement of Practical Treatment, If Swallowed" rephrase to read:

Drink promptly large quantities of water.
Avoid alcohol. Get medical attention.

3. Please make all the necessary changes according to the May 21, 1990 Label Improvement Program.
4. Submit five (5) copies of your final printed labeling.

A stamped copy of the label is enclosed for your records.

61927:I:Farmer:L31-10:KENCO:09/20/90:10/18/90:CL:VO:EK:CL


CONCURRENCES

SYMBOL	H-2505-C						
SURNAME	V. Dutch						
DATE	9-26-90						

2073

Should you have any further questions, please contact Veronica Dutch
at (703) 557-7404.

Sincerely yours,


John H. Lee
Product Manager (31)
Antimicrobial Program Branch
Registration Division (H7505C)

Enclosure

PM 31 8

Vc

So

Coastal

Anti-Fou

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS: Flammable. Keep away from heat and open flame.

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

ANTI-FOULING PAINT FOR METAL BOTTOMS: To control the attachment of marine fouling, i.e., barnacles, grass, algae, etc., on steel bottoms in salt and brackish water which would sustain such growth. Not recommended for use on aluminum. A minimum of two coats is recommended for best performance.

Surface Preparation: All surfaces must be dry and cleaned of dirt, dust, oil, rust, loose paint, salt residues, and other contaminants. Steel should be blast-cleaned and must be coated with a suitable primer or anti-corrosive barrier coats. When applied over Barne-Cool System, some discoloration may be evident, this does not affect performance.

Mixing: Before use, power mix or stir the paint until the product is uniform. Stir the paint at intervals during application to maintain uniformity.

Application: Apply by brush, roller or spray. Do not paint in cold or damp weather.

Thinner: Thin slightly with Thinner 7-T-33 when required for application. Use Thinner 7-T-33 for clean-up. Use Thinner 7-T-41 where Air Pollution Regulations are in effect.

Note: Must comply with applicable VOC regulations after thinning.

Dry Time: At 75°F. (24°C.) and 50% R.H., allow at least 4 hour dry time between coats, and a minimum of 8 hours before re-floating. Launching is recommended preferably within 48 hours.

STORAGE AND DISPOSAL

PESTICIDE MISUSE: Do not contaminate water, food or feed by storage or disposal. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative listed at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

46-769 ~~XXXX~~

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS (& DOMESTIC ANIMALS) (SR-1)

PHYSICAL OR CHEMICAL HAZARDS:

Do not use or store near heat or open flame.

CONTAINS ORGANIC SOLVENT

WARNING!



of in accordance with applicable regulations.
PRACTICAL TREATMENT: If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention. If in eyes: Flush with plenty of water. Get medical attention. If on skin: Wash with plenty of soap and water. Get medical attention. If inhaled: Remove victim to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. Get medical attention.

U.O.T. SHIPPING NAME: PAINT
U.O.T. HAZARD CLASS: FLAMMABLE LIQUID
U.O.T. HAZARD IDENTIFICATION NUMBER: UN 1263
Refer to Product Material Safety Data Bulletin, available upon request, for further safety and handling information. OCL 84 (12 85)

AVAILABILITY: CAUSES EYE IRRITATION, HARMFUL IF ABSORBED THROUGH SKIN.
Avoid contact with eyes, skin and clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapors or spray mist. When used in enclosed areas, spraying paint or sanding boat surface, wear appropriate properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable levels. Follow respirator manufacturer's directions for use. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling. Keep container closed - neutral in use. In case of spillage, absorb with inert material and dispose

For Industrial Use
Around a House
Not Sold For Use In
Photochemically

KEEP OUT OF
WARNING! See Pr

NET 5 G

ACCEPTED
with COMMENTS
in EPA Letter Dated:

SEP 26 1990

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended and registered under EPA Reg. No.

8177-40