

PM 31 8111 - 42

# Valspar

## PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS (& DOMESTIC ANIMALS) (SR-1)

### WARNING!

CAUSES EYE IRRITATION. HARMFUL  
IF ABSORBED THROUGH SKIN.

Avoid contact with eyes, skin and clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapors or spray mist. When used in enclosed areas, spraying paint or sanding boat surface, wear appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable levels.

**ENVIRONMENTAL HAZARDS:** This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

**PHYSICAL OR CHEMICAL HAZARDS:** Flammable. Keep away from heat and open flame.

**DIRECTIONS FOR USE:** It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

**ANTI-FOULING PAINT FOR METAL BOTTOMS:** To control the attachment of marine fouling, i.e., barnacles, grass, algae, etc., on steel bottoms in salt and brackish water which would sustain such growth. Not recommended for use on aluminum. A minimum of two coats is recommended for best performance.

**Surface Preparation:** Before application of anti-fouling, all surfaces must be dry and cleaned of dirt, dust, oil, rust, loose paint, salt residues, and other contaminants. Steel must be coated with a suitable primer or anti-corrosive barrier coats.

Follow respirator manufacturer's directions for use. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

**PRACTICAL TREATMENT:** If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention. If in eyes: Flush with plenty of water. Get medical attention. If on skin: Wash with plenty of soap and water. Get medical attention. If inhaled: Remove victim to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. Get medical attention.

8CL-84

**Mixing:** Before use power mix or box the paint until the product is uniform. Stir the paint at intervals during application to maintain uniformity.

**Application:** Apply by brush, roller or spray. Do not paint in cold or damp weather. When used over epoxy base coats, the first coat of anti-fouling should be applied while the epoxy is still in a soft, uncured condition, typically, within 12-16 hours at 75° F (24° C). When this is not practical, apply a tie-coat of 80-R-8 Vinyl Primer, or 83 Series Hi-Build Vinyl within this interval. Anti-fouling may then be applied at any later time.

**Thinning:** Thin slightly with Thinner 7-T-37 when required for application. Use Thinner 7-T-37 for clean-up.

**Coverage:** Apply at a rate that will provide a 2 mil dry film per coat, theoretically 350 sq. ft. per gallon. Actual coverage will vary depending upon application technique, job conditions and type of surface.

**Dry Time:** At 75° F and 50% R.H., allow at least 4 hour dry time between coats, and a minimum of 8 hours before refloating. Where exposed to direct sunlight or high temperatures, launching is recommended no more than 24 hours after application.

D.O.T. SHIPPING NAME: PAINT

D.O.T. HAZARD CLASS: FLAMMABLE LIQUID

D.O.T. HAZARD IDENTIFICATION NUMBER:

UN 1263

Refer to Product Material Safety Data Bulletin, available upon request, for further safety and handling information.

## MARINE COATINGS

## VINYL ANTI-FOULING PAINT

### Dark Brown 59-D-22

ACTIVE INGREDIENTS: Cuprous Oxide

INERT INGREDIENTS:

CONTAINS PETROLEUM DISTILLATES

For Commercial Use Only. Do Not Use In or  
Around a Household or Dwelling (FA-11)



Not Sold For Use in Air Pollution Regulation Areas.  
Photochemically Reactive Per Rule 102. (FR-21)

KEEP OUT OF REACH OF CHILDREN

WARNING! See Precautions Elsewhere on Label

NET 5 GAL. (18.927 Liters)

ML-102 (G-59)



LC34M1 3-87HMS

18820-6001-00

### STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

**Pesticide Disposal:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL:** Triple rinse, (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

The VOC of this paint exceeds  
420 grams/liter (3.5 lbs./gal.)  
SR-6 (6-87)

## 06 59D22

E.P.A. Reg. No. 8177-42  
E.P.A. Est. No. 8177-MD-1

**The Valspar Corporation**  
MAINTENANCE & MARINE COATINGS DEPARTMENT  
MINNEAPOLIS, MN 55415

MEDICAL  
EMERGENCY NO.  
1-800-228-5635

