

OCT 17 1986

The Valspar Corporation  
101 Third Street  
Minneapolis, Minn 55415

Attn: Mr. Brian C. Heath

Subject: Coastal Super Service Antifouling 59-R-7  
EPA Reg. No. 8177-45  
Submission dated October 1, 1986

The draft labels referred to above, submitted in connection with registration under FIFRA is acceptable provided that you:

(1) Submit five (5) copies of your final printed labeling before you release the product for shipment.


If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product bearing the amended labeling constitutes acceptance of these conditions.

A stamped copy of the labeling is enclosed for your records.

Refer to the A-79 enclosure in meeting the final printed label submission requirements. In most cases the final label is the label that will be affixed to the container.

The comments made in our letter of September 9, 1986 are appropriate and must be considered at the next printing of your label.

Sincerely,

  
John H. Lee  
Product Manager 31  
Disinfectants Branch  
Registration Division (TS-767C)

Enclosure



8



Active Ingredient  
 Cuprous Oxide 47.61%  
 Inert Ingredients 52.39%

100.00%

CONTAINS PETROLEUM DISTILLATES

EPA REG. NO. 8177-46 EPA EST. NO. 8177-TX-1



Hi Performance  
 3588 Red Copper

KEEP OUT OF REACH OF CHILDREN

WARNING

See Back Panel For Additional  
 Precautionary Statements

1 Gallon (128 fl. oz.) \$ 7.85

the contents can be harmful or fatal

**PRACTICAL TREATMENT**

**Inhalation:** Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available drink large quantities of water. Avoid alcohol. Get medical attention.

**If in eyes:** Flush with plenty of water. Get medical attention.

**If on skin:** Wash with plenty of soap and water. Get medical attention.

**If inhaled:** Remove victim to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. Get medical attention.

DOT SHIPPING NAME: PAINT  
DOT HAZARD CLASS: FLAMMABLE LIQUID  
DOT HAZARD IDENTIFICATION NUMBER: UN 1263  
Ref. to Prod. & Material Safety Data Bulletin as table  
require further safety and handling information

Cuprous Oxide	47.61%
OTHER INGREDIENTS	52.39%
	100.00%

CONTAINS PETROLEUM DISTILLATES  
NET 5 GAL. (18.927 Liters)

ACCEPTED

NOV 1 1986

8177-45

or marine fouling, i.e., barnacles, green, algae, etc. on steel bottoms in salt and brackish water which would sustain such growth. Not recommended for use on aluminum. A minimum of two coats is recommended for best performance.

**Surface Preparation:** Before application of anti-fouling, all surfaces must be dry and cleaned of dirt, dust, oil, rust, loose paint, salt residues, and other contaminants. Steel must be coated with a suitable primer or anti-corrosive barrier coats.

**Mixing:** Before use, pour mix or box the paint until the product is uniform. Stir the paint at intervals during application to maintain uniformity.

**Application:** Apply by brush, roller, or spray. Do not paint in cold or damp weather.

**Thinning:** Thin slightly with Thinner 7-1-33 when required for application. Use Thinner 7-1-33 for clean-up.

**Coverage:** Apply at a rate that will provide a 2 mil dry film per coat, theoretically 433 sq ft per gallon. Actual coverage will vary depending upon application technique, job conditions and type of surface.

**Dry Time:** At 75°F and 50% RH, allow at least 2 hour dry time between coats, and a minimum of 4 hours before refloating. Where exposed to direct sunlight or high temperatures, launching is recommended no more than 24 hours after application.

The Valspar Corporation  
MAINTENANCE & MARINE COATINGS DEPARTMENT  
MINNEAPOLIS, MN 55415