

US ENVIRONMENTAL PROTECTION AGENCY
OFFICE OF PESTICIDES PROGRAMS
REGISTRATION DIVISION (75-757)
WASHINGTON, DC 20460

EPA REGISTRATION NO.
8177-68

DATE OF REGISTRATION
MAR 14 1989

TERM OF ISSUANCE

NOTICE OF PESTICIDE: REGISTRATION
 REREGISTRATION

(Under the Federal Insecticide, Fungicide,
and Rodenticide Act, as amended)

NAME OF PESTICIDE PRODUCT

Valspar Marine Coatings 60A1000
Hydro Clean Anti-Fouling

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

The Valspar Corporation
1101 Third Street South
Minneapolis, MN 55415

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA section 3(c)(7)(A) provided that you:

1. Submit/cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data.

2. Make the labeling changes listed below before you release the product for shipment:

a. Add the phrase "EPA Registration No. 8177-68."

b. We note that your product contains a red pigment, but your label does not declare a "Basic" color. You may wish to indicate/establish the "Basic" color of your product by/in its basic brand name at the time you amend your registration to include alternate formulations (colors) with their corresponding additional brand names.

3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 enclosure for a further description of final printed labeling.


ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL

BEST AVAILABLE COPY

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.


John H. Lee
Product Manager (31)
Antimicrobial Program Branch
Registration Division (H7504C)

Enclosures

BEST AVAILABLE COPY

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS (& DOMESTIC ANIMALS) (SR-1)



WARNING!

CAUSES IRRITATION. HARMFUL IF ABSORBED THROUGH SKIN.

Avoid contact with eyes, skin and clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapors or spray mist. When used in enclosed areas, spraying paint or sanding boat surface, wear appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable levels. Follow respirator manufacturer's directions for use. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

PRACTICAL TREATMENT: If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention. If in eyes: Flush with plenty of water. Get medical attention. If on skin: Wash with plenty of soap and water. Get medical attention. If inhaled: Remove victim to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. Get medical attention.

5-85 HMS MTS#2

18820-2501-01

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS: Flammable. Keep away from heat and open flame.

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

ANTI-FOULING PAINT FOR METAL BOTTOMS: To control the attachment of marine fouling, i.e., barnacles, grass, algae, etc., on steel bottoms in salt and brackish water which would sustain such growth. Do not use on aluminum. A minimum of two coats is recommended for best performance.

Surface Preparation: Before application of anti-fouling, all surfaces must be dry and cleaned of dirt, dust, oil, rust,

loose paint, salt residues, and other contaminants. Steel must be coated with a suitable primer or anti-corrosive barrier coats.

Mixing: Before use power mix or mix the paint until the product is uniform. Stir the paint at intervals during application to maintain uniformity.

Application: Apply by brush, roll or spray. Contents may be applied by hot spray (temperatures not to exceed 95°F), airless spray or regular cold spray. Apply a full wet coat in a double crosshatch pattern. Do not paint in cold or damp

weather.

Thinning: Normally no thinning required. Where thinning is necessary, use thinner 7-T-33, Xylene


Dry Time: At 70°F and 50% R.H., allow at least 4 hour dry time between coats, and a minimum of 8 hours before refoating

D.O.T. SHIPPING NAME: PAINT


D.O.T. HAZARD CLASS: FLAMMABLE LIQUID

D.O.T. HAZARD IDENTIFICATION NUMBER: UN 1263

Refer to Product Material Safety Data Bulletin, available upon request, for further safety and handling information.



BEST AVAILABLE COPY



Reg no: 8177

Valspar

MARINE COATINGS

60A-1000

HYDRO-CLEAN ANTI-FOULING

ACTIVE INGREDIENT: Cuprous Oxide 40.9%

INERT INGREDIENTS: 59.1%

CONTAINS PETROLEUM DISTILLATES

For Commercial Use Only. Do Not Use In or
Around a Household or Dwelling.

Not Sold For Use In Air Pollution Regulation Areas.
Photochemically Reactive Per Rule 102.

KEEP OUT OF REACH OF CHILDREN

WARNING! See Precautions Elsewhere on Label (FA-22)

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Pesticide Disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse, (or equivalent) then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

The VOC of this paint exceeds
420 grams/liter (3.5 lbs./gal.)
SR-6 (N-87)

NET 5 GALS. (18.927 Liters)

E.P.A. Reg. No. 8177
E.P.A. Est. No. 8177-MD-1

The Valspar Co.
MAINTENANCE & MARINE CO.
MINNEAPOLIS.

000101

BEST AVAILABLE COPY

A
with
in EP
MA
Under the
Fungicide,
amended
registered