


# Severe Weather *r* By ENTERPRISE®

[House & Deck Graphic]

**EXTERIOR**  
**OIL BASE**  
**WATER REPELLENT**



- Water Repellent
- Retards Mildew, Rot & Decay
- Contains Polyurethane
- For Exterior Wood Siding, Shingles, Fences & Trim
- Dries to a Clear Protective Finish
- Contains a UV Screener

*Sunburst  
Graphic*

**UV Resistant**

# ENTERPRISE CLEAR WOOD PRESERVATIVE SIDING & DECK PROTECTOR

**KEEP OUT OF REACH OF CHILDREN**

**WARNING: SEE ADDITIONAL  
PRECAUTIONS ON BACK OF LABEL**

EPA REG. NO. 8177-73

**ACTIVE INGREDIENTS:**

3-Iodo-2-Propynyl Butyl Carbamate.....0.57%

**INERT INGREDIENTS**.....99.43%

**TOTAL**.....100.00%

1 Gallon

Clear 7515-01 3.785 Liters

This product must be used before the expiration date.

Expiration Date: \_\_\_\_\_

**ACCEPTED**  
DEC 23 2003  
Under the Federal Insecticide, Fungicide, and  
Rodenticide Act as amended, for the  
pesticides registered under  
EPA Reg. No. 8177-73

8177-73

12/23/2003

1/2

**GENERAL INFORMATION:**

Severe Weather knows what's best for the exterior of your home. Fortified with polyurethane, this clear protective finish seals exterior wood surfaces, resisting moisture penetration, rotting and decay. Severe Weather exceeds water repellency requirements of the Federal Spec. TT-W-572b, 3.7. It also retards the aging (silvering) process of new wood. An effective fungicide helps to resist mildew while a UV screener works to filter out the sun's rays. (IMPORTANT: Although this product preserves and beautifies wood, it cannot do so indefinitely. When wood first begins to "silver" or darken with age, reapply Severe Weather® Enterprise Clear Wood Preservative after sanding all unweathered and protected areas. This allows greater penetration for the new application of this product. If painting is desired, surface must be well-weathered. Sand protected areas before applying exterior oil base primer. Then paint.)

**Type of Finish:** Clear

**Where to Use:** For use only above-ground on bare exterior wood surfaces – structural lumber, wood siding, decks, shingles, fences, doors, frames, sashes, and porches. No sealers are necessary for frequent dermal contact surfaces.

**Coverage:** Approximately 200 - 400 sq. ft. (18.6 - 37.2 m<sup>2</sup>) per gallon depending upon method of application, porosity and density of wood. Do not thin. Do not tint.

**Drying Time:** Dries to the touch rapidly. Complete drying requires 24 hours. For extra protection, apply a second coat within 48 hours of the first coat.

**Cleanup:** Clean equipment promptly with brush and roller cleaner or mineral spirits.

**Extractive Bleeding:** New as well as old redwood, cedar and Douglas fir woods contain natural water-soluble materials which "bleed" or migrate to the surface. This bleeding is normally reddish brown in fir and cedar and black in redwood. It must be removed with a mild, nonabrasive detergent solution before Enterprise Clear Wood Preservative is applied. Cleaned wood must dry at least 24 hours before applying Enterprise Clear Wood Preservative.

**Surface Preparation:** Clean discolored areas with detergent and water to remove dirt. If discoloration is due to resin bleed, remove by sanding. Dark mildew discoloration may be present in new or old wood. It must be removed before applying this product. Scrub surfaces with a solution of 1 part household bleach and 3 parts water. (Protect eyes and skin while using bleach solution.) Rinse well. Then allow to dry thoroughly. Replace rotted boards and wash surrounding areas with above 1-to-3 solution. (Wood turned darker from mildew must be bleached before application to kill the fungus.) Seal cracks around openings with caulking. Be sure surface is clean and dry. To insure proper penetration of Enterprise Clear Wood Preservative into the wood, smooth new wood must be sanded to remove the mill glaze.

**GENERAL PRECAUTIONS AND RESTRICTIONS:**

DO NOT apply this product in a way that will contact any person or pet.

DO NOT USE on interior surfaces.

DO NOT USE on previously stained, painted, varnished or sealed surfaces or hardboard siding.

DO NOT USE on wood used for food, feed or potable water contact.

DO NOT mix Clear Wood Preservative with any other product.

DO NOT apply in direct sunlight or on days when air or surface temperatures are below 50°F (10°C).

DO NOT use where dairy and farm animals may come into contact with the treated wood.

Cover desirable plants and shrubs to avoid possible injury.

**DIRECTIONS FOR USE:**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Apply this product only as specified on the label.

**Application Instructions:** Stir product thoroughly before using. Apply liberally by brush, roller or spray. Begin application at the corner of a few boards and continue until you reach a window or door frame. IMPORTANT: ALLOW WOOD TO DRY 2 TO 3 DAYS AFTER RAIN BEFORE APPLYING CLEAR WOOD PRESERVATIVE.

**STORAGE AND DISPOSAL:**

**Pesticide Storage:** Store product in original container within locked storage area.

**Pesticide And Container Disposal:** Dispose of container and any unused product by securely wrapping container in several layers of newspaper. Then discard in trash. DO NOT REUSE CONTAINER.

**PRECAUTIONARY STATEMENTS:**

**HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**WARNING:** Causes skin irritation and moderate eye irritation Do not get on skin or on clothing. Avoid contact with eyes. Wear protective clothing, chemical-resistant gloves and protective eyewear (goggles, face shield, or safety glasses) when handling. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Remove and wash contaminated clothing before reuse.

**USER SAFETY RECOMMENDATIONS**

Users should:

- Wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet.
- Remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.

**FIRST AID**

Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

**If on skin or clothing:**

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or doctor for treatment advice.

**If in eyes:**

- Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
- Call a poison control center or doctor for treatment advice.

In case of emergency call toll free 1-888-345-5732.

**NOTE TO PHYSICIAN:** Probable mucosal damage may contraindicate the use of gastric lavage.

**ENVIRONMENTAL HAZARDS:** This pesticide is toxic to fish. Do not apply directly to water or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment washwater or rinsate.

**PHYSICAL AND CHEMICAL HAZARDS:** DO NOT USE, POUR SPILL OR STORE NEAR HEAT OR OPEN FLAME. PROTECT FROM FREEZING.

This product contains less than 720 g/L VOC (6.0 lb./Gal VOS)

ACCEPTED  
DEC 23 2003  
8177-73