



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF
PREVENTION, PESTICIDES
AND TOXIC SUBSTANCES

May 13, 2008

Georgia Anastasiou
Lewis & Harrison Consultant
Agent for
The Valspar Corporation
122 C Street, N.W., Suite 740
Washington, DC 20001

Subject: Notification in Accordance with PR Notice 98-10
Enterprise Clear wood Preservative
EPA Registration Number 8177-73
Application: April 22, 2008
Receipt Date: April 23, 2008

Dear Ms. Anastasiou:

This will acknowledge receipt of your notification, submitted under the provisions of PR Notice 98-10, FIFRA section 3 (c) 9.

Proposed Notification:

- Add marketing language
- Revise directions for use


General Comment:

Based on a review of the material submitted, the following comments apply.

The notification application is acceptable. A copy has been inserted in the file for future reference.

Should you have any questions concerning this letter, please contact me by telephone at (703) 308-6422 or email address at: heyward.adam@epa.gov, or Renae Whitaker telephone at (703) 308-7003 or email address at: whitaker.renae@epa.gov during the hours of 8:00 am to 3:30 pm EST. When submitting information or data in response to this letter, a copy of this letter should accompany the submission to facilitate processing.

Sincerely,



Adam Heyward
Product Manager 34
Regulatory Management Branch II
Antimicrobials Division (7510P)

3 8 13



EPA

United States
Environmental Protection Agency
 Washington, DC 20460

Regist on
 Amendment
 Other: NOTIFICATION

OPP Identifier Number

Application for Pesticide - Section I


1. Company/Product Number 8177-73	2. EPA Product Manager Adam Heyward	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) Enterprise Clear Wood Preservative	PM# 34	
5. Name and Address of Applicant (Include ZIP Code) The Valspar Corporation 1101 Third Street South Minneapolis, MN 55415 <u>PLEASE SEND ALL CORRESPONDENCE TO "CONTACT POINT" LISTED BELOW</u>	6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(I), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section - II

Amendment - Explain below. Final printed labels in response to Agency letter dated _____
 Resubmission in response to Agency letter dated _____ "Me Too" Application
 Notification - Explain below. Other - Explain below

Explanation: Use additional page(s) if necessary. (For Section I and Section II.)
Notification to add marketing language and revise the applications directions to expand the language for coverage area. None of the proposed changes increase the amount of stain being applied and there are no changes in any of the application methods. Accordingly, none of these modifications will affect exposure to the stain.
PLEASE READ COVER LETTER FOR DETAILS.

Notification in Accordance With PR Notice 98-10
This notification is consistent with the provisions of PR Notice 98-10 and EPA regulations at 40 CFR 152.46, and no other changes have been made to the labeling or the confidential statement of formula of this product. I understand that it is a violation of 18 U.S.C. Sec. 1001 to willfully make any false statement to EPA. I further understand that if this notification is not consistent with the terms of PR Notice 98-10 and 40 CFR 152.46, this product may be in violation of FIFRA and I may be subject to enforcement action and penalties under sections 12 and 14 of FIFRA.

Signature:  Date: 4/22/08

Section - III


1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes* <input type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No		<input type="checkbox"/> Metal	<input type="checkbox"/> Plastic
*Certification must be submitted		If "Yes" Unit Packaging wgt.	No. per container	If "Yes" Package wgt.	No. per container
3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container		5. Location of Label Directions <input type="checkbox"/> On Label <input type="checkbox"/> On labeling accompanying product	
6. Manner in Which Label is Affixed to Product <input type="checkbox"/> Lithograph <input type="checkbox"/> Other _____ <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled					

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application)

Name Georgia Anastasiou, Lewis & Harrison 122 C St. NW Suite 740, Washington DC 20001	Title Agent for The Valspar Corporation	Telephone No. (Include Area Code) (202) 393-3903 x19
--	--	--

Certification
 I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.

2. Signature 	3. Title Agent for The Valspar Corporation	6. Date Application Received (Stamped)
4. Typed Name Georgia Anastasiou	5. Date April 22, 2008	

NOTE TO REVIEWER: The headings underlined represent different types of claim sections and are not intended for use on the product label. Language in [] is considered optional or interchangeable.

[Front panel]

- WOOD PRESERVATIVE
- DEEP PENETRATING
- WATER REPELLENT
- SUPERIOR DURABILITY

ENTERPRISE CLEAR WOOD PRESERVATIVE

CLEAR SOLUTION®

[A TRANSLUCENT ~~WOOD~~ OIL FINISH FOR DECKS, SIDING, FENCES AND TRIM]

AUSTRALIAN TIMBER OIL®

[FOR DECKS, RAILINGS, STAIRS AND OUTDOOR FURNITURE]

[THREE WAY OIL PROTECTION. TUNG, LINSEED, ALKYD]

SEMI-TRANSPARENT FINISH

[SEMI-TRANSPARENT OIL]

[SEMI-TRANSPARENT OIL FINISH]

[SEMI-TRANSPARENT PRESERVATIVE]

[ENHANCES THE NATURAL BEAUTY OF WOOD GRAIN]

[PENETRATING WOOD PRESERVATIVE FOR SIDING, FENCES & TRIM]

[PENETRATING OIL THAT ENHANCES THE NATURAL BEAUTY OF WOOD]

[SUPERIOR U.V. PROTECTION FOR WOOD SIDING, TRIM & FENCES]

[SEMI-TRANSPARENT SIDING FINISH]

SEMI-SOLID® SIDING FINISH

[SEMI-SOLID® OIL]

[SEMI-SOLID® OIL FINISH]

[SEMI-SOLID® OIL SIDING FINISH]

[SEMI-SOLID® PRESERVATIVE]

[EXTRA PIGMENTED FOR PROTECTION OF WOOD SIDING, TRIM & FENCES]

[U.V. PROTECTION & WOOD PRESERVATIVE FOR SIDING, FENCES & TRIM]

SEMI-SOLID DECKING FINISH

[DECKING FINISH]

[DECKING OIL]

[DECKING PRESERVATIVE]

[DURABLE SEMI-SOLID FINISH-MADE TO BE WALKED ON]

[DURABLE SEMI-SOLID WOOD PRESERVATIVE-MADE TO BE WALKED ON]

[SEMI-SOLID® FINISH]

[SEMI-SOLID® OIL DECKING FINISH]

NOTE TO REVIEWER: The headings underlined represent different types of claim sections and are not intended for use on the product label. Language in [] is considered optional or interchangeable.

SOLID COLOR SIDING FINISH

[SOLID COLOR OIL]

[SOLID COLOR OIL FINISH]

[SOLID COLOR OIL SIDING FINISH]

[SOLID COLOR PRESERVATIVE]

[LONG LASTING OPAQUE FINISH FOR WOOD SIDING, TRIM & FENCES]

SOLID COLOR DECKING FINISH

[SOLID COLOR OIL DECKING]

[SOLID COLOR OIL DECKING FINISH]

[SOLID COLOR DECKING PRESERVATIVE]

[FOR ALL DECKS, RAILINGS & OUTDOOR FURNITURE]

[FOR ALL DECKS, RAILINGS, STAIRS AND OUTDOOR FURNITURE]

NOTE TO REVIEWER: The headings underlined represent different types of claim sections and are not intended for use on the product label. Language in [] is considered optional or interchangeable.

KEEP OUT OF REACH OF CHILDREN

WARNING!

COMBUSTIBLE LIQUID AND VAPOR

See back panel for additional precautionary statements.

Active Ingredients:

3-Iodo-2-Propynyl Butyl Carbamate.....0.57%

Inert Ingredients.....99.43%

TOTAL.....100.00%

Contains petroleum distillates

EPA Reg. No. 8177-73

EPA Est. No. 8177-MA-001

Net Contents: 1 gallon, 3.78 liters

[Back Panel]

CLEAR SOLUTION®

GENERAL INFORMATION:

Clear Solution is formulated with a blend of resin and oil to provide a natural finish for bare wood. Easy to apply, Clear Solution slightly darkens wood when first applied leaving a flat, translucent-toned finish, which weathers with time to a natural wood hue. For use on new or reconditioned exterior wood only, including decks, siding, shingles, shakes, trim and on log homes.

AUSTRALIAN TIMBER OIL®

GENERAL INFORMATION:

Cabot Australian Timber Oil® is a unique blend of oils originally formulated to protect dense Australian tallowwood, cambara and merbau from extreme exposures. It is a proven translucent oil treatment that is specially formulated for decks and outdoor furniture. Penetrates deep into woods to accentuate natural wood depth and patina. Containing a precise blend of superb-grade linseed oil for maximum penetration, long-oil alkyds for durability and pure Tung oil for color depth and water repellency, it delivers three-way oil protection. In addition, complex translucent iron-oxide pigments are added to ensure a lasting U.V.-absorbing surface rich with color and dimension.

NOTE TO REVIEWER: The headings underlined represent different types of claim sections and are not intended for use on the product label. Language in [] is considered optional or interchangeable.

SEMI-TRANSPARENT FINISH

GENERAL INFORMATION:

Cabot Semi-Transparent Finish is a deep-penetrating, oil based finish that beautifies and protects exterior wood. Water repellent, mildew-resistant, and when properly applied, won't crack, peel or blister. For use on exterior wood siding, shingles, shakes and roofs. Especially effective on rough-sawn surfaces. Not for use on decks.

SEMI-SOLID[®] SIDING FINISH

GENERAL INFORMATION:

Cabot Semi-Solid[®] Finishes are richly pigmented, deep penetrating oil based finishes that provide long lasting beauty and wood protection. These unique finishes provide greater hiding power than semi-transparent finishes, yet their attractive flat finish highlights the natural beauty of the wood's texture. Cabot Semi-Solid Finishes can be used on most types of smooth and rough exterior wood, including siding, shingles, fences, log homes and roofs. They provide excellent results on weathered wood and well-seasoned lumber. Not for use on decks.

SEMI-SOLID DECKING FINISH

GENERAL INFORMATION:

Cabot Decking Finish has an alkyd resin base that provides an extremely tough and scuff-resistant finish. Use this extremely durable finish on all types of wood decking and fencing.

SOLID COLOR SIDING FINISH

GENERAL INFORMATION:

Cabot Solid Color Oil Finish contains a blend of tough alkyd resin and linseed oil and offers tremendous hiding power, yet resists cracking, peeling and blistering. For use on most types of smooth and tough exterior wood, including siding, shingles, shakes and trim. Not for use on decks.

SOLID COLOR DECKING FINISH

GENERAL INFORMATION:

Cabot Solid Color Decking Finish combines maximum color and U.V. protection with a tough alkyd resin. The results are a completely opaque finish that imparts lasting beauty and is formulated to withstand foot traffic and wear. For use on exterior wood decks, railings and outdoor furniture.

NOTE TO REVIEWER: The headings underlined represent different types of claim sections and are not intended for use on the product label. Language in [] is considered optional or interchangeable.

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Apply this product only as specified on the label.

Application Instructions:

CLEAR SOLUTION®

Stir product thoroughly before using. Apply only with a natural bristle brush or pad to horizontal surfaces. Apply with natural bristle brush or professional spray equipment on vertical surfaces. Start at one edge and follow through to the end of the boards to avoid lap marks.

AUSTRALIAN TIMBER OIL®

Stir thoroughly before and occasionally while using. Intermix containers of the same color. Optimal results are achieved by using a pure lambswool applicator. Apply to small sections at a time (2-3 boards) to avoid lap marks. One coat is recommended.

SEMI-TRANSPARENT FINISH

Shake before and stir thoroughly during use. Intermix all containers of the same color. Apply with a natural bristle brush or professional spray equipment. When spraying, always back-brush immediately to ensure uniformity. Start at one edge and follow through to a logical break. One coat is recommended.

SEMI-SOLID® SIDING FINISH

Shake before and stir thoroughly during use. Intermix all containers of the same color. Apply with natural bristle brush or professional spray equipment. When spraying, always back-brush immediately to ensure uniformity. Start at one edge and follow through to a logical break. One coat is recommended.

SEMI-SOLID DECKING FINISH

Stir thoroughly before and occasionally during use. Intermix all containers of the same color. This product must be applied evenly and only with a brush. Apply stain to small sections at a time. To avoid lap marks, start at one edge and follow through to the end of the boards. One coat is recommended.

SOLID COLOR SIDING FINISH

Shake before and stir thoroughly during use. Intermix all containers of the same color. Apply with a high-quality natural bristle brush or professional spray equipment. When spraying, always back-brush immediately to ensure uniformity. Start at one edge and follow through to a logical break. A one-coat application is recommended.

SOLID COLOR DECKING FINISH

Stir thoroughly before and during use. Intermix all containers of the same color. Apply with natural bristle brush, professional spray equipment or roller. When spraying or rolling, always back-brush immediately to ensure uniformity. A one-coat application is generally sufficient to provide protection and longevity. The application of a second coat

NOTE TO REVIEWER: The headings underlined represent different types of claim sections and are not intended for use on the product label. Language in [] is considered optional or interchangeable.

will yield maximum coverage and performance, particularly when using dark colors.
Apply second coat within 48 hours of first coat.

Type of Finish: Clear
[Pigmented]

Where to Use:

CLEAR SOLUTION®

For use only aboveground on new or reconditioned exterior wood, including decks, siding, shingles, shakes, trim and on log homes.

AUSTRALIAN TIMBER OIL®

Decks, railings, stairs and outdoor furniture.

SEMI-TRANSPARENT FINISH

For use on exterior wood siding, shingles, shakes and roofs.

SEMI-SOLID® SIDING FINISH

For use on most types of smooth and rough exterior wood, including siding, shingles, fences, log homes and roofs.

SEMI-SOLID DECKING FINISH

For use on all types of wood decking and fencing.

SOLID COLOR SIDING FINISH

For use on most types of smooth and tough exterior wood, including siding, shingles, shakes and trim.

SOLID COLOR DECKING FINISH

For use on exterior wood decks, railings and outdoor furniture.

~~Coverage: On smooth surfaces, approximately 400-500 sq. ft. (37.2-46.4 m²) per gallon; on rougher surfaces 250-350 sq. ft. (23.2-32.5 m²) per gallon depending upon method of application, porosity and density of wood. Do not thin.~~

CLEAR SOLUTION®

On smooth surfaces, approximately 400-600 sq.ft. (37.2-55.7m²) per gallon; on rough surfaces, 200-300 sq.ft. (18.6-27.9m²) per gallon.

AUSTRALIAN TIMBER OIL®

On smooth surfaces, approximately 400-600 sq.ft. (37.2-55.7m²) per gallon; on rough surfaces, 250-350 sq.ft. (23.2-32.5m²) per gallon.

SEMI-TRANSPARENT FINISH, SEMI-SOLID® SIDING FINISH and SOLID COLOR SIDING FINISH

NOTE TO REVIEWER: The headings underlined represent different types of claim sections and are not intended for use on the product label. Language in [] is considered optional or interchangeable.

On smooth surfaces, approximately 450-650 sq.ft. (41.8-60.4m²) per gallon; on rough surfaces, 200-300 sq.ft. (18.6-27.9m²) per gallon.

SOLID COLOR DECKING FINISH

On smooth surfaces, approximately 400-500 sq.ft. (37.2-46.4m²) per gallon; on rough surfaces, 250-350 sq.ft. (23.2-32.5m²) per gallon.

SEMI-SOLID® DECKING FINISH

Covers approximately 400-500sq.ft. (37.2-46.4m²) per gallon.

Drying Time:

CLEAR SOLUTION® and AUSTRALIAN TIMBER OIL®

Approximately 24 hours depending on temperature and humidity.

SEMI-TRANSPARENT FINISH, SEMI-SOLID® SIDING FINISH, SOLID COLOR SIDING FINISH and SOLID COLOR DECKING FINISH

Approximately 24-48 hours depending on temperature and humidity.

SEMI-SOLID DECKING FINISH

Approximately 8 hours depending on temperature and humidity.

Cleanup: Clean equipment with mineral spirits.

Surface Preparation: Be sure surface is free of all dirt, mildew stains and loose wood fibers. Surfaces must be sound and absolutely dry (moisture content below 15%). Finish must be able to penetrate wood surface. Prepare unpainted weathered wood with Cabot Problem-Solver® Wood Cleaner or Wood Brightener. Previously stained surfaces must be stripped with Cabot Wood Strippers.

GENERAL PRECAUTIONS AND RESTRICTIONS:

DO NOT apply this product in a way that will contact any person or pet.

DO NOT USE on interior surfaces.

DO NOT USE on wood used for food, feed or potable water contact.

DO NOT apply in direct sunlight or on days when air or surface temperatures are below 50°F (10°C).

DO NOT use where dairy and farm animals may come into contact with the treated wood.

Cover desirable plants and shrubs to avoid possible injury.

PRECAUTIONARY STATEMENTS:

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING: Causes skin irritation and moderate eye irritation. Do not get on skin or on clothing. Avoid contact with eyes. Wear protective clothing, chemical-resistant gloves and protective eyewear (goggles, face shield, or safety glasses) when handling. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, or using tobacco. Remove and wash contaminated clothing before reuse.

NOTE TO REVIEWER: The headings underlined represent different types of claim sections and are not intended for use on the product label. Language in [] is considered optional or interchangeable.

USER SAFETY RECOMMENDATIONS

Users should:

- Wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet.
- Remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.

FIRST AID

Have the product container or label with you when calling a poison control center or doctor, or going for treatment.

If on skin or clothing:	<ul style="list-style-type: none"> • Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15-20 minutes. • Call a poison control center or doctor for treatment advice.
If in eyes:	<ul style="list-style-type: none"> • Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. • Call a poison control center or doctor for treatment advice.

In case of emergency call toll free 1-888-345-5732.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

Warning: This product contains chemicals known to the State of California to cause cancer.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not apply directly to water or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when disposing of equipment washwater or rinsate.

PHYSICAL AND CHEMICAL HAZARDS: DO NOT USE, POUR SPILL OR STORE NEAR HEAT OR OPEN FLAME. PROTECT FROM FREEZING.

NOTICE --- SPONTANEOUS COMBUSTION HAZARD: RAGS, STEEL WOOL OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED, IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED WATER-FILLED METAL CONTAINER.

This product contains less than 350 g/l VOC (2.9 lb/gal VOS)

STORAGE AND DISPOSAL:

Pesticide Storage: Store product in original container within locked storage area.

Pesticide and Container Disposal: Dispose of container and any unused product by securely wrapping container in several layers of newspaper. Then discard in trash. DO NOT REUSE CONTAINER.

13 8 13

NOTE TO REVIEWER: The headings underlined represent different types of claim sections and are not intended for use on the product label. Language in [] is considered optional or interchangeable.

LIMITED WARRANTY

If this product does not perform as stated on the label after you apply it according to label directions, Valspar will either replace this product or refund its purchase price, at its option. Valspar disclaims all other implied or express warranties. Valspar will not provide or pay for labor for removal or application of the product. This warranty excludes all incidental or consequential damages. This warranty gives you specific legal rights, and you may have other rights which vary from state to state.

Cabot®
The Valspar Corporation
Newburyport, MA 01950
© 2007 Valspar