

PM31

8177-78

1 of 4

US ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (TS-767) WASHINGTON, DC 20460	EPA REGISTRATION NO. 177-76	DATE OF ISSUANCE <b>OCT 23 1981</b>
	TERM OF ISSUANCE	
	NAME OF PESTICIDE PRODUCT METHYL-1,1,1-TRICHLORO-2,2,2-TRIFLUOROETHANE GARDOLIN 2.5% SOL	

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

The Valpar Corporation  
 1101 Third Street South  
 Minneapolis, MN 55415

**NOTE:** Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is subject to the data requirements specified in the January 31, 1985 Data Call-In Notice on Tributyltin, the July 29, 1986 Data Call-In Notice on Tributyltin, the March 22, 1989 Data Call-In Notice for TBT Monitoring and Product Efficacy Data, and the Registration Data Requirements Package for products containing TBT issued in 1990.

1. This registration is subject to the data requirements specified in the January 31, 1985 Data Call-In Notice on Tributyltin, the July 29, 1986 Data Call-In Notice on Tributyltin, the March 22, 1989 Data Call-In Notice for TBT Monitoring and Product Efficacy Data, and the Registration Data Requirements Package for products containing TBT issued in 1990.

In addition, the data requirements specified in the January 31, 1985 Data Call-In Notice on Tributyltin, the July 29, 1986 Data Call-In Notice on Tributyltin, the March 22, 1989 Data Call-In Notice for TBT Monitoring and Product Efficacy Data, and the Registration Data Requirements Package for products containing TBT issued in 1990 are among the data requirements applicable to your registration and for which you are required to select a compliance method of compliance and to inform the Agency of such selection and to comply with all deadlines on a schedule consistent with that required of other registrants of similar products as required by FIFRA Section 3(c)(7)(A).

This registration is subject to the Data Call-In requirements including, but not limited to, those specified in the January 31, 1985 Data Call-In Notice on Tributyltin, the July 29, 1986 Data Call-In Notice on Tributyltin, the March 22, 1989 Data Call-In Notice for TBT Monitoring and Product Efficacy Data, and the Registration Data Requirements Package for products containing TBT issued in 1990.

**BEST AVAILABLE COPY**

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL	DATE
---------------------------------	------

2. Make the labeling change listed below before your release the product for shipment.

- Add the phrase "EPA Registration No. 8177-78"

3. Before you release the product for shipment bearing the EPA registered labeling, you must submit an amended Confidential Statement of Formula for your product which demonstrates that your product is within the certified limits for TBT release rate which places it within the release rate limit imposed by the Organotin Antifouling Paint Control Act of 1988. Your product was certified as being within the OAPCA limit by the Agency in its letter dated May 28, 1991.

"The release rate data submitted is accepted for certification purposes. Hydro-Clean O.M.P. Antifouling Paint 64SAF4267 Red has a certified average release rate of 3.54  $\mu\text{g}/\text{cm}^2/\text{day}$ ."

4. Submit five (5) copies of your final printed labeling before you release the product for shipment.

A stamped copy of the label is enclosed for your records.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product bearing the final labeling approved as part of your conditional registration constitutes acceptance of these conditions.

If you have any questions concerning this letter, please contact Marshall Swindell at (703) 557-6908.

Sincerely yours,



John H. Lee  
Product Manager 31  
Antimicrobial Programs Branch  
Registration Division (H7505C)

**BEST AVAILABLE COPY**

# Vals

## RESTRICTED USE

Due to Toxicity to Aquatic Organisms  
For sale only to certified applicators  
for use only by certified applicators  
persons under the direct supervision  
(at the work site) of certified applicators

## HYDRO-CLEAN ANTIFOULING 64SAF420

Active Ingredient: Tributyltin Methacrylate  
Inert Ingredients: .....  
Total Tin Content: .....

CONTAINS PETROL

KEEP OUT OF REACH OF CHILDREN

**DANGER!** See Precautions

### NET 5 GAL.

### STORAGE AND DISPOSAL

**Storage:** Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

**Pesticide Disposal:** Paint chips, spent abrasives, and any other waste materials from removal of old paint must be disposed of in a sanitary landfill (or if required by Federal, State or local regulations, handled as a hazardous waste).

2. If possible, use all of the contents by application according to label instructions. Manage excess paint, rinseate, and other application wastes in accordance with Federal, State, and local requirements. Consult your state pesticide or Environmental control agency, nearest EPA Regional Office, or the RCRA/Superfund Hotline (800-424-9346) for waste disposal guidance.

**Container Disposal:** Triple rinse container if intended for recycling or reconditioning. Empty paint containers with small amounts of dried residue must be disposed of in a sanitary landfill (or if required by Federal, State or local regulations, handled as a hazardous waste).

**DIRECTIONS FOR USE:** It is a violation of Federal law to use this product in a manner inconsistent with its labelling. It is unlawful to use this product on nonaluminum hulled vessels less than 82 feet (25 meters) in length (on deck), except for the outboard motor or lower drive unit of such vessel.

Users must comply with all applicable OSIRA requirements.

Hydro-Clean O.M.P. is an Antifouling paint of the self polishing variety.

It may be applied by brush, roller or spray to steel vessels operating in fresh and/or salt water and subject to attack by barnacles, algae, tube worms, and other fouling organisms.

**SURFACE PREPARATION:** Clean surface thoroughly of grease, oil, loose paint, dirt, mildew, rust scale or any other foreign material.

**PRIMING:** A Jotun/Valspar primer must be applied to bare newly sandblasted, or porous surfaces before painting.

Always apply paint to a dry surface.

Stir Paint thoroughly from the bottom.

\*For Further Use Directions See The Technical Data Bulletin\*.

**IMPORTANT:** If it is necessary to paint under unusual conditions, call your Jotun/Valspar representative for technical service.

D.O.T. SHIPPING NAME: PAINT  
D.O.T. HAZARD CLASS: FLAMMABLE LIQUID  
D.O.T. HAZARD IDENTIFICATION NUMBER:  
UN 1263

RESTRICTED USE COPY

ACCEPTED  
with COMMENTS  
by EPA Letter Dated

OCT 23 1991

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act  
as amended, for the pesticide  
registered under EPA Reg. No.  
8177-78

061 23 1981

Under the Federal Insecticide, Fungicide, and Rodenticide Act

amended, for the pesticide while spraying paint or sanding boat surface, registered under FPA Reg. No. 8177-78. Approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

Avoid breathing (vapor, spray mist, dust or chips from sanding). Wash thoroughly with soap and water after handling and before eating or smoking. Use with adequate ventilation.

respiration. Probable mouth. Get medical attention. C 73 PHYSICIAN. Probable oral contact may contraindicate the use of gastric lavage.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to aquatic organisms including fish and shellfish. Do not apply directly to water. Do not allow chips and dust generated during paint removal to enter water.

PHYSICAL AND CHEMICAL HAZARDS: Flammable. Keep away from heat and open flame.

The VOC of this paint exceeds 420 grams/liter (3.5 lbs./gal.) SR-6 (6-87)

For Commercial Use Only. Do Not Use In or Around a Household or Dwelling. Not For Residential Use. (FR 11.3700) Not Sold For Use In Air Pollution Regulation Areas. Photochemically Reactive Per Rule 102. (FR 21.3700)

06-67SAF4267

EPA Reg. No. 8177-78  
EPA Est. No. 8177-MD-1

The Valspar Corporation  
MAINTENANCE & MARINE COATINGS DEPARTMENT  
MINNEAPOLIS, MN 55415

MEDICAL  
EMERGENCY NO.  
1-800-228-5635

BEST AVAILABLE COPY