

U.S. ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (75-767) WASHINGTON, DC 20460	EPA REGISTRATION NO. 8177-82 TERM OF ISSUANCE	DATE OF ISSUANCE JUL 11 1994
NOTICE OF PESTICIDE: <input type="checkbox"/> REGISTRATION <input type="checkbox"/> REREGISTRATION <i>(Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)</i>	NAME OF PESTICIDE PRODUCT Jotun Valspar Marine Coatings 60A2000 Red Hydro Clean Anti- Fouling Low VOC	
NAME AND ADDRESS OF REGISTRANT (Include ZIP code) <div style="text-align: center;"> <p>The Valspar Corporation 1101 Third St. South Minneapolis, MN 55415</p> </div>		
NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.		
<p>On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.</p> <p>A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.</p> <p>Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.</p> <p style="text-align: center;">This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:</p> <ol style="list-style-type: none"> 1. Submit/cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data; and submit acceptable responses required for reregistration of your product under FIFRA section 4. 2. Make the labeling changes listed below before you release the product for shipment: <ol style="list-style-type: none"> a. Add the phrase "EPA Registration No. 8177-82". b. The signal word: Warning and the heading: Keep out of Reach of children must be of the appropriate type size, ie 18 points and 12 points respectively. (based upon the label size submitted) c. The heading: Storage and Disposal must also be a minimum of 12 points. <p><input type="checkbox"/> ATTACHMENT IS AVAILABLE</p>		
SIGNATURE OF APPROVING OFFICIAL		DATE

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

- 2 -

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



Marshall Swindell
Acting Product Manager (31)
Antimicrobial Program Branch
Registration Division (H7505C)

CONCURRENCES

SYMBOL								
QUANTITY								
DATE								

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS & DOMESTIC ANIMALS**

WARNING!

CAUSES EYE IRRITATION. HARMFUL IF ABSORBED THROUGH SKIN

Avoid contact with eyes, skin and clothing. Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat. May be fatal if swallowed or inhaled. Do not breathe vapors or spray mist. When used in enclosed areas, spraying paint or sanding boat surface, wear appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates vapor/mist levels are below applicable levels.

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS: Do not use or store near heat or open flame.

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

ANTI-FOULING PAINT FOR METAL BOTTOMS: To control the attachment of marine fouling, i.e., barnacles, grass, algae, etc., on steel hulls on boats and vessels ONLY, in salt and brackish water which would sustain such growth. Not recommended for use on aluminum. A minimum of two coats is recommended for best performance.

Surface Preparation: Before application of anti-fouling, all surfaces must be dry and cleaned of dirt, dust, oil, rust, loose paint, salt residues, and other contaminants. Steel must be coated with a suitable primer or anti-corrosive barrier coats

Follow respirator manufacturer's directions for use. Remove contaminated clothing, and wash before reuse. Wash thoroughly with soap and water after handling.

STATEMENT OF PRACTICAL TREATMENT: If swallowed, drink promptly a large quantity of milk, egg whites, or plain solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention. If in eyes: flush with plenty of water. Get medical attention. If on skin: wash with plenty of soap and water. Get medical attention. If inhaled: remove victim to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. Get medical attention.

Mixing: Before use power mix or box the paint until the product is uniform. Stir the paint at intervals during application to maintain uniformity.

Application: Apply by brush, roll or spray. Contents may be applied by hot spray (temperatures not to exceed 95°F.), airless spray or regular cold spray. Apply a full wet coat in a double crosshatch pattern. Do not paint in cold or damp weather.

Thinning: Normally no thinning required. Where thinning is necessary, use thinner 7-T-33, Xylene.

Dry Time: At 70°F., 50% R.H., allow at least 4 hours dry time between coats and a minimum of 8 hours before refloating.

D.O.T. SHIPPING NAME: PAINT
D.O.T. HAZARD CLASS: FLAMMABLE LIQUID
D.O.T. HAZARD IDENTIFICATION NUMBER: UN 1263

Refer to Product Material Safety Data Bulletin available upon request, for further safety and handling information.

MARINE C

60A200

HYDRO CLEAN

LOW

ACTIVE INGREDIENT: Cup
INERT INGREDIENTS: . . .

KEEP OUT OF REACH OF CHILDREN

WARNING
CONTAINS PETROL
For Commercial Use
In or Around a House

Not Sold for Use in Air
Photochemically Resistant

See back panel for additional information

Under the Federal Insecticide, Fungicide, and Rodenticide Act, amended, for the label registered under EPA Reg. No.

ACCEPTED
with COMMENTS
to EPA Label Draft
8177-82
JUL 11 1994

NET CONTENTS 5

BEST AVAILABLE COPY

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Keep container closed when not in use. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

Pesticide Disposal: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse, (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

The VOC of this paint is
330 grams/liter (2.75 lbs./gal)

SR-16 (8-92)

06 - 60A2000

E.P.A. Reg. No. 8177-

E.P.A. Est. No. 8177-TX-2

The Valspar Corporation
MAINTENANCE & MARINE COATINGS DEPARTMENT
MINNEAPOLIS, MN 55415



The Valspar Corporation
MAINTENANCE & MARINE COATINGS DEPARTMENT
MINNEAPOLIS, MN 55415

BEST AVAILABLE COPY