



MFG. FOR CARBOLINE COMPANY  
350 HANLEY INDUSTRIAL CT., ST. LOUIS, MO 63144

ACCEPTED  
AUG 29 1975  
Under the Federal Insecticide,  
Fungicide, and Rodenticide Act,  
as amended, for the pesticide  
registered under  
EPA Reg. No. 8186-3

# CARBOLINE® TROPICAL ANTI-FOULING *Comments* RED AD 1023

FOR USE IN COMMERCIAL SHIPYARDS ONLY

**CAUTION: Flammable Liquid**  
Flash Point 79° F  
(Closed Cup)  
Keep away from heat or open  
flame.

CARBOLINE AD 1023	
Active Ingredients:	
Copper	0.5%
Cuprous Oxide	26.5%
Inert Ingredients:	73.0%
TOTAL	100.0%
Net Contents 5 Gallons or 18.9 Liters	

Do Not reuse container.  
Destroy when Empty.  
Do Not contaminate water  
by cleaning of equipment,  
or disposal of wastes.

**CAUTION:** Contains flammable solvents. Keep away from sparks and open flames. In confined areas, workmen must wear fresh airline respirators. Hypersensitive persons should wear gloves or use protective cream. All electric equipment and installations should be made and grounded in accordance with the National Electrical Code. Workmen should be required to use non-ferrous tools and to wear conductive and non-sparking shoes in areas where explosion hazards exist.

## CAUTION

KEEP OUT OF REACH OF CHILDREN

Harmful if Swallowed  
Contains Petroleum  
Distillates, Ketones and  
Alcohol

EPA Reg. No. 8186-3  
EPA Est. No.

**CAUTION:** If swallowed, do not induce vomiting. Call Physician immediately. Use with adequate ventilation. Avoid contact with skin, eyes and breathing of vapor or spray mist. Close container after use. Wash after handling. May be absorbed through skin. In case of skin contact, remove contaminated clothing and immediately wash with soap and water; wash clothes before reuse. In case of eye contact, flush thoroughly with water. Get medical attention if irritation persists. Avoid storage near food or feed products.

Directions for use: See Application Instructions.  
Designed for use on ship or boat bottoms.

**Warranty:** Our recommendations for use of this product are based upon tests believed to be reliable. The use of this product being beyond the control of the manufacturer, no guarantee, expressed or implied, is made as to the effects of such or the results to be obtained if not used in accordance with directions or established safe practice. The buyer must assume all responsibility, including injury or damage, resulting from its misuse as such, or in combination with other materials.



MFG. FOR CARBOLINE COMPANY  
300 HANLEY INDUSTRIAL CT., ST LOUIS, MO. 63144

# CARBOLINE® TROPICAL ANTI-FOULING RED AD 1023

FOR USE IN COMMERCIAL SHIPYARDS ONLY

**CAUTION: Flammable Liquid**  
Flash Point 79° F  
(Closed Cup)  
Keep away from heat or open  
flame.

## CAUTION

KEEP OUT OF REACH OF CHILDREN

**CAUTION:** If swallowed, do not induce vomiting. Call Physician immediately. Use with adequate ventilation. Avoid contact with skin, eyes and breathing of vapor or spray mist. Close container after use. Wash after handling. May be absorbed through skin. In case of skin contact, remove contaminated clothing and immediately wash with soap and water; wash clothes before reuse. In case of eye contact, flush thoroughly with water. Get medical attention if irritation persists. Avoid storage near food or feed products.

CARBOLINE AD 1023	
Active Ingredients:	
Copper	0.5%
Cuprous Oxide	26.5%
Inert Ingredients:	73.0%
TOTAL	100.0%
Net Contents 5 Gallons or 18.9 Liters	

Harmful if Swallowed  
Contains Petroleum  
Distillates, Ketones and  
Alcohol

EPA Reg. No. 8186-3  
EPA Est. No.

Directions for use: See Application Instructions.  
Designed for use on ship or boat bottoms.

Do Not reuse container.  
Destroy when Empty.  
Do Not contaminate water  
by cleaning of equipment,  
or disposal of wastes.

**CAUTION:** Contains flammable solvents. Keep away from sparks and open flames. In confined areas, workmen must wear fresh airline respirators. Hypersensitive persons should wear gloves or use protective cream. All electric equipment and installations should be made and grounded in accordance with the National Electrical Code. Workmen should be required to use non-ferrous tools and to wear conductive and non-sparking shoes in areas where explosion hazards exist.

Warranty: Our recommendations for use of this product are based upon tests believed to be reliable. The use of this product being beyond the control of the manufacturer, no guarantee, expressed or implied, is made as to the effects of such or the results to be obtained if not used in accordance with directions or established safe practice. The buyer must assume all responsibility, including injury or damage, resulting from its misuse as such, or in combination with other materials.

*Handwritten note:* Adm. Tropical Anti-Fouling

ACCEPTED WITH COMMENTS