



MFG. FOR CARBOLINE COMPANY  
350 HANLEY INDUSTRIAL CT., ST. LOUIS, MO 63144

# POLYCLAD® ANTI-FOULING RED 1240-19

FOR USE IN COMMERCIAL SHIPYARDS ONLY

**CAUTION: Flammable Liquid**  
Flash Point 90° F  
(Closed Cup)  
Keep away from heat or open flame.

POLYCLAD 1240-19	
Active Ingredients:	
Copper	0.3%
Cuprous Oxide	16.0%
Inert Ingredients:	83.7%
TOTAL	100.0%
Net Contents 5 Gallons or 18.9 Liters	

Do Not reuse container.  
Destroy when Empty.  
Do Not contaminate water  
by cleaning of equipment,  
or disposal of wastes.

**CAUTION:** Contains flammable solvents. Keep away from sparks and open flames. In confined areas, workmen must wear fresh air line respirators. Hypersensitive persons should wear gloves or use protective cream. All electrical equipment and installations should be made and grounded in accordance with the National Electrical Code. Workmen should be required to use non-ferrous tools and to wear conductive and non-sparking shoes in areas where explosion hazards exist.

## CAUTION

KEEP OUT OF REACH OF CHILDREN

Harmful if Swallowed  
Contains Petroleum  
Distillates, Ketones and  
Alcohol

EPA Reg. No. 8186-5  
EPA Est. No.

**CAUTION:** If swallowed, do not induce vomiting. Call Physician immediately. Use with adequate ventilation. Avoid contact with skin, eyes and breathing of vapor or spray mist. Close container after use. Wash after handling. May be absorbed through skin. In case of skin contact, remove contaminated clothing and immediately wash with soap and water; wash clothes before reuse. In case of eye contact, flush thoroughly with water. Get medical attention if irritation persists. Avoid storage near food or feed products.

Directions for use: See Application Instructions.  
Designed for use on ship or boat bottoms.

Warranty: Our recommendations for use of this product are based upon tests believed to be reliable. The use of this product being beyond the control of the manufacturer, no guarantee, expressed or implied, is made as to the effects of such or the results to be obtained if not used in accordance with directions or established safe practice. The buyer must assume all responsibility, including injury or damage, resulting from its misuse as such, or in combination with other materials.



MFG. FOR CARBOLINE COMPANY  
350 HANLEY INDUSTRIAL CT. ST. LOUIS, MO 63144

# POLYCLAD® ANTI-FOULING RED 1240-19

FOR USE IN COMMERCIAL SHIPYARDS ONLY

**CAUTION: Flammable Liquid**  
Flash Point 90° F  
(Closed Cup)  
Keep away from heat or open  
flame.

POLYCLAD 1240-19  
Active Ingredients:  
Copper 0.3%  
Cuprous Oxide 16.0%  
Inert Ingredients: 83.7%  
TOTAL 100.0%  
Net Contents 5 Gallons or  
18.9 Liters

Do Not reuse container.  
Destroy when Empty.  
Do Not contaminate water  
by cleaning of equipment,  
or disposal of wastes.

**CAUTION:** Contains flammable solvents. Keep away from sparks and open flames. In confined areas, workmen must wear fresh airline respirators. Hypersensitive persons should wear gloves or use protective cream. All electric equipment and installations should be made and grounded in accordance with the National Electrical Code. Workmen should be required to use non-ferrous tools and to wear conductive and non-sparking shoes in areas where explosion hazards exist.

## CAUTION

KEEP OUT OF REACH OF CHILDREN

Harmful if Swallowed  
Contains Petroleum  
Distillates, Ketones and  
Alcohol

EPA Reg. No. 8186-5  
EPA Est. No.

**CAUTION:** If swallowed, do not induce vomiting. Call Physician immediately. Use with adequate ventilation. Avoid contact with skin, eyes and breathing of vapor or spray mist. Close container after use. Wash after handling. May be absorbed through skin. In case of skin contact, remove contaminated clothing and immediately wash with soap and water; wash clothes before reuse. In case of eye contact, flush thoroughly with water. Get medical attention if irritation persists. Avoid storage near food or feed products.

Directions for use: See Application Instructions.  
Designed for use on ship or boat bottoms

**Warranty:** Our recommendations for use of this product are based upon tests believed to be reliable. The use of this product being beyond the control of the manufacturer, no guarantee, expressed or implied, is made as to the results, such or the results to be obtained if not used in accordance with directions or established safe practice. The user must assume all responsibility, including injury or damage, resulting from its misuse as such, or in combination with other materials.