001 1975

Une section of sections, and sections of the section of the sectio



MFG. FOR CARBOLINE COMPANY

350 HANLEY INDUSTRIAL CT, ST LOUIS, MO 63144

EPA Reg. No. SISE-6 Convivered

CARBOLINE SUPER ®TROPICAL ANTI-FOULING BLACK 1240-18

FOR USE IN COMMERCIAL SHIPYARDS ONLY

DANGER: Flammable Liquid

Flash Point 70° F

(Closed Cup)

Keep away from heat or open
flame.

CARBOLINE 1240-18
Active Ingredients:
 Tri-n-butyltin Fluoride 16.0%
 Bis (tri-n-butyltin) Oxide 3.5%
Inert Ingredients: 80.5%
TOTAL 100. %
Net Contents 5 Gallons or

Do Not reuse container.

Destroy when Empty.

Do Not contaminate water by cleaning of equipment, or disposal of wastes.

18.9 Liters

DANGER

KEEP OUT OF REACH OF CHILDREN

May be Fatal if Swallowed

May cause eye damage

May cause skin irritation

Contains Petroleum

Distillates, Ketones and

Alcohol

EPA Reg No 8186-6 EPA Est No. DANGER: If swallowed, do not induce vomiting. Call Physician immediately. Use with adequate ventilation. Avoid contact with skin, eyes and breathing of vapor or spray mist. Wear goggles or face shield when handling. Close container after use. Wash after handling. May be absorbed through skin. In case of skin contact, remove contaminated clothing and immediately wash with soap and water; wash clothes before reuse. In case of eye contact, flush thoroughly with water. Get medical attention if irritation persists. Avoid storage near food or feed products.

Directions for use: See Application Instructions.

Designed for use on ship or boat bottoms.

Warranty: Our recommendations for use of this product are based upon tests believed to be reliable. The use of this product being beyond the control of the manufacturer, no guarantee, expressed or implied, is made as to the effects of such or the results to be obtained if not used in accordance with directions or established safe practice. The buyer must assume all responsibility, including injury or damage, resulting from its misuse as such, or in combination with other materials.

DANGER: Contains flammable solvents. Keep away from sparks and open flames. In confined areas, workmen must wear fresh airline respirators. Hypersensitive persons should wear gloves or use protective cream, All electric equipment and installations should be made and grounded in accordance with the National Electrical Code. Workmen should be required to use non-ferrous tools and to wear conductive and non-sparking shoes in areas where explosion hazards exist.