

Reg # 8186-15

PM-32

131

BLACK 0900/JAN 90

C-FLEX 121 ANTIFOULING


WARNING !

0A0000M/5 GALLON(05)

MIL-P-15931B FORMULA 121-63

095704

DIRECTIONS FOR USE



It is a violation of Federal law to use this product in a manner inconsistent with it's labeling.

FOR COMPLETE APPLICATION INSTRUCTIONS, REFER TO PRODUCT DATA SHEET OR CONTACT CARBOLINE TECHNICAL SERVICE

SURFACE PREPARATION: Surfaces should be coated with non-conductive anti-corrosive coating prior to applying antifouling. Wooden surfaces should be dry and free of old loose paint. Remove all surface contaminants. Be sure previous coating is thoroughly cured. Be certain surface is dry prior to coating.

MIXING: Power mix to a uniform consistency.

RECOMMENDED DRY FILM THICKNESS PER COAT: 2.5 mils

THINNING: May be thinned up to 10% by volume with Thinner #8. Use of thinners other than those supplied or approved may adversely affect product performance and void product warranty, whether express or implied.

APPLICATION TEMPERATURES: Material: 55F minimal, 80F maximum, Surface: 50F minimal, 120F maximum. Do not apply coating if difference between surface temperature and dew point is less than 5F.

CLEANUP, STORAGE AND DISPOSAL: Use Thinner #2 or any thinner recommended above. Equipment should be cleaned immediately. NOTE: Do not contaminate water, food or feed by storage or cleaning of equipment or disposal of wastes. Open dumping is prohibited. Pesticide, spray mixture, or residue that cannot be used or chemically reprocessed should be disposed of according to procedures approved by Federal, State or local disposal authorities. Triple rinse container and dispose of in an approved landfill or bury in a safe place. Consult Federal, State or local disposal authorities for approved alternative procedures. Store indoors. Temperature: 40-110F Humidity: 0-100%

SHELF LIFE: 24 months

DATE 8/83

**CARBOLINE COMPANY 350 HANLEY INDUSTRIAL COURT ST. LOUIS, MO 63144
PHONE: 314-644-1000. CHEMTREC EMERGENCY PHONE: 800-424-9300**

FOR INDUSTRIAL USE ONLY

MATERIAL SAFETY DATA SHEET

CHEMTREC EMERGENCY PHONE NO.: 800-424-9300

FLAMMABLE LIQUID AND VAPOR (vapors travel long distances and flashback). Keep away from heat, sparks, and flame. Use only with adequate ventilation.

INHALATION: Harmful if inhaled. May affect the brain or nervous system, causing dizziness, headache or nausea. May cause nose and throat irritation. Avoid breathing of vapor or mist. Keep exposure below vapor limits using adequate ventilation and proper face mask.

CONTACT: May cause eye and skin irritation. Avoid contact by using glasses, gloves and impervious clothing.

NOTE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Contains **COPPER** which may cause hemolysis of red blood cells and lung injury. Follow all recommendations for proper use to minimize exposure.

FIRST AID: In case of contact flush with plenty of water. If exposed to high concentration of vapor, remove to fresh air. Get medical attention. If swallowed, **CALL A PHYSICIAN IMMEDIATELY.** Read the Material Safety Data Sheet prior to use.

CONTAINS: Copper Compound, Ketone, Xylene and Color Pigment.

Jan 80/1

DATE NOV 27 1990
L.A. PER

