

WOODCARE
with PENTACHlorophenol

WOODCARE with PENTACHlorophenol is a water-repellent, penetrating, wood preservative with unusual protective qualities. Treat wood with WOODCARE to repel termites and to prevent mold and rot. WOODCARE keeps wood drier to make it a long-life building material. It is an excellent base for paint, varnish and enamel, and is odorless when dry.

COVERAGE

For maximum protection coat only about 150 sq. ft. per gallon, one coat.

DIRECTIONS

Prepare surface to be treated by having it clean, dry and unpainted. Existing paint or coatings must be removed so WOODCARE can penetrate. Apply at least 2 coats with brush or spray, applying succeeding coats before first coat is completely dry. Thoroughly soak end-grain of wood. Do not apply when temperature is below 40° F. In new construction, lumber should be treated before it is in position. Surfaces that are broken or cut after treatment should be treated again. Wood intended for use in contact with the soil should be dipped in WOODCARE for a minimum of 3 minutes. Fence posts, poles, foundations, timbers and heavy wooden members should be free of bark, dry and well seasoned and emersed in the product for a period of 12 to 48 hours to be an effective wood preservative.

FINISHING: WOODCARE may be used as a prime coat for paint or varnish. Treated surfaces should be completely dry before applying paint or varnish or before glazing. Drying time in well ventilated area with warm temperature is usually 24 hours. If lacquer is to be applied use a sealer coat after applying WOODCARE.

WARNING! — COMBUSTIBLE
CONTAINS PETROLEUM DISTILLATE

Harmful if swallowed or absorbed through skin. Causes skin irritation. Do not get in eyes or clothing. Wash thoroughly after handling. Avoid breathing of vapor or spray mist. Close container after each use.

Wear protective clothing and rubber gloves when handling the freshly treated lumber. If swallowed or if gets in eyes, call PHYSICIAN immediately. Flush eyes with water for at least 15 minutes. **WARNING:** Do not use, pour, spill or store near heat or open flame.

This product is toxic to fish and wildlife. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

Do not reuse container. Destroy when empty.

USE WITH ADEQUATE VENTILATION
KEEP OUT OF REACH OF CHILDREN

ANOTHER FINE PRODUCT MANUFACTURED BY
ATLAS CHEMICAL CO.

Miami, Florida 33166

Products from Chemistry for Home and Industry . . . Since 1919

Additive S

Cutting and Grinding Fluid Fungicide

DIRECTIONS: Additive 80 is recommended for use in water based mixes: 1) to control slimy mold growth 2) to eliminate musty odors. Add 1 gallon Additive 80 to 1000-1500 gallons of cutting fluid mix. Frequent additions may be made on a weekly basis.

CAUTION

Avoid contact with skin or eyes. In case of contact flush with water; if in the eyes, flush with water and call a physician. Harmful if taken.

KEEP OUT OF REACH OF CHILDREN

ACTIVE INGREDIENT: 1-Hydroxy-2(1H)-Pyridinethione, sodium salt

INERT INGREDIENTS:

Do not contaminate water by cleaning of equipment, or disposal.

DO NOT REUSE CONTAINER. DESTROY WHEN EMPTY.

PROTECT FROM FREEZING

MILACRON

ACC
Under the
Fungicide,
as amended,
registered un
EPA Reg. N