

# Additive MC

## Cutting and Grinding Fluid Bacteriostat

### DIRECTIONS:

Additive MC is recommended for use in central filtration systems using water based cutting and grinding fluid mixes. Add 1 gallon of Additive MC to 1000 gallons of cutting fluid mix once a week:

- 1) to prevent loss of cutting fluid performance (rust, rancidity, poor tool life, etc).
- 2) to prevent rancid odors.
- 3) as a preventive maintenance program to insure long useful cutting and grinding fluid life.

## WARNING: KEEP OUT OF REACH OF CHILDREN

May cause eye damage or skin irritation. Avoid contact with skin, eyes or clothing. In case of skin contact, flush with water; if splashed in the eyes, flush with water and call a physician. Harmful if swallowed. If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician. Remove and wash contaminated clothing before reuse.

Do not contaminate water by cleaning of equipment, or disposal of wastes.

Do not reuse container. Destroy when empty.

Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Apply this product only as specified on this label.

**ACTIVE INGREDIENT:** Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine ..... **48.5%**

**INERT INGREDIENTS:** ..... **51.5%**

Contains Methanol

EPA EST 8314-OH-02

EPA Reg. No. 8314-18

PROTECT FROM FREEZING

**CINCINNATI  
MILACRON**

