

PRECAUTIONARY STATEMENTS
HAZARDOUS TO HUMANS AND DOMESTIC ANIMALS

DANGER

May cause severe eye and skin burns.
May cause allergic skin reaction.
May be harmful if inhaled.
May be fatal if swallowed or absorbed through the skin.
Get into eyes, on skin, or on clothing. Wear goggles, a face shield and rubber gloves when handling. Wash thoroughly with soap and water. Avoid contamination of food. Do not take internally. Wash thoroughly.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge into lakes, streams, ponds, or public water supplies. In accordance with an NPDES permit. For guidance contact your Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on the label.

STORAGE AND HANDLING

PRECAUTIONS:

This product is corrosive to mild steel. Do not store or transport in lined metal containers. Do not contaminate food or feed by storage, disposal or cleaning of equipment.

PESTICIDE DISPOSAL

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

METAL CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

GENERAL

CONSULT FEDERAL, STATE AND LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES

INDUSTRIAL MICROBICIDE FOR USE IN RE-
CULATING WATER COOLING TOWERS AND AIR
WASHER SYSTEMS AND IN PAPER MILLS

ACTIVE INGREDIENTS

5-CHLORO-2-METHYL-4-ISOTHAZOL- IN-3-ONE	1.15
2-METHYL-4-ISOTHAZOLIN-3-ONE	0.35

INERT INGREDIENTS

TOTAL	98.5
-------	------

GARRATT-CALLAHAN FORMULA 315 WEIGH 4.4 LBS./GAL

DANGER
KEEP OUT OF REACH OF CHILDREN

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED: Do not induce vomiting. Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

IF INHALED: Remove immediately to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Call a physician.

IF ON SKIN: Wash thoroughly with soap and water for at least 15 minutes. Call a physician.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate to use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be needed.

SEE LEFT PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

EPA REG. NO. 8540-23

EPA EST. NO.

8540-1-CA	1
8540-1-TX	1
8540-1-CA	1
8540-1-IL	1
8540-1-MJ	1

DIRECTIONS FOR USE

GENERAL CLASSIFICATION

It is against Federal law to use the product in a manner inconsistent with the labeling.

INDUSTRIAL RECYCLATION WATER
COOLING TOWERS

For the control of bacteria, algae and fungi add Garratt-Callahan Formula 315 to the circulating water in the system or to the other parts of the system as needed.

INITIAL DOSE: When the system is noticeably fouled, apply 148 to 883 ppm Garratt-Callahan Formula 315 (1.26 to 7.46 pounds or 19 to 113 fluid ounces of Garratt-Callahan Formula 315) per 1000 gallons of water in the system. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 35 to 219 ppm Garratt-Callahan Formula 315 (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of Garratt-Callahan Formula 315) per 1000 gallons of water in the system weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

AIR WASHER SYSTEMS

Add to the air washer sump or chill water sump, to insure uniform mixing, 35 to 883 ppm Garratt-Callahan Formula 315 (0.3 to 1.86 pounds or 4.5 to 113 fluid ounces of Garratt-Callahan Formula 315) per 1000 gallons of water in the system depending upon the severity of contamination to control bacteria, fungi, and algae which cause fouling in industrial air washer systems.

INTERMITTENT OR SLUG METHOD

INITIAL DOSE: When the system is noticeably fouled, apply 48 to 883 ppm Garratt-Callahan Formula 315 (1.26 to 7.46 pounds or 4.5 to 113 fluid ounces of Garratt-Callahan Formula 315) per 1000 gallons of water in the system. Repeat until control is achieved.

SUBSEQUENT DOSE: When microbial control is evident, add 35 to 219 ppm Garratt-Callahan Formula 315 (0.3 to 1.86 pounds or 4.5 to 113 fluid ounces of Garratt-Callahan Formula 315) per 1000 gallons of water weekly or as needed to maintain control.

CONTINUOUS FEED METHOD

INITIAL DOSE: When the system is just noticeably fouled, apply 148 to 883 ppm Garratt-Callahan Formula 315 (1.26 to 7.46 pounds or 19 to 113 fluid ounces of Garratt-Callahan Formula 315) per 1000 gallons of water in the system.

SUBSEQUENT DOSE: Maintain this treatment level by adding a continuous feed of 35 to 219 ppm Garratt-Callahan Formula 315 (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of Garratt-Callahan Formula 315) per 1000 gallons of water.