

SANI-CHLOR
POOL SANITIZER

21
67

NOT REVIEWED
In Accordance with EPA Notice 82-2
Based on:

EPA Reg. No. 8544-9

6 Manufactured and Packaged by GPS Industries;
City of Industry, California 91746

2/6

CHLORINATING LIQUID FOR POOL
AND SPA SANITIZATION

Active Ingredient: sodium hypochlor-
ite.....12.5%
Inert Ingredients:.....87.5%

KEEP OUT OF THE REACH OF CHILDREN

DANGER

FIRST AID

If contact with eyes occurs, flush with water for at least fifteen minutes. If wearing contact lenses, first rinse eyes, remove contact lenses, and continue flushing with water for at least fifteen minutes. Get prompt medical attention.

If contact with skin occurs, wash with plenty of soap and water.

If swallowed, drink large quantities of milk or gelatin solution. If these are not available, drink large quantities of water. Do not give vinegar or other acids. Do not induce vomiting. Get prompt medical attention.

BEST AVAILABLE COPY

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

NOTE: This product degrades with age. Use a chlorine test kit and increase dosage, as necessary, to obtain the required level of available chlorine.

STORAGE AND DISPOSAL

Store this product in a cool, dry area, away from direct sunlight and heat to avoid deterioration. In case of spill, flood areas with large quantities of water. Product or rinsate which cannot be used should be diluted with water before disposal in a sanitary sewer. Return empty container to dealer or distributor for deposit refund. Do not reuse container. If not returned for deposit refund, place in trash for collection. Do not contaminate food or feed by storage, disposal, or cleaning of equipment.

SWIMMING POOL WATER DISINFECTION

For a new pool or spring start-up, super-chlorinate with 52 to 104 ounces of product for each 10,000 gallons of water to yield 5 to 10 ppm available chlorine by weight. Check the level of available chlorine with a test kit. Adjust and maintain pH to between 7.2 to 7.6. Adjust and maintain the alkalinity of the pool to between 50 to 100 ppm.

To maintain the pool, add manually or by a feeder device 11 ounces of this product for each 10,000 gallons of water to yield an available chlorine residual between 0.6 to 1.0 ppm by weight. Stabilized pools should maintain a residual of 1.5 to 2.0 ppm available chlorine.

BEST AVAILABLE COPY

Test the pH, available chlorine residual, and the alkalinity of the water frequently with appropriate test kits. Frequency of water treatment will depend upon temperature and the number of swimmers.

Every 7 days, or as necessary, superchlorinate the pool with 52 to 104 ounces of product for each 10,000 gallons of water to yield 5 to 10 ppm available chlorine by weight. Check the level of available chlorine with a test kit. Do not reenter pool until chlorine residual is between 1.0 to 3.0 ppm.

At the end of the swimming pool season or when water is to be drained from the pool, chlorine must be allowed to dissipate from treated pool water before discharge. Do not chlorinate pool within 24 hours of discharge.

WINTERIZING POOLS- While water is still clear and clean, apply 3 ounces of product per 1,000 gallons of pool water while filter is running to obtain a 3 ppm available chlorine residual, as determined by a suitable test kit. Cover pool, prepare heater, filter, and heater components for winter by following manufacturers' instructions.

SPAS

Apply 5 $\frac{1}{2}$ ounces of product per 1,000 gallons of water to obtain a free available chlorine residual of 5 ppm, as determined by a suitable chlorine test kit. Adjust and maintain pH to between 7.2 to 7.8. Some oils, lotions, fragrances, cleaners, etc. may cause foaming or cloudy water as well as interfere with the chlorinating process. To maintain the water,

1.5 - AVAILABLE 6P

apply 5½ ounces of this product per 1,000 gallons of water over the surface to maintain a chlorine concentration of 5.0 ppm.

After each use, superchlorinate with 8 ounces of this product per 500 gallons of water to control odor and algae.

During extended periods of disuse, add 5 ounces of product daily per 1,000 gallons of water to maintain a 3.0 ppm chlorine concentration.

PRECAUTIONARY STATEMENTS

Hazards to Humans and Domestic Animals

DANGER. Corrosive, may cause severe skin and eye irritation or chemical burns to broken skin. Causes eye damage. Wear safety glasses or goggles and rubber gloves when handling this product. Wash after handling. Avoid breathing vapors. Vacate poorly ventilated areas as soon as possible. Do not return until strong odors have dissipated.

Environmental Hazards

This product is toxic to fish. Do not discharge into lakes, streams, ponds, or public waterways unless in accordance with a NPDES permit. For guidance contact the regional office of the United States Environmental Protection Agency.

Physical or Chemical Hazards

STRONG OXIDIZING AGENT. Mix only with water.

BEST AVAILABLE COPY

according to label directions. Mixing this product with chemicals, e.g. ammonia, acids, detergents, etc. or organic matter, e.g. feces, urine, etc., will release chlorine gas which is irritating to eyes, lungs, and mucous membranes.

SHIPPING INFORMATION

This product is classified as a hazardous material under regulations issued by the United States Department of Transportation. The correct name and shipping classification for filled containers is as follows: 12.5% Hypochlorite Solution, Corrosive Material, UN 1791, DOT-E-6614. The correct shipping name for return of empty containers to the distributor, dealer, and manufacturer is as follows: Empty containers, last contained Hypochlorite Solution, Corrosive Material, UN 1791, DOT-E-6614. Always return empty containers with the original closure tightly affixed to the container neck.