



**COMPANY
NUMBER** 8590-

**PRODUCT
SERIAL NO.** 511

**LABEL
APPROVAL
DATE** 5-28-85

FOR:

AGWAY WOOD SAVER

DATE: 8/13/84

RESTRICTED USE PESTICIDE

FOR RETAIL SALE TO AND USE ONLY
BY CERTIFIED APPLICATORS OR PERSONS
UNDER THEIR DIRECT SUPERVISION AND
ONLY FOR THOSE USES COVERED BY THE
CERTIFIED APPLICATOR'S CERTIFICATION.

ACCEPTED
MAY 28 1985
Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 8590-511

NET WEIGHT

1 Gal, 5 Gal.

AGWAY

WOOD SAVER

Ready-to-Use Penta Wood Preservative

ACTIVE INGREDIENTS:

Pentachlorophenol	4.43%
Other chlorinated phenols	0.52%
Petroleum hydrocarbons	92.55%

INERT INGREDIENTS:

2.50%

TOTAL

100.00%

Contains 5.3% technical pentachlorophenol

KEEP OUT OF REACH OF CHILDREN (12 pt)

DANGER (18 pt)

See below for additional precautionary statements.

The U. S. Environmental Protection Agency has determined that pentachlorophenol can produce defects in the offspring of laboratory animals. Exposure to pentachlorophenol during pregnancy should be avoided.

AGWAY INC.
Chemical Division
P. O. Box 4933
Syracuse, New York 13221

EPA Reg. No. 8590-511

EPA Est. No. 8590-PA-1

PC - 10 CHARACTERS
EPC - 40 CHARACTERS

FOR: AGWAY WOOD SAVER

DATE: 8/1 /84

((REAR PANEL))

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: May be fatal if swallowed. Harmful if inhaled or absorbed through skin. Causes skin irritation. May produce delayed chemical burns. Do not breathe vapor or spray mist. Do not get in eyes, on skin, or on clothing.

STATEMENT OF PRACTICAL TREATMENT

If swallowed, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY.

In case of eye contact, flush eyes immediately with plenty of water for at least 15 minutes and get medical attention.

In case of skin contact, wash with soap and plenty of water. Wash contaminated clothing before reuse.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL OR CHEMICAL HAZARDS

Do not use or store near heat or open flame.

Treated wood and other wood waste should not come in contact with domestic animals or be used so that they come in contact with useful living plants.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL (12 pt)

PROHIBITIONS: Do not contaminate water, food or feed by storage, disposal or cleaning of equipment. Open dumping is prohibited. Do not reuse empty container.

STORAGE: Store unused product in original container only. Store in a cool, dry area preferably locked and out of the reach of children and animals. Not for use or storage in or around the home. Protect from excess heat.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is

PLA 100 CHARACTERS
EITE 100 CHARACTERS

OK BY

FOR:

AGWAY WOOD SAVER

DATE: 8/13/84

a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

This product is a ready-to-apply pentachlorophenol solution to be used as a preservative treatment to protect wood against dry rot and mildew which cause decay and stains, termites prior to construction, and powder post beetles.

Wood to be treated should be thoroughly dry. Best results will be obtained if the wood is completely immersed and soaked in the solution. If soaking is not possible, apply at least two liberal brush coats, or spray applications. Allow a minimum of three hours between brush or spray applications for each to dry. Be sure all areas, particularly joints and ends, are fully treated.

Applicators must wear gloves impervious to the wood treatment formulation in all situations where dermal contact is expected (for example, during the actual application process and when handling freshly treated wood).

Spray applicators must wear protective clothing (including overalls, jackets, gloves and boots) impervious to the wood treatment formulation, and a respirator, head covering and goggles when spraying.

Applicators who apply pentachlorophenol by other application methods (e.g. brush-on) must wear disposable coveralls or other suitable impermeable protective clothing. Launder non-disposable protective clothing separately from other clothing.

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation.

Wash thoroughly after skin contact and before eating, drinking, use of tobacco products, or using restrooms.

Protective clothing must be changed when it shows signs of contamination. Dispose of worn out protective clothing and workshoes or boots in any general landfill, in the trash, or in any other manner approved for pesticide disposal.

PICA - 50 CHARACTERS
ELITE - 40 CHARACTERS

OK BY

ADVERTISING AND SALES PROMOTION SERVICES

COPY

FOR: AGWAY WOOD SAVER

DATE: 8/13/84

FENCE POSTS AND POLES - Fence posts and poles should be peeled or barked and seasoned until dry. Soak posts and poles in the solution for 48 hours, preferably in a vertical position with large end downward. If butt-end treatment only is used, the posts should be immersed to a depth that will be at least 1 foot above the soil line when the posts are set in the ground. If soaking is impracticable, apply two liberal brush coats. Be sure ends of posts and poles are thoroughly treated.

FENCE PICKETS AND RAILS - Soak in the solution for 48 hours. If immersion is impracticable, apply two liberal brush coats; be sure ends and joints are thoroughly treated.

MILL WORK - To protect wooden parts of windows and frames, doors and frames and screens, immerse the unpainted lumber for a period of three minutes or apply two liberal brush coats.

FLOORS, SUB-FLOORS, SILLS, STUDDING, JOISTS, FURRING STRIPS, STAIRS AND STEPS - Dip or apply two liberal brush or spray coats before construction. If this is not possible prior to construction, brush or spray all surfaces, with particular attention to joints and ends, with two liberal coats of the solution; allow three hours for each to dry. If wood is immersed, soak 5 minutes per inch of thickness. Wood intended for use in contact with the ground should receive at least two heavy brush coats, if such wood cannot be dipped.

Powder post beetles which invade flooring and structural timbers, if accessible for treatment may be controlled by thorough brush or spray application of the solution, but lumber and timbers in place may require several applications. Treatment of wood prior to construction or assembly is preferable for protection against attack by these insects.

To control subterranean termites which already occur in the wood of existing structures, thorough treatment of the soil and replacement of infested timbers is necessary.

In areas where dry wood termites are present, all interior and exterior trim as well as millwork should be treated with this product.

Estimated coverage: 1 gallon per 200 square feet for brush or spray application (2 coats).

Inspect treated wood particularly structural lumber and timbers, at least annually. If incipient rot or mildew, and especially if subterranean or dry wood termites are found, other treatments such as provisions to remove and

FOR THE CHARACTER OF THE CHARACTER OF THE

OK BY

VERTISING AND SALES PROMOTION SERVICES

COPY

FOR:

AGWAY WOOD SAVER

DATE: 8/13/84

to prevent excessive moisture, replacement of infested timbers, and thorough treatment of the soil may be required.

Wood that has been treated may be painted or varnished in 10 days after the last application.

Do not allow the solution or spray to contact desirable or beneficial plants. Severe injury to or killing of the plants may result.

Do not apply to or use treated wood for containers of fruits, vegetables, and other food or feed products, plant stakes, flats, hotbed frames, and greenhouse benches.

Avoid inhaling vapors. If inhalation of vapors cannot be avoided, applicators must wear a properly fitting, well-maintained half-mask cannister or cartridge respirator which is MSHA/NIOSH-approved for organic vapors and acid gases.

Do not apply where there may be direct contact with domestic animals or livestock, and where there may be contamination of food, feed, or drinking and irrigation water.

Do not apply in interiors. Do not apply to wood intended for use in interiors except for those support structures which are in contact with the soil in barns, stables, and similar sites and which are subject to decay or insect infestation; and millwork which has outdoor surfaces (e.g.; doorframes, windows and patio frames). Interior surfaces of the treated wood should be sealed with two coats of an appropriate sealer.

Do not apply pentachlorophenol to wood intended for farrowing or brooding facilities. Do not apply pentachlorophenol to wood intended to be used in the interiors of farm buildings where there may be direct contact with domestic animals or livestock which may crib (bite) or lick the wood. Pentachlorophenol may be used to treat wood intended to be used in interiors of farm buildings where domestic animals or livestock are unlikely to crib or lick the wood, if two coats of an appropriate sealer will be applied.

Do not apply to wood intended to be used in a manner in which the preservative may become a component of food or animal feed. Examples of such sites would be structures or containers for storing silage or food.

Do not use this product to treat wood intended to be used for cutting boards or counter tops.

PCA - SO CHARACTERISTICS
EUTE - SO CHARACTERISTICS

COPY

ADVERTISING AND SALES PROMOTION SERVICES

COPY

FOR: AGWAY WOOD SAVER DATE: 8/13/84

Do not use this product to treat wood intended for construction of those portions of beehives which may come into contact with the honey.

Do not use this product to treat wood intended to be used where it may come into direct or indirect contact with public drinking water, except for those uses involving incidental contact such as docks and bridges.

Do not use this product to treat wood intended to be used where it may come into direct or indirect contact with drinking water for domestic animals or livestock, except for uses involving incidental contact such as docks and bridges.

Wood to be treated with this product should be cut to size before treatment. If it is necessary to saw or machine wood after treatment, wear goggles to protect the eyes from flying particles and a dust mask to avoid inhaling sawdust from the treated wood. If oily preservatives or sawdust accumulate on clothes, launder before reuse. Wash work clothes separately from other household laundry.

Contact with treated surfaces should be avoided even after the preservative has dried. When handling treated wood wear tightly woven coveralls and gloves which are impervious (e.g., vinyl coated) to the pesticide. Wash exposed skin thoroughly after contact with treated wood, and before eating, drinking or using tobacco products.

Wood which has been treated with this product should be disposed by burial or ordinary trash collection. Do not burn treated wood in an outdoor fire or in stoves or fireplaces because toxic chemicals may be produced as part of the smoke and ashes.

This product should not be used to treat wood which will be in frequent or prolonged contact with skin, unless the wood will be treated with an effective sealer.

Note to User: As used on this label, the term "respirators" means properly fitting, well-maintained half-mask canister or cartridge respirators which are MSHA-NIOSH-approved for organic vapors and acid gases. Examples of acceptable materials for protective clothing (e.g., overalls, jackets, head covering, boots, disposable coveralls, and gloves) required during application and handling of pentachlorophenol are polyvinyl acetate (PVA), polyvinyl chloride (PVC), neoprene, NBR (Buna-N), and nitrile. Urethane, shellac, latex (epoxy enamel and varnish are acceptable sealers for pentachlorophenol-treated wood.

PER LINE - 60 CHARACTERS
PER LINE - 60 CHARACTERS

WORK BY