

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**DANGER  
CORROSIVE**

**CAUSES IRREVERSIBLE EYE DAMAGE AND SKIN BURNS  
EYE CONTACT MAY CAUSE LOSS OF VISION  
IRRITATING TO NOSE AND THROAT  
MAY BE FATAL IF INHALED  
HARMFUL IF ABSORBED THROUGH SKIN OR SWALLOWED**

Do not breathe dust or spray mist. Do not get in eyes, on skin, or on clothing. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Wear goggles with side-shields, face shield, or safety glasses; protective clothing and rubber gloves. Wear a dust mist mask or pesticide respirator approved by the National Institute for Occupational Safety and Health. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before re-use.

**ENVIRONMENTAL HAZARDS**

This product is toxic to fish and aquatic organisms. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**CHEMICAL AND PHYSICAL HAZARDS**

Strong oxidizer, mix with water only. Reaction with combustible organic materials, bases, moisture or with oxidizers may generate heat, hazardous gases and, possibly, fire or explosion. Do not add to dispensers or other equipment that is not dry and clean of any chemical remnants. Does not burn, but will decompose, from about 320°F (160°C), releasing toxic gases. Avoid comminution and dusting.

**KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE**

**WARRANTY**

Seller warrants that this product conforms to its chemical description and is reasonably fit for the purposes stated on the label when used in accordance with label directions under normal conditions of use, but neither this warranty nor any other warranty of MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, express or implied, extends to the use of this product contrary to label instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to Seller, and Buyer assumes the risk of any such use.

**MANUFACTURED IN ISRAEL FOR:  
AMERIBROM, INC.  
2115 LINWOOD AVENUE  
FORT LEE, NJ 07024  
(201) 242-6560**

EPA Reg. No. 8622-30

NET CONTENTS: \_\_\_\_\_ LBS(KGS).

**ACCEPTED**  
MAY 31 2006  
Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under 8622-30  
EPA Reg. No. 8622-30  
EPA Est. No. 16298-1S-1

**HALOGENE T-30**

**BROMO-CHLORO-DIMETHYLHYDANTOIN**

A MICROCIDAL BACTERICIDE, FUNGICIDE, ALGAEKILLER AND SLIMEKILLER, FOR TREATING INDUSTRIAL RECIRCULATING COOLING WATER AND ONCE-THROUGH COOLING WATER SYSTEMS, ORNAMENTAL FOUNTAINS, AIR CONDITIONER CONDENSATE, PULP & PAPER MILL WATER SYSTEMS.

ACTIVE INGREDIENT: Bromochloro-5,5-dimethylhydantoin..... 98%  
OTHER INGREDIENTS: ..... 2%  
TOTAL .....100%

**KEEP OUT OF REACH OF CHILDREN**

**DANGER**

**CORROSIVE AND STRONG OXIDIZER**

**FIRST AID**

<b>If in eyes</b>	<ul style="list-style-type: none"> <li>Hold eye open and rinse slowly and gently with water for 15-20 minutes.</li> <li>Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.</li> <li>Call a poison control center or doctor for treatment advice.</li> </ul>
<b>If on skin or clothing</b>	<ul style="list-style-type: none"> <li>Take off contaminated clothing.</li> <li>Rinse skin immediately with plenty of water for 15-20 minutes.</li> <li>Call a poison control center or doctor for treatment advice.</li> </ul>
<b>If inhaled</b>	<ul style="list-style-type: none"> <li>Move person to fresh air.</li> <li>If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.</li> <li>Call a poison control center or doctor for further treatment advice.</li> </ul>
<b>If swallowed</b>	<ul style="list-style-type: none"> <li>Call poison control center, or doctor immediately for treatment advice.</li> <li>Have person sip a glass of water if able to swallow.</li> <li>Do not induce vomiting unless told to do so by the poison control center or doctor.</li> <li>Do not give anything by mouth to an unconscious person.</li> </ul>

Have the product container or label with you when calling a poison control center or doctor, or going for treatment.  
**YOU MAY ALSO CONTACT 1-800-420-9236 FOR EMERGENCY MEDICAL TREATMENT INFORMATION.**

**NOTE TO PHYSICIAN**

Probable mucosal damage may contraindicate the use of gastric lavage.

See side panels for additional precautionary statements.  
**USE WITH ADEQUATE VENTILATION  
WASH THOROUGHLY AFTER HANDLING  
DO NOT SMOKE, DRINK, OR EAT WHEN HANDLING.**

**DIRECTIONS FOR USE**

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

**INDUSTRIAL RECIRCULATING COOLING WATER SYSTEMS**

Used effectively at treatments recommended to achieve exposures to one part per million (ppm) of 'active' residual bromine to control algal, bacterial and fungal slimes in industrial cooling towers; influent water systems, e.g. flow-through filters, and lagoons, etc.; heat-exchange water systems; industrial water scrubbing systems, brewery and canning pasteurizers and industrial air-washing systems equipped with a mist eliminator.

**Treatment rates**

**Initial treatment:** When noticeably fouled, add 2-6 lbs/10,000 gallons of water contained in the system. Repeat initial treatment until one ppm of 'active' residual bromine is established for at least 4 hours.

**Subsequent treatment:** When microbial control is evident, add 1-3 lbs/10,000 gallons of water contained in the system. Repeat as needed to maintain one ppm of 'active' residual bromine for at least 4 hours.

**ONCE-THROUGH INDUSTRIAL COOLING WATER SYSTEMS**

Used for the control of algal, bacterial and fungal slimes, by adding to the system inlet, or before any other contaminated area in the system, in once-through and closed-cycle fresh and sea water cooling systems; cooling ponds; canals; and lagoons

**Treatment rates**

**Initial treatment:** When noticeably fouled, add 2-6 lbs/10,000 gallons of water contained in the system. Repeat initial treatment until one ppm of 'active' residual bromine is established for at least 4 hours.

**Subsequent treatment:** When microbial control is evident, add 1-3 lbs/10,000 gallons of water contained in the system. Repeat as needed to maintain one ppm of 'active' residual bromine for at least 4 hours.

**ORNAMENTAL FOUNTAINS**

See treatment rates for industrial recirculating cooling water systems.

**AIR CONDITIONER CONDENSATE**

Place tablet in condensate line dispenser. Check once every six months or as required. The life of the tablet will vary depending upon atmospheric conditions and indoor air temperature requirements.

**PULP AND PAPER MILL WATER SYSTEMS**

This product is intended for use as a slimeicide for the process water used in the manufacture of paper and paperboard products that do not contact food. Treat water at critical areas in the system process where mixing of the product with influent will be uniform. The frequency and duration of the treatment will depend upon the severity of the problem. Badly fouled process systems must be cleaned before initial treatment. [Note: Either one or both of the following treatment methods may be included on the label.]

**Treatment by system volume**

When a system is noticeably fouled: add 0.098 to 0.98 pounds of HALOGENE T-30 to 1,000 gallons or 12 to 120 ppm of water in the system. When biological control is evident: add 0.098 to 0.74 pounds of HALOGENE T-30 to 1,000 gallons or 12 to 90 ppm of water in the system.

**Treatment by residual method**

Add sufficient HALOGENE T-30 to maintain a measured residual up to 5 ppm as bromine. Once biological control is evident, the use of HALOGENE T-30 normally can be reduced to something less than 1 ppm as bromine.

**[Optional Statement]** An alternative method of calculating the appropriate level of HALOGENE T-30 is to estimate the paper mill's daily production, then add over a 24-hour period, up to 588 grams (1.27 pounds) of HALOGENE T-30 per dry ton of paper produced over a 24-hour period. Test for bromine to verify the level of 5 ppm is not being exceeded.

**DO NOT SHIP WITH FOODS, FEEDS, DRUGS, OR CLOTHING.**

**STORAGE AND DISPOSAL**

Do not contaminate water, food, or feed by storage or disposal.

**STORAGE:** Store in a dark, cool [below 86°F (30°C)], dry, well-ventilated area, in well-closed original containers, away from energy sources, combustible organic materials, oxidizers, strong bases and moisture.

**PESTICIDE DISPOSAL**

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or residue is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**CONTAINER DISPOSAL**

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

**SPILLS**

When handling or dealing with spills, use impact-resistant goggles with side-shields, or face shield; body-covering clothes, including impervious rubber or plastic gloves and boots; use a dust respirator if dusting occurs. Sweep up dry spills and dispose of as described for pesticide disposal. If drum contents are contaminated or decomposing, do not reseal container; isolate unsealed drum in the open or in a well-ventilated area; flood with large volumes of water if necessary.

**IN CASE OF FIRE:** Do not use ammonium phosphate extinguisher near water and HALOGENE T-30. Hazardous reactions may occur.

8622-30

05/31/2006

1/1