

- c. The following statements are suggested types of information that may be included in the first aid statements.

- technical information on symptomatology;
- use of supportive treatments to maintain life functions;
- medicine that will counteract the specific physiological effects of the pesticide;
- company telephone number to specific medical personnel who can provide specialized medical advice.

- d. Add the statement "***or safety glasses***" to the precautionary statement. All of the precautionary statement texts must be in the same letter type size (bold letters if prefer).

- e. Revise the Storage and Disposal statements to read as follows:

STORAGE and DISPOSAL

Do not contaminate water, food or feed by storage and disposal

PESTICIDE STORAGE:

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. ImproperEPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinsestay out of smoke.

Refer to PR Notices 83-3 for detailed information.

- f. Add the following PPE language to the label:

Personal Protection Equipment (PPE)

Applicators and other handlers must wear:

- Coveralls worn over long sleeved shirt and long pants.
- Chemical-resistant footwear plus socks
- Goggles or face shield
- Chemical-resistant gloves (such as barrier laminate, butyl rubber, neoprene rubber, nitrile rubber, polyvinyl chloride (PVC and viton).

g. **For Cleaning Equipment:**

-Chemical-resistant apron

h. User Safety Requirements and Recommendations must read as follows:

"Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instruction exist for washables, use detergent and hot water. Keep and wash PPE separately from other laundry."

"User Safety Recommendations"

"Users should wash hands before drinking, chewing gum, using tobacco, or using the toilet."

"Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing." Users should remove personnel protective equipment immediately after handling this product. Wash outside of gloves before removing. As soon as possible wash thoroughly.


3. The basic Confidential Statement of Formula dated February 1, 2002 is acceptable. However, the certified limits of the active ingredient must be corrected to conform to the Agency standard in 40 CFR§158.175.

4. Submit three (3) copies of the revised final printed label bearing the revisions prior to releasing this product for sale.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product bearing the amended labeling constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



Adam Heyward
Product Manager (34)
Regulatory Management Branch II
Antimicrobials Division (7510C)

Enclosure:

486

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

CORROSIVE
CAUSES IRREVERSIBLE EYE DAMAGE
EYE CONTACT MAY CAUSE LOSS OF VISION
HAZARDOUS IF SWALLOWED, INHALED OR ABSORBED
THROUGH THE SKIN

Avoid breathing vapors or spray mist. Do not get in eyes or on clothing. Avoid contact with skin. In case of contact immediately rinse skin with plenty of water. Get medical attention if irritation persists. Wear protective eyewear (goggles or face shield). Use with adequate ventilation. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash clothing before reuse.

FIRST AID	
If in eyes	<ul style="list-style-type: none">• Hold eye open and rinse slowly and gently with water for 15-20 minutes.• Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.• Call a poison control center or doctor for treatment advice.
If inhaled	<ul style="list-style-type: none">• Move person to fresh air.• If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.• Call a poison control center or doctor for further treatment advice.
If on skin or clothing	<ul style="list-style-type: none">• Take off contaminated clothing.• Rinse skin immediately with plenty of water for 15-20 minutes.• Call a poison control center or doctor for treatment advice.
If swallowed	<ul style="list-style-type: none">• Call poison control center, or doctor immediately for treatment advice.• Have person sip a glass of water if able to swallow.• Do not induce vomiting unless told to do so by the poison control center or doctor.• Do not give anything by mouth to an unconscious person.
Have the product container, or label with you when calling a poison control center or doctor, or going for treatment.	
NOTE TO PHYSICIAN	
"Note to Physician: Probable mucosal damage may contraindicate the use of gastric lavage."	

WASH THOROUGHLY AFTER HANDLING

BIOBROM® C-105L
DBNPA

A MICROBIOCIDAL BACTERICIDE, FUNGICIDE, ALGICIDE AND SLIMICIDE, USED IN TREATING RECIRCULATING COOLING WATER IN INDUSTRIAL COOLING SYSTEMS, PAPER MILLS, BREWERY PASTEURIZER WATER, METALWORKING CUTTING FLUIDS, NON-POTABLE REVERSE OSMOSIS SYSTEMS, ENHANCED OIL RECOVERY SYSTEMS, AIR-WASHER SYSTEMS, INDUSTRIAL PRESERVATION APPLICATIONS AND PUBLICLY-OWNED TREATMENT WORKS.

ACTIVE INGREDIENT: 2,2-Dibromo-3-nitropropionamide..... 5.49%
INERT INGREDIENTS: 94.51%
TOTAL: 100.00%

2.5 pounds BIOBROM® C-105L liquid per gallon.

KEEP OUT OF REACH OF CHILDREN

DANGER

See side panels for additional precautionary statements

EPA Reg. No. 8622-xx

EPA Est. No. 61688-AL-01

NET CONTENTS: _____ GALS.(LBS.)

WARRANTY

Seller warrants that this product conforms to its chemical description and is reasonably fit for the purposes stated on the label when used in accordance with label directions under normal conditions of use, but neither this warranty nor any other warranty of MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, express or implied, extends to the use of this product contrary to label instructions, or under abnormal conditions, or under conditions not reasonably foreseeable to Seller, and Buyer assumes the risk of any such use.

MANUFACTURED IN ISRAEL FOR:
AMERIBROM, INC.
2115 LINWOOD AVENUE
FORT LEE, NJ 07024
(201) 242-6560

ACCEPTED
with COMMENTS
in EPA Letter Dated:

MAR 11 2002

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No. 8622-63

ENVIRONMENTAL HAZARDS

This product is toxic to fish and aquatic organisms. Do not contaminate water by cleaning of equipment or disposal of waste. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

CHEMICAL AND PHYSICAL HAZARDS

Reaction with strong reducing agents may be explosive. Avoid misting.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

STORAGE

Store in a dark, cool, dry, well-ventilated area, not above 104°F (40°C), in well-closed original containers, away from energy sources, combustible organic materials, oxidizers and moisture.

DISPOSAL

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

SPILLS

When handling or dealing with spills, use impact-resistant goggles with side shields, or face shield; wear body-covering clothes, including impervious rubber gloves and boots; use a respirator if misting occurs. Cover wet spills with 10% sodium bicarbonate solution, water and then an inert absorbent before sweeping up and disposing as described for pesticide disposal. If drum contents are contaminated or decomposing, isolate unsealed drum in the open or in a well-ventilated area; flood with 10% sodium bicarbonate solution and large volumes of water if necessary.

KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE
TO MAINTAIN PRODUCT QUALITY, STORE IN THE DARK AT
TEMPERATURES BELOW 104°F (40°C).
DO NOT SHIP WITH FOOD, FEEDS, DRUGS, OR CLOTHING
DO NOT SMOKE, DRINK, OR EAT WHEN HANDLING

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and directions.

DIRECTIONS FOR TREATING INDUSTRIAL RECIRCULATING COOLING WATER IN INDUSTRIAL COOLING SYSTEMS

NOTE: Add BIOBROM C-105L separately to the system. Do not mix it with other additives, so as to avoid decomposition of BIOBROM C-105L due to the high pH of many additive formulations. Add BIOBROM C-105L to the basin (or any other point of uniform mixing). Addition should be made via a metering pump; it may be continuous or intermittent, depending on the severity of the contamination when treatment is begun, and the in-system retention time. Optimum performance with this product is achieved by continuous or intermittent treatment. If "shock" treatment is used, the blowdown should be discontinued for 24-48 hours.

FOR CONTROL OF BACTERIA

Add 0.00380-0.0380 gallons of BIOBROM C-105L / 1000 gal. of water in the system depending on the severity of contamination.

INTERMITTENT OR SLUG METHOD

Initial Dose: When the system is noticeably fouled, add 0.0192-0.0380 gal. of BIOBROM C-105L / 1000 gal. of water in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 0.0096-0.0380 gal. of BIOBROM C-105L / 1000 gal. of water in the system every 4 days, or as needed to maintain control.

Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

Initial Dose: When the system is noticeably fouled, add 0.0192-0.0380 gal. of BIOBROM C-105L / 1000 gal. of water in the system.

Subsequent Dose: Maintain this level by pumping a continuous feed of 0.00380-0.0192 gal. of BIOBROM C-105L / 1000 gal. of water in the system lost by blowdown. Badly fouled systems must be cleaned before treatment is begun.

FOR CONTROL OF FUNGI AND ALGAE

Add 0.116-0.380 gallons of BIOBROM C-105L / 1000 gal. of water in the system, depending on the severity of contamination.

INTERMITTENT OR SLUG METHOD

Initial Dose: When the system is noticeably fouled, add 0.192-0.380 gal. of BIOBROM C-105L / 1000 gal. of water in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 0.116-0.380 gal. of BIOBROM C-105L / 1000 gal. of water in the system daily, or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

Initial Dose: When the system is noticeably fouled, add 0.192-0.380 gal. of BIOBROM C-105L / 1000 gal. of water in the system.

Subsequent Dose: Maintain this treatment level by pumping a continuous feed of 0.116-0.380 gal. of BIOBROM C-105L / 1000 gal. of water in the system per day. Badly fouled systems must be cleaned before treatment is begun.

DIRECTIONS FOR TREATING PULP AND PAPER MILL SYSTEMS

NOTE: Add BIOBROM C-105L separately to the system. Do not mix it with other additives, so as to avoid decomposition of BIOBROM C-105L due to the high pH of many additive formulations. For the control of slime-forming bacterial, fungal, and yeast growth in pulp, paper and paperboard mills add BIOBROM C-105L at levels of 0.60-2.00 lbs./ton (dry) of pulp or paper produced. Addition can be continuous or intermittent, depending upon the type of system and the severity of contamination. Addition is via a metering pump at a point in the system that will ensure uniform distribution of BIOBROM C-105L in the mass of fiber and water, such as the beaters, Jordan inlet or discharge, broke chests, furnish chests, save-alls and white-water tanks. Heavily fouled systems must first be boiled out, then treated with 0.80-1.40 lbs. of BIOBROM C-105L / ton (dry) of paper or pulp as necessary for control. Moderately fouled systems should be treated continuously with 1.40-2.00 lbs. of BIOBROM C-105L / ton (dry) of paper or pulp until the slime accumulation is controlled. Subsequent rates can then be reduced to 0.60-1.40 lbs. of BIOBROM C-105L / ton (dry) of paper on a continuous or intermittent basis as needed for control. Dislodged slime may cause breaks in the paper and a clean-up of the paper machine may be advisable. Slightly fouled systems should be treated continuously with 0.60-1.40 lbs. of BIOBROM C-105L / ton (dry) of paper or pulp, until the slime is controlled, then added on an intermittent basis to maintain control.

DIRECTIONS FOR TREATING NON-POTABLE REVERSE OSMOSIS SYSTEMS

For controlling bacteria, fungi and algae slimes in non-potable Reverse Osmosis systems and peripheral equipment, add BIOBROM C-105L to the system inlet water or before any other contamination area ahead of the Reverse Osmosis unit. BIOBROM C-105L should be added with a metering pump on an intermittent basis depending on the severity of contamination and the guidelines specified by the membrane manufacturer for BIOBROM C-105L. Add BIOBROM C-105L at the rate of 0.04 to 4.0 lbs (1 to 120 ppm) per 1000 gals of feedwater. During use of BIOBROM C-105L both permeate and reject waters should be directed to the drain. Once treatment is completed, rinsing with feedwater should continue until conductivity values in the permeate are at or below values before treatment with BIOBROM C-105L. Badly fouled systems must be cleaned before treatment is begun.

FOR CONTROL OF BACTERIA

Initial Dose: When the system is noticeably fouled, add BIOBROM C-105L at the rate of 0.2 to 0.4 lb (6 to 12 ppm) per 1000 gals of feedwater.

Minimum treatment intervals should be 15 minutes. Repeat until control is achieved or as specified by guidelines recommended by the membrane manufacturer.

Subsequent Dose: When microbial control is achieved, add BIOBROM C-105L at the rate of 0.1 to 0.4 lb (3 to 12 ppm) per 1000 gals of feedwater as needed to maintain control or as specified by guidelines recommended by the membrane manufacturer.

FOR CONTROL OF FUNGI AND ALGAE

Initial Dose: When the system is noticeably fouled, add BIOBROM C-105L at the rate of 2.0 to 4.0 lbs. (80 to 120 ppm) per 1000 gals of feedwater.

Minimum treatment intervals should be 15 minutes. Repeat until control is achieved or as specified by guidelines recommended by the membrane manufacturer.

Subsequent Dose: When microbial control is achieved, add BIOBROM C-105L at the rate of 1.2 to 4.0 lbs. (36 to 120 ppm) per 1000 gals of feedwater as needed to maintain control or as specified by guidelines recommended by the membrane manufacturer.

DIRECTIONS FOR TREATING METALWORKING FLUIDS CONTAINING WATER

BIOBROM C-105L is effective in metalworking fluid concentrates which have been diluted in water at ratios of 1:25 to 1:1. For controlling (or inhibiting) the growth of bacteria, fungi and yeasts that may deteriorate metalworking fluids containing water, add this product to the fluid in the collection tank. Additions should be made with a metering pump.

Initial or Slug Dose: When the system is noticeably fouled, add BIOBROM C-105L at the rate of 1.1 gals (2.65 lbs) per 1000 gals of metalworking fluid in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add BIOBROM C-105L at the rate of 0.4 to 0.8 gal (1.06 to 2.12 lbs) per 1000 gals of metalworking fluid per day, or as needed to maintain control. Additions of BIOBROM C-105L product can be made continuously or intermittently. Slug the system as required.

DIRECTIONS FOR TREATING BREWERY PASTEURIZER WATER

For controlling (or inhibiting) the growth of bacteria, fungi and yeasts in brewery pasteurizing water systems, add BIOBROM C-105L at a point in the system to insure uniform mixing.

Initial or Slug Dose: When the system is noticeably fouled, add BIOBROM C-105L at the rate of 1.1 gals (2.65 lbs) per 1000 gals of water in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add BIOBROM C-105L at the rate of 0.4 to 0.8 gal (1.06 to 2.12 lbs) per 1000 gals of water per day, or as needed to maintain control. Additions of BIOBROM C-105L product can be made continuously or intermittently. Slug the system as required. Badly fouled systems must be cleaned before treatment is begun.

DIRECTIONS FOR TREATING ENHANCED OIL RECOVERY SYSTEMS

NOTE: Add BIOBROM C-105L separately to the system. Do not mix it with other additives, so as to avoid decomposition of BIOBROM C-105L due to the high pH of many additive formulations. Addition of BIOBROM C-105L may be made at the free water knockouts, before or after the injection pumps and injection well headers. For controlling slime-forming bacteria, sulfide-producing bacteria, yeasts, and fungi in oil field water, polymer or micellar floods, water-disposal systems, or other oil field water systems, add 1-80 ppm BIOBROM C-105L (0.4 - 25.6 gallons of BIOBROM C-105L per 2400 barrels of water) depending on the severity of contamination. Additions should be made with a metering pump either continuously or intermittently.

CONTINUOUS FEED METHOD

When the system is noticeably fouled, add 10-80 ppm BIOBROM C-105L (3.2-25.6 gals. of BIOBROM C-105L per 2400 barrels of water) continuously until the desired degree of control is achieved. Subsequently, treat with 1-15 ppm BIOBROM C-105L (0.4-4.8 gals. of BIOBROM C-105L per 2400 barrels of water) continuously or as needed to maintain control.

INTERMITTENT OR SLUG METHOD

When the system is noticeably fouled or to maintain control of the system, add 10-80 ppm BIOBROM C-105L (3.2-25.6 gals. of BIOBROM C-105L per 2400 barrels of water) intermittently for 4-8 hours per day and from 1-4 times per week, or as needed depending on the severity of contamination.

NOTE: For control of bacteria, yeast, and fungi in aqueous solutions of biopolymer used in flooding operations, add 15-80 ppm BIOBROM C-105L (4.8 - 25.6 gals. of BIOBROM C-105L per 2400 barrels of water). Additions of BIOBROM C-105L should be made with a metering pump immediately after preparation of the aqueous biopolymer solution to reduce loss of viscosity.

DIRECTIONS FOR TREATING AIR-WASHER SYSTEMS

Add 0.06 - 0.38 gallons BIOBROM C-105L / 1000 gal of water in the system, depending on the severity of contamination, to control slime-forming bacteria and fungi in industrial air washing systems.

Intermittent or Slug Method

Initial Dose: When the system is noticeably fouled, add 0.012 - 0.380 gal BIOBROM C-105L / 1000 gal of water in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 0.005 - 0.188 gal BIOBROM C-105L / 1000 gal of water in the system every 2 days, or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

Initial Dose: When the system is noticeably fouled, add 0.012 - 0.380 gal BIOBROM C-105L / 1000 gal of water in the system.

Subsequent Dose: Maintain this level by pumping a continuous feed of 0.006 - 0.188 gal BIOBROM C-105L / 1000 gal of water in the system per day. Badly fouled systems must be cleaned before treatment is begun.

NOTE: For use only in industrial air-washer systems that maintain effective mist eliminating components.

DIRECTIONS INDUSTRIAL PRESERVATION APPLICATIONS

BIOBROM C-105L may be used to reduce microbiological contamination in raw materials and/or products such as: aqueous paints and coatings, polymers, slimes, adhesives, latex and resin emulsions, sizing, caulk, process water, along with specialty industrial products including: inks, polishes, waxes, detergents, and cleansers.

TO REDUCE MICROBIOLOGICAL CONTAMINATION

Add BIOBROM C-105L to the material or product at a concentration of 25 to 2,000 ppm by weight. This concentration is equivalent to 11.2 to 896.0 fluid ounces BIOBROM C-105L per 1,000 gallons or 85.6 to 6,848.0 milliliters BIOBROM C-105L per 1,000 liters. The required concentration will depend on the material being treated and the level of contamination present.

DIRECTIONS FOR TREATING PUBLICLY-OWNED TREATMENT WORKS TO CONTROL COLIFORM AND OTHER BACTERIA

Add BIOBROM C-105L at a concentration of 1.0 to 10.0 ppm by weight of water being treated, depending on the severity and contamination in the system.

Addition should be CONTINUOUS and should be made with a metering pump at a point in the system where mixing will be rapid and thorough. Add BIOBROM C-105L to the system in a location where contact time will be 30 minutes or greater before reaching the outfall.

TO USE AS A CO-TREATMENT WITH CHLORINE

Add 0.4 - 1.5 ppm BIOBROM C-105L by weight of water treated. Chlorination should result in a minimum detectable residual (i.e., greater than zero but less than the NPDES permit level) Addition should be CONTINUOUS and made at a point just after initial chlorine mixing. Rapid mixing is necessary for maximum effectiveness. BIOBROM C-105L should be added at a location where a contact time of 10 minutes or longer will be provided before reaching the outfall.

6
3
9