UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

5/11/2004

May 11, 2004

Robert Rosenwasser Manager, Regulatory Affairs Ameribrom, Inc. 2115 Linwood Avenue Fort Lee, NJ 07024

Subject:

BIOBROM C-105L

EPA Registration No. 8622-63 Application Date: March 24, 2004 Receipt Date: March 24, 2004

Dear Mr. Rosenwasser:

This acknowledges receipt of your notification, submitted under the provision of PR Notice 98-10, FIFRA section 3(c)9.

Proposed Notification

addition of hotline number to First Aid statement

General Comments

Based on a review of the material submitted, the following comments apply:

The notification application is acceptable and a copy has been inserted in your file for future reference.

Should you have any questions or comments concerning this letter, please contact me at (703) 308-6345.

Sincerely,

Wanda Mitchell Product Reviewer 32 Regulatory Management Branch II Antimicrobials Division (7510C)

	CONCURRENCES	
SYMBOL 75 10 C 75700		
SURNAMEN E. Belg Mitchell		
DATE \$ 5/11/04 5-11-04		
FPA Form 1320-1A (1/90)	Printed on Pagerlad Pages	OFFICIAL EU C CONY

	efore completing form.	For	m Approved	. OMB No.	2070-006	O. Approvel expires 2-28-9
l o Ens	United States Onmental Protect Washington, DC 2	ion Agency	V	Registra Amend Other	ation	OPP Identifier Number
	Applicat	ion for Pesticide -	Section	l		
1. Company/Product Number 8622-63		2. EPA Produc W. Mitchell	t Menager		·	oposed Classification
4. Company/Product (Name) BIOBROM C-105L		PM# 32		et vat og i de De Souetalego og		
5. Name and Address of Applicant the Ameribrom, Inc. 2115 Linwood Avenue Fort Lee, NJ 07024		(b)(i), my pro to: EPA Reg. N	duct is sim			FIFRA Section 3(c)(3) mposition and labeling
		Section - II			9 IN 18150	
Amendment - Explain below. Resubmission in response to a Notification - Explain below.	Agency letter dated	Agen	printed label cy letter dat Too" Applica - Explain be	ed ition.	e to	· · · · · · · · · · · · · · · · · · ·
Explanation: Use additional page(a "Notification of Addition of Hotline Tele "This notification is consistent with the labeling or the confidential statement of EPA. I further understand that if this not FIFRA and I may be subject to enforce	provisions of PR Notice 98 of formula of this product. I otification is not consistent	amended First Aid Statement -10 and EPA regulations at 4 understand that it is a violatio with the terms of PR Notice 9 under sections 12 and 14 of I	0 CFR 152.4 n of 18 U.S.C 8-10and 40 C FIFRA.*	6, and no oth C. Sec. 1001 CFR 152.46,	to willfully r	nakė any false statement to
		Section - III 👙		1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -		
1. Material This Product Will Be Pack	aged In:	10 (00)	5 J. A. 1977	1541 5.0	e de la companya de l	
Yes No If "Yes"	ckaging /es No. per ckaging wgt. container		. per ntainer	2. Type of	Metal Plastic Glass Paper Other (S	
3. Location of Net Contents Informati	A Size(e) B	etail Container	TE LO	cation of Lal	nal Directio	nng .
Label Container						
6. Manner in Which Label is Affixed to Product Paper glued Stenciled Dithograph Other						
		Section - IV				
1. Contact Point (Complete items dir	ectly below for identificat		cted, if nec	essary, to pi	ocess this	application.)
Name		Title				Nos (Include Area Code)
Robert Rosenwasser		Manager, Regulatory A	ffairs	_	(201) 242	-6977
I certify that the statements I h I acknowledge that any knowling both under applicable law.	Certific nave made on this form an nglly false or misleading s	d all attachments thereto a	re true, accu by fine or i	rate and eomprisonmen	mplete.	6. Date Application Received (Stamped)
2. Signature		3. Title Manager, Regulatory Affa	irs	• •	••••	••••
4. Typed Name Robert Rosenwasser		5. Date March 2	4, 2004			••••



AmeriBrom, Inc.

2115 Linwood Avenue, Fort Lee, NJ 07024-5004 Tel: 1 (201) 242-6560 Fax: 1 (201) 242-6561 Info@AmeriBrom.dsbg.com

March 24, 2004

Page 1 of 2

Document Processing Desk (AMEND)
Office of Pesticide Programs (7504C)
U.S. Environmental Protection Agency
Room 266A, Crystal Mall 2
1921 Jefferson Davis Highway
Arlington, VA 22202-4501

Attention: Wanda Mitchell PM-32 (7510C)

RE: Notification of Addition of Hotline Telephone Number to already amended First Aid Statements per PR Notice 98-10.

- 1. AmeriBrom, Inc., 2115 Linwood Avenue, Fort Lee, NJ 07024 is filing these Notifications to add an Emergency Hot Line Phone Number to our already amended First Aid Statements.
- 2. This notification is consistent with the provisions of PR Notice 98-10 and EPA regulations at 40 CFR 152.46, and no other changes have been made to the labeling or the confidential statement of formula of this product. I understand that it is a violation of 18 U.S.C. Sec. 1001 to willfully make any false statement to EPA. I further understand that if this notification is not consistent with the terms of PR Notice 98-10and 40 CFR 152.46, this product may be in violation of FIFRA and I may be subject to enforcement action and penalties under sections 12 and 14 of FIFRA.

Enclosed in this packet are Two (2) copies of each label. Please see page 2 for a complete list of the AmeriBrom labels.

If you have any questions or require further information, please feel free to call me at: (201) 242-6577.

Sincerely yours,

Robert Rosenwasser

Manager, Regulatory Affairs

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

The second secon

CORROSIVE

CAUSES IRREVERSIBLE EYE DAMAGE EYE CONTACT MAY CAUSE LOSS OF VISION. HARMFUL IF SWALLOWED, INHALED OR ABSORBED 44 THROUGH THE SKIN

Avoid breathing vapors or spray mist. Do not get in eyes or on clothing. Avoid contact with sidn, in case of contact immediately rinse skin with plenty of water. Get medical attention if irritation persists. Wear protective eyewear (goggles, face shield or safety glasses). Use with adequate ventilation. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash clothing before reuse.

PERSONAL PROTECTION EQUIPMENT (PPE):

- -Applicators and other handlers must wear.
- -Coveralis worn over long sleeeved shirt and long pants.
- -Chemical resistant footwear plus socks. -Googles or face shield.
- -Chemical-resistant gloves(such as barrier laminate, butyl rubber, neoprene rubber, nitrile rubber, polyvinyl chloride (PVC and viton).

FOR CLEANING EQUIPMENT:

-Chemical-resistant apron.

Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions exist for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

User Safety Recommendations

Users should wash hands before drinking, chewing gum, using tobacco, or using the toilet. Users should remove clothing immediately if pesticide gets

inside. Then wash thoroughly and put on clean clothing. Users should remove personal protective equipment immediately after handling this product. Wash outside of gloves before removing. As soon as possible wash thoroughly.

WARRANTY

Seller warrants that this product conforms to its chemical description afti is reasonably fit for the purposes stated on the label when used in accordance with label directions under normal conditions of use, but neither this warranty nor any other warranty of MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, express or implied, extends to the use of this product contrary to label instructions, or under abnormal conditions, or under conditions natureasonably foreseeable Seller, and Buyer assumes the risk of any such use.

BIOBROM® C-105L

A MICROBIOCIDAL BACTERICIDE, FUNGICIDE, ALGAECIDE AND SLIMICIDE, USED IN TREATING RECIRCULATING COOLING. WATER IN INDUSTRIAL COOLING SYSTEMS, PAPER MILLS. BREWERY PASTEURIZER WATER, METALWORKING CUTTING FLUIDS, NON-POTABLE REVERSE OSMOSIS SYSTEMS, ENHANCED OIL RECOVERY SYSTEMS, AIR-WASHER SYSTEMS, INDUSTRIAL PRESERVATION APPLICATIONS AND PUBLICLY-OWNED TREATMENT WORKS.

ACTIVE INGREDIENT:	2,2-Dibromo-3-nitrilopropionamide	5.49%
NERT INGREDIENTS:	***************************************	94.51%
jet i	TOTAL:	100.00%

2.5 pounds BIOSROM® C-105L liquid per gallon.

KEEP OUT OF REACH OF CHILDREN

DANGER

See side panels for additional precautionary statements		
FIRST AID		
If in eyes	 Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice. 	
f inhaled	 Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to -mouth, if possible. Call a poison control center or doctor for further treatment advice. 	
If on skin or clothing	 Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. 	
If swallowed	 Call poison control center, or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person. 	
	oduct container or label with you when calling a	

poison control center or doctor, or going for treatment.

- YOU MAY ALSO CONTACT 1-800-420-9236 FOR
- EMERGENCY MEDICAL TREATMENT INFORMATION.

NOTE TO PHYSICIAN

*Probable mucosal damage may contraindicate the use of gastric lavage."

WASH OROUGHLY AFTER HANDLING

ENVIRONMENTAL HAZARDS

This product is toxic to fish and aquatic organisms. Do not contaminate water by cleaning of equipment or disposal of waste. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

CHEMICAL AND PHYSICAL HAZARDS

Reaction with strong reducing agents may be explosive. Avoid misting

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage and disposal.

PESTICIDE STORAGE:

Store in a dark, cool, dry, well-ventilated area, not above 104°F (40°C), in well-closed original containers, away from energy sources, combustible organic materials, oxidizers and moisture

PESTICIDE DISPOSAL:

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for ouidance

CONTAINER DISPOSAL:

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

SPILLS:

When handling or dealing with spills, use impact-resistant goggles with side shields, or face shield; wear body-covering clothes, including impervious rubber gloves and boots; use a respirator if misting occurs. Cover wet spills with 10% sodium bicarbonate solution, water and then an inert absorbent before sweeping up and disposing as described for pesticide disposal. If drum contents are contaminated or decomposing, isolate unsealed drum in the open or in a well-ventilated area: flood with 10% sodium bicarbonate solution and large volumes of water if necessary.

KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE TO MAINTAIN PRODUCT QUALITY, STORE IN THE DARK AT TEMPERATURES BELOW 104°F (40°C). DO NOT SHIP WITH FOOD, FEEDS, DRUGS, OR CLOTHING DO NOT SMOKE, DRINK, OR EAT WHEN HANDLING

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and

DIRECTIONS FOR TREATING INDUSTRIAL RECIRCULATING COOLING WATER IN INDUSTRIAL COOLING SYSTEMS

NOTE: Add BIOBROM C-105L separately to the system. Do not mix it with other additives. so as to avoid decomposition of BIOBROM C-105L due to the high pH of many additive formulations. Add BIOBROM C-105L to the basin (or any other point of uniform mixing). Addition should be made via a metering pump; it may be continuous or intermittent. depending on the severity of the contamination when treatment is begun, and the insystem retention time. Optimum performance with this product is achieved by continuous or intermittent treatment. If "shock" treatment is used, the blowdown should be discontinued for 24-48 hours.

FOR CONTROL OF BACTERIA

Add 0.00380-0.0380 gallons of BIOBROM C-105L / 1000 gal, of water in the system depending on the severity of contamination.

INTERMITTENT OR SLUG METHOD

initial Dose: When the system is noticeably fouled, add 0.0192-0,0380 gai, of BIOBROM C-105L / 1000 gal. of water in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 0,0096-0,0380 gat, of BIOBROM C-105L / 1000 gal. of water in the system every 4 days, or as needed to maintain control. Badly fouled systems must be cleaned before treatment is beoun, **CONTINUOUS FEED METHOD**

initial Dose: When the system is noticeably fouled, add 0.0192-0.0380 gal. of BIOBROM C-105L / 1000 gal, of water in the system.

'ubsequent Dose: Maintain this level by pumping a continuous feed of 0.00380-0.0192 il. of BIOBROM C-105L / 1000 gal. of water in the system lost by blowdown. Badly ouled systems must be cleaned before treatment is begun.

FOR CONTROL Add 0.116-0.38 depending on th NTERMITTENT Initial Dose: Wi C-105L / 1000 g Subsequent D BIOBROM C-10 control. Badly for CONTINUOUS Initial Dose: Wi C-105L / 1000 o Subsequent D 0.116-0.380 cal fouled systems (

DIRECTIONS F NOTE: Add BH additives, so as many additive for growth in pulp, 2.00 lbs./ton (i intermittent, der Addition is via distribution of B Jordan inlet or tanks. Heavily t lbs. of BIOBRO Moderately for BIOBROM C-10 Subsequent rate (dry) of paper of stime may caus advisable. Sligi of BIOBROM C added on an inti DIRECTIONS F

For controlling systems and pe water or before BIORROM C-10 depending on t membrane man Add BIOBROM gals of feedwate waters should t with feedwater : or below values must be cleaned FOR CONTROL Initial Dose: W the rate of 0.2 treatment interv specified by qui-Subsequent Do at the rate of 0.1 maintain control manufacturer. FOR CONTROL Initial Dose: Wi at the rate of a Minimum treato achieved or a: manufacturer.

DIRECTIONS WATER BIOBROM C-10 heen diluted in growth of bacte

Subsequent Do

at the rate of 1

needed to main

membrane man

containing water, add this product to the fluid in the collection tank Additions should be made with a matering pump.

Initial or Sing Dose: When the system is noticeably fouled, add BIOBRIOM C-10SL at the rate of 1.1 gais (2.65 lbs) per 1000 gais of metalworking fluid in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add BIOSROM C-105L at the rate of 0.4 to 0.8 gel (1.06 to 2.12 ths) per 1000 gais of matakeoridag fluid per day, or as needed to maintain control. Additions of BIOSROM C-105L product can be made continuously or intermittently. Slug the system as required.

DIRECTIONS FOR TREATING BREWERY PASTEURIZER WATER

For controlling (or inhibiting) the growth of bacteria, fungi and years in brewery pasteurizing water systems, add BIOBROM C-105L at a point in the system to incure uniform mixing.

initial or Sius Dose: When the system is noticeably fouled, add BIOBROM C-105L at the rate of 1.1 gais (2.65 lbs) per 1000 gais of water in the system. Repeat until control is achieved.

Subsequent Dose: When microbiel control is evident, add BIOBROM C-105L at the rate of 0.4 to 0.8 gal (1.06 to 2.12 lbs) per 1000 gals of water per day, or as needed to maintain control. Additions of BIOBROM C-105L. product can be made continuously or intermittently. Slug the system as required. Badly fouled systems must be cleaned before treatment is begin.

DEFECTIONS FOR TREATING ENHANCED OIL RECOVERY SYSTEMS

NOTE: Add BIOBROM C-105L separately to the system. Do not mix it with other additives, so as to avoid decomposition of BIOBROM C-105L due to the high pH of many additive formulations. Addition of BIOBROM C-105L may be made at the free water knockouts, before or after the injection curros and injection well headers. For controlling stime-forming bacteria; sulfide-producing bacteria, yeasts, and fungi in oil field water, polymer or miceliar floods, water-disposal systems, or other oil field water systems, add 1-80 part BIOBROM C-105L (0.4 - 25.6 gallons of BIOBROM C-105L par 2400 barrels of water) depending on the severity of contamination. Additions should be made with a metering pump either continuously or · 人名英格兰 (基本文本 节25)

CONTINUOUS FEED METHOD

When the system is noticeably fouled, add 10-80 ppm BIOSIROM C-105L (3.2-25.6 cals. of BIOBROM C-105L per 2400 barrels of water) continuously until the desired degree of control is achieved. Subsequently, treat with 1-15 porn BIOBROM C-105L (0.4-4.8 gals, of BIOBROM C-105L per 2400 barrels of water) continuously or as needed to maintain control. INTERMITTENT OR SLUG METHOD

When the system is noticeably fouled or to maintain control of the system, add 10-80 ppm BIOBROM C-105L (3.2-25.6 gats. of BIOBROM C-106L per 2400 barrals of water) intermittently for 4-8 hours per day and from 1-4 times per week, or as needed depending on the severity of contamination. NOTE: For control of bacteria, yeast, and fungi in aqueous solutions of biopolymer used in flooding operations, add 15-80 ppm BIOBROM C-105L (4.8-25.6 gais, of BIOBROM C-105L per 2400 barrels of water). Additions of EXCEROM C-105L should be made with a metering pump immediately after

preparation of the aqueous biopolymer solution to reduce loss of viscosity.

DIRECTIONS FOR TREATING AIR-WASHER SYSTEMS

Add 0.06 - 0.38 gallons BIOBROM C-105L / 1000 gall of water in the system, depending on the severity of contamination, to control stime-forming bacteria. and funci in industrial air washing systems.

Intermittent or Slug Method

Initiat Dose: When the system is noticeably fouled, add 0.012 - 0.380 gal BIOEROM C-105L / 1000 gal of water in the system. Repeat until control is

Subsequent Dose: When microbial control is evident, ard 0 006 x 0 188 gal BIOBROM C-105L / 1000 gal of water in the system every C days, cras e a needed to maintain control. Badly fouled systems must be cleaned before treetment is begun.

CONTINUOUS FEED METHOD

25 G 100

Initial Dose: When the system is noticeably fouled, add 0.012 - 0.360 page BIOBROM C-105L / 1000 gal of water in the system. . .

Subsequent Does: Maintain this level by numeings continuous test of 0.006 - 0.188 gal BIOBROM C-105L / 1030 Cat Cl widersn the system per " day. Badly fouled systems must be cleaned before treatment is before NOTE: For use only in industrial air-washer systems that maintain affective grist aliminating components.

DIRECTIONS FOR INDUSTRIAL PRESERVATION APPLICATIONS EXCERCIAL C-105L may be used to reduce microbiological contamination in trair materials and/or products such as: aqueous paints and coalings, polymers, sturries, adhesives, latex and resin emulsions, sizing, caulk, process water, along with specialty industrial products including: inks, polishes, waxes, detergents, and cleansers. 4.4

TO REDUCE MICROBIOLOGICAL CONTAMINATION

Add BIOBROM C-10SL to the meterial or product at a concentration of 25 to 2,000 ppm by weight. This concentration is acuivalent to 11.2 to 896.0 fluid ounces BIOBROM C-105L per 1,000 gallons or 85.6 to 6,848.0 milliliters BIOBROM C-105L per 1,000 liters. The required concentration will depend on the material being treated and the level of contamination present.

DIFFECTIONS FOR TREATING PUBLICLY-OWNED TREATMENT WORKS TO CONTROL COLIFORM AND OTHER BACTERIA

Add BIOBROM C-105L at a concentration of 1.0 to 10.0 ppm by weight of water being treated, depending on the severity and contamination in the system. Addition should be CONTINUOUS and should be made with a metering pump at a point in the system where mixing will be rapid and thorough. Add BIOBROM C-105L to the system in a location where contact time will be 30 minutes or greater before reaching the outtail.

TO USE AS A CO-TREATMENT WITH CHLORINE Add 9.4 -1.5 ppm BIOBROM C-105L by weight of water treated. Chlorination should

result in a minimum detectable residual (i.e., greater than zero but less than the NPDES permit level) Addition should be CONTINUOUS and made at a point just after initial chiorine moing. Repid mixing is necessary for maximum effectiveness. BIOBROM C-105L should be added at a location where a contact time of 10 minutes or longer will be provided before reaching the outfall.

> MANUFACTURED IN ISRAEL FOR: AMERIBROM, INC. 2115 LINWOOD AVENUE FORT LEE, NJ 07024 (201) 242-6560

EPA Reg. No. 8622-63	EPA Est. No. 61688-AL-01
NET CONTENTS:	GALS.(LBS.)

AMB2/04

11/02