

MITCO CC-13-L ALGICIDE

FOR CONTROLLING GROWTH OF ALGAE IN INDUSTRIAL RECIRCULATING WATER COOLING SYSTEMS

COMPOSITION

	Per cent
Active ingredient	70.0
Poly (oxyethylene (dimethyliminio) ethylene (dimethyliminio) ethylene dichloride)	30.0
Inert ingredient	30.0
Weight per gallon	8.9 pounds
Weight of active ingredient per gallon	2.67 pound

EPA Reg. No. 8637-6

APPLICATION

Mitco CC-13-L Algicide is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 1.9 to 4.75 fluid ounces of Mitco CC-13-L Algicide per 1000 gallons of water, to provide a concentration of 16 to 40 parts per million of Mitco CC-13-L Algicide based on the total weight of water in the system is recommended. Subsequent slug additions of 0.47 to 4.75 fluid ounces of Mitco CC-13-L Algicide per 1000 gallons of water (4 to 40 parts per million of Mitco CC-13-L Algicide) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CAUTION

KEEP OUT OF THE REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food. Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

This product is toxic to fish. Do not add treated effluent to lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Use only directed on label.

DISTRIBUTED BY

Mitco INC.

1601 STEELE AVE., S. W. GRAND RAPIDS, MICHIGAN

✓ Net contents shown elsewhere on container

ACCEPTED