

MITCO CC-17-L ALGICIDE

FOR CONTROLLING GROWTH OF ALGAE IN INDUSTRIAL RECIRCULATING WATER COOLING SYSTEMS

COMPOSITION

	Percent by weight
Active ingredient	60.0 percent
Poly [oxyethylene (dimethyliminio) ethylene (dimethyliminio) — ethylene dichloride]	60.0 percent
Inert ingredient	40.0 percent
Weight per gallon	9.6 pounds
Weight of active ingredient per gallon ...	5.76 pound

EPA Reg. No. 8637-11

APPLICATION

MITCO CC-17-L ALGICIDE is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algae growth, microbiological slime and other deposits. An initial slug addition of 0.9 to 2.2 fluid ounces of MITCO CC-17-L ALGICIDE per 1000 gallons of water to provide a concentration of 8 to 20 parts per million of MITCO CC-17-L ALGICIDE based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 0.2 to 2.2 fluid ounces of MITCO CC-17-L ALGICIDE per 1000 gallons of water (2 to 20 parts per million of MITCO CC-17-L ALGICIDE) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CAUTION

KEEP OUT OF THE REACH OF CHILDREN

Harmful if swallowed. Do not get in eyes. Avoid contact with skin. If contact occurs, wash thoroughly with water. For first aid, consult physician or poison control center. For more information, see back of container.

This product is not intended for use in drinking water. Do not use in areas where it may be consumed. Do not use in areas where it may be inhaled. Do not use in areas where it may be absorbed through the skin.

Keep this and all containers tightly closed. Do not use if container is damaged or leaking. Do not use if contents are empty. Do not use if contents are expired.

DISTRIBUTED BY

Mitco INC.

1100 E. AVE. S.W. GRAND RAPIDS, MICHIGAN 49508

Net contents shown elsewhere on container.

MITCO CC-17-L ALGICIDE

FOR CONTROLLING GROWTH OF ALGAE IN INDUSTRIAL RECIRCULATING WATER COOLING SYSTEMS

COMPOSITION

	Percent by weight
Active ingredient	60.0 percent
Poly[oxyethylene (dimethylamino)ethylene (dimethylamino)ethylene dichloride]	60.0 percent
Inert ingredient	40.0 percent
Weight per gallon	9.6 pounds
Weight of active ingredient per gallon	5.76 pound

EPA Reg. No. 8637-11

APPLICATION

MITCO CC-17-L ALGICIDE is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algae growth, microbiological slime and other deposits. An initial slug addition of 0.9 to 2.2 fluid ounces of MITCO CC-17-L ALGICIDE per 1000 gallons of water to provide a concentration of 8 to 20 parts per million of MITCO CC-17-L ALGICIDE based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 0.2 to 2.2 fluid ounces of MITCO CC-17-L ALGICIDE per 1000 gallons of water (2 to 20 parts per million of MITCO CC-17-L ALGICIDE) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CAUTION

KEEP OUT OF REACH OF CHILDREN

MITCO INC.