

Harmful if swallowed. Skin and eye contact may cause severe irritation. Avoid contact with skin and eyes.

### ANTIDOTE INTERNALLY:

Feed cooked cereal or egg white followed by olive oil or cooking oil. Call a Physician.

#### **EXTERNALLY:**

Immediately flood with cold water. Call a Physician for eyes or if skin irritation persists.

OO NOT MIX WITH ACID DETERGENTS.

USE DILUTE SOLUTIONS ONLY AS DIRECTED ON LABEL.

AS LIGHT AND HEAT WILL REDUCE STRENGTH

## TABLE OF DILUTIONS:

### AVAILABLE CHLORINE

800 P.P.M. Use 4 oz in 3 gal water

200 P.P.M. - Use 1 oz ın a 3 gal water

T.U P.P.M. - Use 16 oz iņ 10,000 gal water

0.5 P.P.M. - Use 1 oz in 1200 gal water

(P.P.M. means - Parts available chlorine per million parts of water)

Degrades with age. Use a test kit and increase dosage as necessary to obtain required level of available chlorine.

SECONOMICAL DE LA CONTRACTION DE LA CONTRACTION

EPA NO. 25024- 2

· 11973

Contract of the Table 1

INA

s b.

a'

PMF 🦠

SOFT FOR STANK

ESODIUM HY SOLU

> CHLORINE-BEARING FOR WATER CHLORINA

Active Ingredient: Sodium I Inert Ingredient by wt.

RINSE EMPTY CONTAINER THORO

CAUTION: Keep out of reach of child

See side panel for additional caution



## PRECISION CL-2152

(EPA Reg. No. 11621-2)

	Percent by weigh
Active ingredient	. 15.0 percent
Poly(oxyethylene(dimethyliminio)ethylene (dimethyliminio)ethylene	•
dichloride) 15 percent	
Inert ingredient	. 85.0 percent
Weight per gallon	8.58 pounds 1.29 pound
APPLICATION	

Precision CL-2152 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 3.9 to 9.75 fluid ounces of Precision CL-2152 per 1000 gallons of water, to provide a concentration of 32 to 80 parts per million of Precision CL-2152 based on the total weight of water in the system is recommended. Subsequent slug additions of 1.0 to 9.75 fluid ounces of Precision CL-2152 per 1000 gallons of water (8 to 80 parts per million of Precision CL-2152) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

# **CAUTION** KEEP OUT OF THE REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food.

This product is toxic to fish. Do not add treated effluent to lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal or waste. Use only as directed on label.

Do not reuse empty drum. Esturn to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

ACCEPTED

N'ET CONTENTS 55 GALLONS

PRECISION CHEMICALS, INC. Atlanta, Georgia 30325