For: Cooling Towers



ALGAECIDE BRIQUETTES

Kills Algae Controls Slime Formation Noncorrosive to Metal

For use in recirculating water cooling towers and evaporative condensers where water is not used for drinking or bathing purposes.

Slime in water cooling tower is likely to be composed of algae, bacteria and fungi.

DIRECTIONS

Use 6 to 12 briquettes per 1000 gallons of water in a clean system, repeated as needed to obtain control, followed by 3 to 6 briquettes per 1000 gallons of water weekly, or as needed. Briquettes are to be placed in sump.


Sodium salts of other

WARNING: Harmful or fatal if swallowed. Do not breathe dust or spray mist. Wash thoroughly after handling. Do not get in eyes, on skin or on clothing. In case of swallowing, induce vomiting by administering warm salt water (one tablespoon per glass) or other emetic. Call a physician.

This product is toxic to fish and wildlife. Do not discharge treated effluent into lakes, streams or ponds. Solution will kill grass and shrubs.

Do not reuse empty container. Destroy it by burying with waste or burning. Stay away from smoke or fumes.

KEEP OUT OF REACH OF CHILDREN



NET CONTENTS 50 LBS.

Sold By PRECISION CHEMICALS, INC. Atlanta, Georgia 30325 USDA REG. No. 8728-2

For: Evaporative Condensers