

PRECISION CL-2151

(EPA Reg. No. 11621-2)

	Percent by weigh
Active ingredient	. 7.5 percent
Poly(oxyethylene(dimethyliminio)ethylene (dimethyliminio)ethylene dichloride)	·
Inert ingredient	. 92.5 percent
Weight per gallon	
APPLICATION	

Precision CL-2151 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 8.0 to 20 fluid ounces of Precision CL-2151 per 1000 gallons of water, to provide a concentration of 64 to 160 parts per million of Precision CL-2151 based on the total weight of water in the system is recommended. Subsequent slug additions of 2.0 to 20 fluid ounces of Precision CL-2151 per 1000 gallons of water (16 to 160 parts per million of Precision CL-2151) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CAUTION KEEP OUT OF THE REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food.

This product is toxic to fish. Do not add treated effluent to lakes streams or pends. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label.

Do not reuse empty drum. Roturn to drum reconditioner or destroy by perforating or crusning and burying in a safe place.

ACCEPTED

NET CONTENTS 55 GALLONS

PRECISION CHEMICALS, INC.

Atlanta, Georgia 30325

THE FEDERAL INSECTICIDE
FUR DE AND RODENTIQUE ACT

1 January 8728-6