

8788-18

1063.

Pm 21

Front Panel

EXTERIOR CLEAR WOOD PRESERVATIVE

Does not contain Penta* (*Pentachlorophenol)

ACTIVE INGREDIENTS:

Methylene bis(thiocyanate) 0.50%

2-(Thiocyanomethylthio)benzothiazole 0.50%

Inert Ingredients 99.00%

One Gallon

KEEP OUT OF REACH OF CHILDREN

WARNING

See Back Panel for Additional Precautionary Statements


This product weighs 7.50 pounds per gallon

ACCEPTED
with COMMENTS
in EPA Letter Dated:

AUG 28 1986

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.

8788-18



Side Panel

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

WARNING. Causes eye damage and skin irritation. Harmful if swallowed or absorbed through skin. This product may cause skin sensitization. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling.

Avoid breathing vapors or mist. [To avoid overexposure to solvent vapors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC-23C or equivalent) or leave the area.] Do not take internally.

[NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.]

STATEMENT OF PRACTICAL TREATMENT: In case of skin contact, wash promptly and thoroughly with soap and water. In case of eye contact, flush immediately with copious amounts of clean, cool water for 15 to 20 minutes. Get medical attention immediately. If swallowed, call a physician or Poison Control Center. Drink a large quantity of milk, egg whites or gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not apply directly to water. Permits may be required for discharges containing this pesticide into lakes, streams, ponds or public water. For guidance, contact the regional office of the Environmental Protection Agency.

PHYSICAL AND CHEMICAL HAZARDS: Combustible. Do not use or store near heat or open flame.

STORAGE: Keep container closed when not in use. Store in a cool place. Leaking or damaged containers should be placed in a plastic bag and discarded in trash. All pesticides should be stored away from food.

DISPOSAL: Do not reuse empty can. Securely wrap original container in several layers of newspaper and discard in trash.

KEEP OUT OF REACH OF CHILDREN

Manufactured by: DeSoto, Inc./1700 S. Mount Prospect/Des Plaines, IL 60017

The above precautionary labeling includes wording in brackets. These words were inserted due to the National Paint and Coating Association (NPCA) solvent toxicity labeling program (See attached brochure). DeSoto believes that this language is important, but we do not want to delay approval of this label. If at the time of label review this language is not approved, please approve the label without the solvent toxicity language.

Side Panel

PRESERVATIVE

- *Clear wood preservative...for bare wood before staining, painting, or varnishing.
- *Superior formulation...maximum protection on decks, railings, patio furniture, siding, shingles, millwork and structural lumber.
- *Penetrates deeply...protects against mildew, rot, decay--repels termites.
- *DIRECTIONS FOR USE:
It is a violation of Federal law to use the product in a manner inconsistent with its labeling.

GENERAL INSTRUCTIONS: Brush away loose dirt. Wash with Heavy-duty Cleaner and rinse. For mildew see instructions below. Fill cracks, open construction and knot holes with Caulk.

SPECIFIC INSTRUCTIONS: Remove mildew by scrubbing with a mixture of 1/3 cup Heavy-duty Cleaner, 1 qt. household chlorine bleach and 3 qts. warm water. Use a long handled scrub brush. Rinse completely.

NOTE: DO NOT USE DETERGENTS CONTAINING AMMONIA!

WEAR RUBBER GLOVES AND SAFETY GLASSES. AVOID SKIN AND EYE CONTACT. DO NOT BREATHE FUMES!

APPLICATION TOOLS: *Use roller or Paint Pad or Brush.

APPLICATION: *Surface should be thoroughly dry before application. *Apply generously, soaking wood thoroughly, especially end grain, joints and cracks.

*Re-treat cuts and holes made after initial application. *For maximum protection apply 2 coats. *When painting, staining or varnishing over treated wood surface, be certain wood is thoroughly dry. (At least 24 hours with average humidity conditions). *For extra protection--studs, joists and posts can be dipped for up to 30 minutes. *Apply at temperatures above 40°F.

CLEAN-UP: Clean tools immediately after use with thinner or Brush Cleaner.

COVERAGE: Up to 200 square feet per gallon. Dipping boards for 3 minutes may require up to 2 gallons per 100 board feet.

PROTECT FROM FREEZING: Do not use additives. Do not thin.

