

# RPM

Manufactured Exclusively by  
REPUBLIC POWDERED METALS - MEDINA, OHIO 44256, U.S.A.

## STOP-ROT Wood Preservative & Soil Poison for Termites

### ACTIVE INGREDIENTS:

Pentachlorophenol	4.56%	
Other Chlorophenols	.54%	5.10

### INERT INGREDIENTS:

Diacetone Alcohol		5.69
Mineral Spirits		89.00
Other Inert		.21

100.00

**CAUTION:** Keep out of reach of children.  
See right panel for additional cautions.

**ANTIDOTE:** External — Wash with soap and water. Internal — Call physician. Cause patient to vomit by use of warm water and salt. Repeat until vomit fluid is clear. Have patient lie down and keep warm.

LIQUID GALLON

U.S. MEASURE

• VARNISHES • ENAMELS

# RPM

REPUBLIC POWDERED METALS MEDINA OHIO 44130 U.S.A.

## STOP-ROT Wood Preservative & Soil Poison for Termites

### ACTIVE INGREDIENTS:

Pentachlorophenol	4.56%	
Other Chlorophenols	.54%	5.10%

### INERT INGREDIENTS:

Diacetone Alcohol		5.69%
Mineral Spirits		89.00%
Other Inert		.21%

100.00%

### CAUTION:

Keep out of reach of children.  
See right panel for additional cautions.

### ANTIDOTE:

External — Wash with soap and water. Internal — Call a physician. Cause patient to vomit by use of warm water and salt. Repeat until vomit fluid is clear. Have patient lie down and keep warm.  
LIQUID GALLON

U. S. MEASURE

# DIMM

**ACCEPTED**  
JUN 10 1968  
UNDER THE F.E. ... ICIDE  
FUNGICIDE AND RODENT C. DE ACT  
FOR ECONOMIC POISON REGISTERED  
ED UNDER NO. 8-790-1 SUBJECT  
TO ATTACHED COMMENTS.

ALS MEDINA, OHIO 44256, U.S.A.

## P-ROT Preservative & n for Termites

4.56%	
ils .54%	5.10%
<hr/>	
	5.69%
	89.00%
	.21%
<hr/>	
	100.00%

of reach of children.  
for additional cautions.  
h with soap and water. Internal -- Call a phy-  
tient to vomit by use of warm water and salt.  
mit fluid is clear. Have patient lie down and  
U. S. MEASURE

**FOR SUBTER**  
Apply STOP-  
but not below  
shallower. Tr  
around the  
gallon STOP-  
including bac  
ROT per 5 li  
15 inches dee  
porches and  
the house.  
**WHERE POW**  
already in pl  
or swab app  
hardwood lum  
minute dip c  
ment per inc  
any larvae th

**FOR PROTE**  
**TREAT WOO**  
**STRUCTION.**  
**OPEN TANK**  
All lumber s  
dried to belo  
above ground  
minutes per  
ground or in  
sion of 30 to  
drop-siding,  
inch of thick  
frames 3 mir  
bundled lum  
all glass oper  
ing. Figure c  
board feet fo  
feet for bru  
moisture pick  
grain moistur  
is extremely