



E-Z CLOR SUPER-90[®] CLOR PAC

Automatic swimming pool chlorination
KEEP OUT OF REACH OF CHILDREN
DANGER

See first aid and other precautions on back panel
Active ingredient: Trichloro-s triazinetrione 100%
Available chlorine 90%

NOTE: Remove this wrapper and tape at bottom of CLOR PAC before using. Do not remove CLOR PAC until empty.

Net contents: 4 lbs (1.81 Kg)

INSTRUCTIONS

If water is not already conditioned, add CYANURIC ACID Stabilizer to pool water. Follow directions and precautions on the label for that product. Adjust water pH to 7.2 to 7.6 using E-Z CLOR pH Up or Down, according to label directions or precautions for that product, before starting E-Z CLOR FEEDER.

TO START CHLORINATION

1. Select numbered dimple on CLOR PAC according to guide below, and push punch through up to shank. Also punch out unnumbered dimples at bottom of both sides of CLOR PAC.

APPROX. POOL GALLONS & STARTING NUMBER
(BASED ON 24-HR. CONTINUOUS EQUIPMENT OPERATION)

5,000 Gallons—No. 1	25,000 Gallons—No. 5
15,000 Gallons—No. 3	35,000 Gallons—No. 7

2. Remove tape from slot at bottom of CLOR PAC and place in feeder.

TO ADJUST CHLORINATION

Test pool water after 24 hours. If less than 1.0 ppm, punch out next higher number. If more than 2.0 ppm, cover hole with black electrical tape and punch out next lower number. Make additional adjustments as required to maintain an average 1.5 ppm residual.

CHECK PERIODICALLY

1. Withdraw and shake CLOR PAC to see tablet level. Insert new CLOR PAC when old one is almost empty.
2. Check chlorine residual with E-Z CLOR or other good test kit. Residual of 1.0-2.5 ppm recommended.
3. Check pH and adjust with E-Z CLOR pH Up or Down to proper range of 7.2 - 7.6, according to label directions or precautions for that product.

IMPORTANT: When using punch, push all the way in and turn to get clean, full size hole.

DANGER: KEEP AWAY FROM
eye damage. May be fatal if swallowed or on clothing. Irritant to skin and breathing dust. May cause dizziness after handling.

FIRST AID: If swallowed, do not induce vomiting. If in eyes, flush with cold water for 15 minutes. If on skin, remove clothing and wash with soap and water. Seek medical attention. Remove before reuse.

DANGER: STRONG OXIDIZER
Use clean dry utensils. Do not mix with other chemicals. Store in a cool, dry, well-ventilated area. Keep away from open flame. Decompose harmful gases. In case of fire, use dry chemical or carbon dioxide. Keep container tightly closed and store in a cool, dry place before discarding.

ENVIRONMENTAL HAZARD
Treated effluent should not be discharged into lakes, streams, ponds, or other bodies of water. Do not contaminate water by disposal of wastes. Apply this product as directed.

DO NOT REUSE OR DESTROY WHEN

EPA REG. NO. 8791-2
EPA EST. NO. 8791-MQ
Mfd. Under Patent No. 3,411,111

E-Z CLOR SYSTEMS
A division of Airwick Products
4 CERMAK BLVD., ST. LOUIS, MO. 63103

DANGER: KEEP AWAY FROM CHILDREN. Corrosive, causes eye damage. May be fatal if swallowed. Do not get in eyes, on skin or on clothing. Irritating to nose and throat. Avoid breathing dust. May cause burns to broken skin. Wash hands after handling.

FIRST AID: If swallowed feed gruel, cooked cereal, or bread soaked in milk, followed by olive oil or cooking oil. In case of personal contact, remove excess material and flush skin or eyes with cold water for at least 15 minutes. For eyes get medical attention. Remove and wash contaminated clothing before reuse.

DANGER: STRONG OXIDIZING AGENT. Mix only with water. Use clean dry utensils. Contamination by moisture, organic matter, or other chemicals may liberate hazardous gases. Store in a cool, dry, well-ventilated area away from heat or open flame. Decomposes at 350°F-475°F, with liberation of harmful gases. In case of decomposition, if possible, isolate container in open air. Flood with large amounts of water. Keep container tightly closed when not in use. Rinse empty container thoroughly with water to dissolve all material before discarding.

ENVIRONMENTAL HAZARDS: This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public waters. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on the label.

**DO NOT REUSE CONTAINER.
DESTROY WHEN EMPTY.**

EPA REG. NO. 8791-2 969532-810
EPA EST. NO. 8791-MO-1 900145
Mfd. Under Patent No. 3390695

E-Z CLOR SYSTEMS
A division of Airwick Pool Products, Inc.
4 CERMAK BLVD., ST. PETERS, MO. 63376