

DIRECTIONS FOR USE

For Algae Prevention and Control in Swimming Pools. For prevention and control of the algae species listed below, premix the desired quantity of Algi-Kleer with water. The resulting slurry may be poured into the skimmer or evenly distributed around the edge of the pool. There is no waiting to swim after application. Water temperatures of 50 degrees F or greater result in faster algae control. The effectiveness of Algi-Kleer is not influenced by the normal range of pool water pH.

Algi-Kleer is compatible with all pool additives, and is non-corrosive to pool filters, heaters, piping and fittings. Pool filtering systems will not reduce the effectiveness of Algi-Kleer. Algi-Kleer removes the need for excessive quantities of chlorine to combat algae.

FIRST AID

Harmful if swallowed. Do not let dust or powder contact eyes—In case of contact flush with large amounts of water for 15 minutes, and get medical attention. Avoid contamination of food. Rinse empty container thoroughly with water.

ENVIRONMENTAL HAZARDS

Treated water should not be discharged where it will drain into lakes, streams, ponds and public water. Do not allow filter backwash or treated water from pool to contact grass or plants since they may be killed. Apply this product only as specified on this label.

POOL FORMULA

To calculate pool volume of rectangular or square pool, multiply in feet, the length x width x average depth x 7.5. For a round or oval pool, multiply in feet, the length x width x average depth x 5.9.

Preventive Algae Treatment. Apply at the rate of 1½ oz. per 10,000 gallons (0.8 ppm active ingredient) of pool water that is visibly clean. Repeat treatment every 8 to 10 weeks or when algae reappears. (See dosage chart)

Green Algae Control. Apply first application at the rate of 2 oz. per 10,000 gallons of pool water (1.2 ppm active ingredient) when algae growth is first visible. Seven days after treatment, brush algae growth from walls, vacuum out settled algae and immediately begin preventive algae treatment. (See dosage chart)

Black Algae Control. Apply first application at the rate of 2½ oz. per 10,000 gallons of pool water (1.6 ppm active ingredient) when algae growth is first visible. For faster results, remove top of algae growth with wire brush daily and vacuum out settled algae. After seven days, begin preventive treatment. (See dosage chart)

Schedule	DOSAGE PER 10,000 GALLONS		
	WEIGHT Oz	VOLUMETRIC	
Preventive	1½	7¼	½
Green Algae	2	11	¾
Black Algae	2½	14½	1

900545 EPA REG. NO. 8791-14
951035-609 EPA EST. NO. 8791-MO-1

Packaged by
E-Z CLOR SYSTEMS
A division of Airwick Pool Products, Inc.
4 CERMAK BLVD., ST. PETERS, MO. 63376

