

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS
AND DOMESTIC ANIMALS**

ENVIRONMENTAL HAZARDS

THIS PESTICIDE IS TOXIC TO FISH. DO NOT APPLY IN MARINE OR ESTUARINE OIL FIELDS. DO NOT DISCHARGE EFFLUENT CONTAINING THIS ACTIVE INGREDIENT INTO LAKES, STREAMS, PONDS, ESTUARIES, OCEANS, OR PUBLIC WATERS UNLESS THIS PRODUCT IS SPECIFICALLY IDENTIFIED AND ADDRESSED IN AN NPDES PERMIT. DO NOT DISCHARGE EFFLUENT CONTAINING THIS PRODUCT TO SEWER SYSTEMS WITHOUT PREVIOUSLY NOTIFYING THE SEWAGE TREATMENT PLANT AUTHORITY. FOR GUIDANCE CONTACT YOUR STATE WATER BOARD OR REGIONAL OFFICE OF THE EPA.

***** FLAMMABLE *****

KEEP AWAY FROM HEAT AND OPEN FLAME

PHYSICAL PROPERTIES

SPECIFIC GRAVITY: 1.05
FREEZING POINT: 10°F

STORAGE AND DISPOSAL

STORAGE

COREXIT 7672 OIL FIELD BACTERICIDE SHOULD BE STORED IN AN AREA APPROVED FOR FLAMMABLE PRODUCTS. KEEP DRUM OPENINGS CAPPED TO PREVENT EVAPORATION OR PRODUCT CONTAMINATION. LOSS OF SOLVENT CAN RESULT IN GELLING.

PROHIBITIONS

DO NOT CONTAMINATE WATER, FOOD, OR FEED BY STORAGE OR DISPOSAL.

PESTICIDE DISPOSAL

PESTICIDE WASTES ARE TOXIC. IMPROPER DISPOSAL OF EXCESS PESTICIDE, SPRAY MIXTURE, OR RINSATE IS A VIOLATION OF FEDERAL LAW. IF THESE WASTES CANNOT BE DISPOSED OF BY USE ACCORDING TO LABEL INSTRUCTIONS, CONTACT YOUR STATE PESTICIDE OR ENVIRONMENTAL CONTROL AGENCY, OR THE HAZARDOUS WASTE REPRESENTATIVE AT THE NEAREST EPA REGIONAL OFFICE FOR GUIDANCE.

CONTAINER DISPOSAL

TRIPLE RINSE (OR EQUIVALENT) THEN OFFER FOR RECYCLING OR RECONDITIONING, OR PUNCTURE AND DISPOSE OF IN A SANITARY LANDFILL, OR BY OTHER PROCEDURES APPROVED BY STATE AND LOCAL AUTHORITIES.

ACCEPTED

APR 28 1986

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 8928-4

COREXIT

**7672
OIL FIELD
BACTERICIDE**

**A MICROBIOCIDICIDE FOR USE IN CONTROLLING
BACTERIA IN OIL FIELD APPLICATIONS**

ACTIVE INGREDIENTS	
ALKYL*1,3-DIPROPYLENE DIMINES	30.1%
ACIAL ACETIC ACID	15.0%
ISOPROPANOL	27.1%
INERT INGREDIENTS	27.8%
	100.0%

* 3% C8, 3% C10, 4% C12, 15% C14, 10% C16, 28% C18

DANGER!

CORROSIVE! CAUSES EYE AND SKIN DAMAGE

DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WEAR GOGGLES OR FACE SHIELD, RUBBER GLOVES AND PROTECTIVE CLOTHING WHEN HANDLING. HARMFUL OR FATAL IF SWALLOWED. AVOID CONTAMINATION OF FOOD.

KEEP OUT OF REACH OF CHILDREN

EXXON MANUFACTURED BY
EXXON CHEMICAL AMERICAS

A Division of EXXON CHEMICAL COMPANY, a Division of EXXON CORPORATION
Houston, Texas 77253-3272

CHEMICALS

EPA REGISTRATION NO. 8928-4
MADE IN U.S.A. EPA ESTABLISHMENT NO. 8928-TX-1

1 of 1 # 8928-4 PM 31

STATEMENT OF PRACTICAL TREATMENT

IN CASE OF CONTACT, IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MIN. FOR EYES, CALL A PHYSICIAN. REMOVE AND WASH CLOTHING BEFORE REUSE.

IF SWALLOWED, DRINK PROMPTLY A LARGE QUANTITY OF MILK, EGG WHITES, GELATIN SOLUTION OR IF THESE ARE NOT AVAILABLE, DRINK LARGE QUANTITIES OF WATER. AVOID ALCOHOL. CALL A PHYSICIAN IMMEDIATELY!

NOTE TO PHYSICIAN PROBABLE MUCOSAL DAMAGE MAY CONTRAINDICATE THE USE OF GASTRIC LAVAGE. MEASURES AGAINST CIRCULATORY SHOCK, RESPIRATORY DEPRESSION AND CONVULSION MAY BE NEEDED.

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

COREXIT 7672 IS A COMBINATION BACTERICIDE AND CORROSION INHIBITOR. IT IS PARTICULARLY EFFECTIVE IN KILLING SULFATE-PRODUCING BACTERIA SUCH AS DESULFOHABIBIO DESULFOHABIBIO, AS WELL AS SLIME-FORMING BACTERIA. IT IS ALSO AN EXCELLENT INHIBITOR AGAINST CORROSION BY HYDROGEN SULFIDE, CARBON DIOXIDE, ACIDS AND SALTS DUE TO ITS ABILITY TO FORM TENACIOUS FILMS ON METAL SURFACES.

**WATERFLOODS AND
SALT WATER DISPOSAL SYSTEMS**

CONTINUOUS: USING A SUITABLE CHEMICAL PUMP, INJECT COREXIT 7672 AT 10-50 PPM (APPROXIMATELY 0.4 TO 2.0 GALLONS PER 1000 BARRELS WATER) AT A POINT OF GOOD MIXING SUCH AS THE FLOWLINE UPSTREAM OF THE INJECTION PUMP.

BATCH OR SLUG: INJECT 50-200 PPM COREXIT 7672 (APPROXIMATELY 2-8 GALLONS PER 1000 BARRELS WATER) FOR UP TO 16 HOURS ONCE OR TWICE A WEEK, OR AS NEEDED TO MAINTAIN CONTROL OF THE SYSTEM.

COMBINATION: THIS VARIATION MAY BE NEEDED TO COMBAT SEVERE BACTERIAL PROBLEMS. FOR EXAMPLE, USE WEEKLY BATCH TREATMENTS UPSTREAM OF FILTER (AT HEATER TREATERS, WATER COLLECTION TANKS, OR FLOWLINES), PLUS CONTINUOUS TREATMENT AFTER THE FILTERS AT 10-25 PPM (0.4 TO 1.0 GALLON COREXIT 7672 PER 1000 BARRELS WATER).

**DRILLING MUDS, PACKER
AND WORKOVER FLUIDS**

WHILE THE FLUID IS BEING MADE UP, INJECT COREXIT 7672 AT A SUITABLE CHEMICAL PUMP AT A POINT OF GOOD MIX AT A RATE OF APPROXIMATELY 1200-2400 PPM (5-10 GALLONS PER 1000 BARRELS, OR APPROXIMATELY 1-2 DRUMS PER 1000 BARRELS).

BEST AVAILABLE COPY

**NET WEIGHT 432 LBS (196 KG)
NET VOLUME 55 GAL (U.S.) (208.2 L)**