

Rust-Ban

VY 5528 Organometallic Anti-Fouling Protective Coating

A Hard Drying Coating Highly Resistant to Algae, Barnacles and Other Marine Fouling

ACTIVE INGREDIENTS TRI-BUTYL TIN FLUORIDE 10.40%

INERT INGREDIENTS 89.60%

E.P.A. Reg. No. 8928-12

WARNING! FLAMMABLE!

KEEP AWAY FROM HEAT OR OPEN FLAME.

VAPOR HARMFUL

MAY CAUSE SEVERE EYE BURNS

MAY BE FATAL IF SWALLOWED

MAY CAUSE SKIN IRRITATION

KEEP OUT OF REACH OF CHILDREN

See other Precautions on right panel.

EXXON CHEMICAL COMPANY U.S.A.

Operating division of EXXON CHEMICAL COMPANY, a division of EXXON CORPORATION
Houston, TX 77029

NET CONTENTS 5 U.S. GALLONS • 18.9 LITRES

Made in U.S.A.

EXXON
CHEMICALS

ACCEPTED

JUN 5 1973

UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTER-
ED UNDER NO. 728-12 SUBJECT
TO ATTACHED COMMENTS.

Precautions

Do not get in eyes, on skin, or on clothing.

Personnel applying this paint should wear full face air mask and protective clothing to avoid skin and eye contact. Avoid exposure to vapor or mist. Keep away from heat and open flame. Use with adequate ventilation. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and call a physician; wash skin with plenty of soap and water. Wash contaminated clothing before reuse. Close container after each use.

Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

Directions for Use

Surface should be free of all grease, dirt and rust. Mix thoroughly and apply two

coats of RUST-BAN VY 5528 Anti-Fouling Paint over properly primed surfaces. Apply by roller or brush. While thinning is not normally required, RUST-BAN TH 6866 Thinner should be used when necessary.

Allow two hours drying time between coats. Dry film thickness of each anti-fouling coat should be 1.5 mils. Vessel should not be launched in less than six hours after application of final coat of anti-fouling.

Do not reuse containers. Destroy by perforating or crushing container and burying in a safe place.

RUST-BAN VY 5528 Analysis - Wt. %

Pigment	39.20
Active tri-n-butyltin fluoride	26.50
Inerts	73.50
	100.00
Vehicle	60.80
Non volatiles	14.63
Volatiles	85.37
	100.00 100.00

(G) 5528-a

Trademark Registered