

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS

*** FLAMMABLE ***

KEEP AWAY FROM HEAT AND OPEN FLAME

PHYSICAL PROPERTIES

Specific Gravity	0.868	Solubility in Water	Total
Freezing Point	-65°F	pH at 25°C	6.5 to 9.0

STORAGE AND DISPOSAL

PROHIBITIONS

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

Triple rinse (or equivalent). Then offer to recycling, reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by State and local authorities.

MICROBIOCIDES

A MICROBIOCIDES FOR USE IN CONTROLLING BACTERIA IN OIL FIELD APPLICATIONS

Active Ingredients	
Didecyl Dimethyl Ammonium Chloride	25.0%
Inert Ingredients	75.0%
	<hr/>
	100.0%

Corrosive. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

KEEP OUT OF REACH OF CHILDREN

DANGER

EXXON

CHEMICAL

MANUFACTURED BY
EXXON CHEMICAL AMERICAS

A Division of EXXON CHEMICAL COMPANY, a Division of EXXON CORPORATION

Houston, Texas 77253-3272

EPA Registration No. 8928-15
EPA Establishment No. 8928-TX-1

MADE IN U.S.A.

Measures against circulatory shock, respiratory depression and convulsions may be needed

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

**** USE WITH CLOSED DELIVERY SYSTEMS ONLY ****

OIL FIELD WATERFLOOD

OR SALT WATER DISPOSAL SYSTEMS

DO NOT APPLY IN MARINE AND ESTUARINE OIL FIELDS

1. For control of slime forming and sulfate reducing bacteria in oilfield waterflood or salt water disposal systems, add 20-40 ppm SURFLO B7676 (1-2 gallons per 1000 barrels of water) continuously. Levels for effective control will vary depending on conditions at the site.
2. For intermittent use, dose at a rate of 20-80 ppm SURFLO B7676 (1-4 gallons per 1000 barrels of water) for 4-8 hours per day, one to four times a week as needed to maintain control.

Add SURFLO B7676 directly from the drum with the proper type of metering equipment. This product weighs 7.23 pounds per gallon at 20°C.

DATE: _____
NO TYPIFICATION
LABEL NOT REVIEWED
PER PER NOTICE 02/90

EMERGENCY TELEPHONE NUMBERS:

Exxon Chemical Americas
Chemtrec

713 - 870-6000
800 - 424-9300

NET WT. 398 LBS. (181 KG.)

9/90

NET VOL. 55 GALS. (U.S.) (208.2 LITERS)