

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

KEEP OUT OF REACH OF CHILDREN

Corrosive. Causes severe eye damage and skin damage. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not apply in marine and/or estuarine oil fields. Do not discharge into lakes, streams, ponds, or public waters unless in accordance with an NPDES permit. For guidance contact your Regional Office of the EPA. Do not contaminate water by cleaning of equipment, or disposal of wastes.

**PHYSICAL OR CHEMICAL HAZARDS. FLAMMABLE.
KEEP AWAY FROM HEAT AND OPEN FLAME.**

PHYSICAL PROPERTIES

Specific Gravity at 20/20°C..... 0.963 Solubility in Water at 20°C..... Complete
Freezing Point..... -20°F Solubility of Water at 20°C..... Complete

STORAGE AND DISPOSAL

COREXIT 7766 Corrosion Inhibitor Microbicide should be stored in an area approved for flammable products. Keep down openings capped to prevent evaporation or product contamination.

1. PROHIBITIONS—Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. Do not reuse empty container.
2. PESTICIDE DISPOSAL—Pesticide, spray mixture, or rinse water that cannot be used according to label instructions must be disposed of according to federal or approved state procedures under subtitle C of the Resource Conservation and Recovery Act.
3. CONTAINER DISPOSAL—Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.
4. GENERAL—Consult Federal, State, or local disposal authorities for approved alternative procedures.

CORPENIL 7785

CORROSION INHIBITOR / MICROBIOCIDES

A MICROBIOCIDES FOR USE IN CONTROLLING BACTERIA IN OIL FIELD APPLICATIONS

Active Ingredients:	
n-Alkyl - 1,3 - Propylene diamine	8.4%
Glacial Acetic Acid	4.2%
Isopropyl Alcohol	16.0%
Inert Ingredients:	
14% C ₁₀ , 5% C ₁₂ , 42% C ₁₄ , 15% C ₁₆ , 5% C ₁₈ , 20% C ₂₀	71.4%
	100.0%

Product weighs 8.02 pounds per gallon.

8928-15

KEEP OUT OF REACH OF CHILDREN

DANGER!

STATEMENT OF PRACTICAL TREATMENT

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse.

If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed. See Left Panel For Additional Precautionary Statements.

EXXON
CHEMICALS

MANUFACTURED BY
EXXON CHEMICAL AMERICAS
A DIVISION OF EXXON CHEMICAL COMPANY, A DIVISION OF EXXON CORPORATION
Houston, Texas 77001

MADE IN U.S.A.

EPA REGISTRATION NO. 8928-15
EPA ESTABLISHMENT NO. 9661-TX-1

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.
"COREXIT 7765 is intended for control of anaerobes such as sulfate-reducing bacteria of the species *Desulfovibrio Desulfuricans*."

WATERFLOODS / SALT WATER DISPOSAL SYSTEMS

Add COREXIT 7765 via a chemical metering pump to the water injection system at a point of uniform mixing such as the inlet line to the water holding tank or the injection pump suction line.

Slug treatment:

Initial treatment: Inject via chemical pump 200-400 ppm COREXIT 7765 (3-15 gallons per 1000 barrels water) for a period of 4-8 hours twice weekly.

Subsequent dosage: Inject 200-400 ppm COREXIT 7765 (3-15 gallons per 1000 barrels water) for 4 hours once a week, or as needed to maintain control.

Continuous treatment: Inject 20-100 ppm COREXIT 7765 (approximately 0.3-4 gallons per 1000 barrels water) via a suitable chemical injection pump.

PACKER FLUIDS

Mix COREXIT 7765 into the fluid as it is being made up, using a treat rate of 1300-2600 ppm (1-2 drums per 1000 barrels fluid), for prevention of general corrosion and corrosion due to activity of sulfate reducing bacteria.

WORKOVER FLUIDS

COREXIT 7765 should be added to the water in the mix tank as the workover fluid is made up. Use 250-1000 ppm COREXIT 7765 for this service (10.2-40.7 gallons per 1000 barrels fluid).

NET WT. 441 LBS. (200 Kg.)
NET VOL. 55 GALS. (U.S.) (208.2 LITERS)