

TOWERTRINE N-25

E.P.A. REG. NO. 8959-22

E.P.A. Est. No. 8959-WI-1

BIOCIDE

FOR USE IN COMMERCIAL & INDUSTRIAL RECIRCULATION WATER TOWERS

ACTIVE INGREDIENT

Polyoxyethylene (dimethylimino) ethylene (dimethylimino) ethylene dichloride 25%

INERT INGREDIENTS

Weight Per Gallon 8.82 lbs.

Weight of Active Ingredient per gallon 2.11 lbs.

APPLICATIONS: TOWERTRINE is used to control algae, bacteria and fungi in commercial and industrial cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 2.4 to 6.0 fluid ounces of TOWERTRINE per 1000 gallons of water, to provide a concentration of 20 to 50 parts per million based on the total weight of water in the system is recommended. Subsequent slug additions of 6.0 to 6.0 fluid ounces of TOWERTRINE per 1000 gallons of water (5 to 50 parts per million) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CAUTION

KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. May cause skin damage. Avoid contact with skin and eyes. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists, get medical attention. Avoid contamination of food.

DO NOT REUSE CONTAINER DESTROY WHEN EMPTY

This product is toxic to fish. Do not add treated effluent to lakes, streams, or ponds. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label.

1005 015

ACCEPTED
8959-22

applied biochemists inc

Net Contents 30 Gallons