

FUNGICIDE AND
FOR ECONOMIC POISON REGISTERED
ED UNDER NO. 9091-1

Comment

vantrol

VANTROL CONDITIONER

To Control Bacterial Contamination In
Metalworking Coolant Systems

WHEN TO USE

Vantrol Conditioner is recommended whenever cleaning, rinsing and refilling the system with fresh coolant does not eliminate odors.

DIRECTIONS

1. Drain system, removing all contamination, including fluid, chips and sludge.
2. Clean system with the recommended Vantrol machine cleaner.
3. Recharge with the recommended Vantrol water soluble.
4. Add one fluid ounce of Vantrol Conditioner for each 10 gallons of emulsion.
5. Repeat the addition of one ounce of Vantrol Conditioner for each 10 gallons of mix after one week of operation and repeat again after two weeks of operation. DO NOT exceed the recommended concentration.

WARNING

Keep out of reach of children.

May cause skin irritation or eye damage. Protect eyes when handling. If in contact, flush thoroughly with water. For eyes get medical attention.

Harmful if swallowed.

ACTIVE INGREDIENTS

2-(Hydroxymethyl)-2-Nitro-1,
3-Propanediol40%

INERT INGREDIENTS60%

NET CONTENT:

EPA Reg. No. 9091-1

Van Straaten Chemical Company
CHICAGO, ILLINOIS 60606

ACCEPTED WITH COMMENTS