

---

# vantrol<sup>®</sup>

---

## VANTROL CONDITIONER No. 5

To Control Bacterial Contamination In  
Metalworking Coolant Systems

### WHEN TO USE

Vantrol Conditioner is recommended whenever cleaning, rinsing and refilling the system with fresh coolant does not eliminate odors.

### DIRECTIONS

1. Drain system, removing all contamination, including fluid, chips and sludge.
2. Clean system with the recommended Vantrol machine cleaner.
3. Recharge with the recommended Vantrol water soluble.
4. Add one fluid ounce of Vantrol Conditioner for each 10 gallons of emulsion.
5. Repeat the addition of one ounce of Vantrol Conditioner for each 10 gallons of mix after one week of operation and repeat again after two weeks of operation. DO NOT exceed the recommended concentration.

## CAUTION

Keep out of reach of children.

Harmful if swallowed, inhaled, or absorbed through skin. Do not get in eyes, on skin, or on clothing. Wear safety goggles and rubber gloves when handling the concentrate. In case of contact, flush with water. In case of eye contact, get medical attention. Rinse empty container thoroughly with water and discard it.

### ACTIVE INGREDIENTS

Hexahydro-1, 3, 5,-tris  
(2-hydroxyethyl)-s-triazine . . . . . 39.2%

INERT INGREDIENTS . . . . . 60.8%

### NET CONTENT:

USDA Reg. No. 9091-3

**Van Straaten Chemical Company**

CHICAGO, ILLINOIS 60606

---

9091-3