

7-21-71  
UNDER THE FEDERAL INSECTICIDE ACT  
FOR ECONOMIC POISON REGISTERED  
ED UNDER NO. 10576

# FOR ALL WOOD SURFACES WOOD-STAIN PRESERVER

Wood must be — BARE, CLEAN AND DRY  
Stir Thoroughly Before Using.

Lumber in contact with the soil should be dipped for three minutes minimum. For maximum protection, poles, fence posts and foundation timbers should be immersed in WOOD-STAIN PRESERVER for a maximum of 12 to 48 hours.

O.K. under varnish, shellac, paint and Waterlox products.

Apply one or two flowing coats of WOOD-STAIN PRESERVER by brush or spray to attain the depth of color desired.

If a gloss finish is desired, wait a minimum of two days before applying a finish coat. See your Waterlox dealer for specific instructions

Clean-up - mineral spirits and paint thinner  
Average coverage 150 sq. ft.



# WOOD-STAIN PRESERVER

FOR ALL WOOD SURFACES

STAIN  
WHITE

U.S.D.A. Reg. No. 9284-6



**SLOWS SHRINKING  
AND SWELLING**



**CONTROLS DECAY AND ROT  
REDUCES SPLITTING**



**LESSENS WARPING**

## PREVENTS WOOD ROT

SEE BACK PANEL FOR ADDITIONAL

**DANGER: HARMFUL OR FATAL IF SWALLOWED. KEEP OUT OF REACH OF CHILDREN.**

ACTIVE INGREDIENTS 79.50%, PENTACHLOROPHENOL 4.50%, OTHER CHLORINATED PHENOLS

**1 GALLON U. S. MEASURES**