

[9319-35]

Silikil

S

ACTIVE INGREDIENTS

Amorphous Silica * 37%

calcium silicate * 55%

INERT INGREDIENTS 8%

*SILICON DIOXIDE equivalent to 65%

DIRECTIONS

DRY WOOD TERMITES - To protect against entrance of dry wood termites, apply with an electric or hand rotary duster beneath the house and attics. Treat all wood surfaces at the rate of one pound per 1,000 square feet of wooden surface. Close air vents on windward side and turn off furnace and close furnace heat vents during treatments. SILIKIL will not kill termites already in wood.

Do not reuse container.
Destroy when empty.

NET WEIGHT: 25 lbs.

CUSTOM CHEMICIDES INC.

SAN LEANDRO, CALIFORNIA 94577

ACCEPTED
MAR 14 1975
Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 9319-3

CAUTION

KEEP OUT OF REACH OF CHILDREN

CAUTION: Avoid inhalation of dust. Avoid skin contact. Wear a respirator when treating confined areas to prevent drying of nose and throat. Wash all exposed skin after application with soap and water to prevent drying & chapping of skin.

Do not use in edible products areas of food processing plants, restaurants or other areas where food is commercially prepared or processed. Do not use in serving areas while food is exposed.

DUST ONLY IN AREAS NOT ACCESSIBLE TO CHILDREN AND PETS

EPA Reg. No. 9319-35

EPA-EST NO. 9319-CA-1 ←

EPA-EST NO. 9319-CA-2