



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

WASHINGTON, D.C. 20460

OFFICE OF
PREVENTION, PESTICIDES
AND TOXIC SUBSTANCES

NOV 03 2004

Mr. Hamdi Latif
Flexabar Corporation
1969 Rutgers University Boulevard
Lakewood, NJ 08701

Subject: Aquagard II Waterbase Antifouling
EPA Registration Number 9339-22
Your Amendment Dated September 27th, 2004
Submission Dated September 28th, 2004

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA), as amended, to revise the "Environmental Hazards" section as per the Department of Pesticide Regulation of California, is acceptable.

A stamped copy of the labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Karen M. Leavy-Munk at (703) 308-6237.

Sincerely,

A handwritten signature in black ink that reads "M. Swindell".

Marshall Swindell
Product Manager 33
Regulatory Management Branch I
Antimicrobial Division(7510C)

ENVIRONMENTAL HAZARDS

This pesticide is toxic to aquatic organisms including fish and shellfish. Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinse is a violation of Federal Law. If these wastes cannot be disposed of by use, according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional office for guidance. Waste resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.*

Do not allow chips, and dust generated during paint removal, to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent to sewer system without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

STORAGE & DISPOSAL

STORAGE

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Store in cool dry area away from heat or open flame. Keep from freezing.

PESTICIDE DISPOSAL

Pesticide spray mixture or rinse water, that cannot be used according to label instructions, must be disposed of according to applicable Federal, State or Local procedures.

CONTAINER DISPOSAL

Do not re-use empty container. Replace cap and dispose of in a sanitary landfill or by other approved State and Local procedures. Do not puncture or incinerate.

AQUAGARD[®] II

WATERBASE Antifouling

Paint for Aluminum Hulls

COMMERCIAL	
ACTIVE INGREDIENTS:	
Cuprous Oxide	3.88%
INERT INGREDIENTS	96.12%
TOTAL	100.00%

FIRST AID

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a Poison Control Center or doctor for treatment advice.
IF INHALED: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give mouth to mouth, if possible. Call a Poison Control Center or doctor for further treatment advice.
IF ON SKIN OR CLOTHING: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a Poison Control Center or doctor for treatment advice.
IF SWALLOWED: Call a Poison Control Center or doctor immediately for treatment advice. Have person sip a glass of water (if able to swallow). Do not induce vomiting unless told to do so by Poison Control Center or doctor. Do not give anything by mouth to an unconscious person.
NOTE TO PHYSICIAN: Probable mucosal damage may contra-indicate the use of gastric lavage.
NOTE: Have the product container or label with you when calling a Poison Control Center or doctor or when going for treatment.

WARNING:

KEEP OUT OF REACH OF CHILDREN

PRECAUTIONARY STATEMENTS

HAZARDOUS TO HUMANS (& DOMESTIC ANIMALS)

~~Causes eye irritation. Do not get in eyes, on skin or on clothing. Wear goggles or face shield. Wear protective clothing such as gloves, long sleeved cotton shirt, long pants and hat. Harmful if inhaled. Avoid breathing spray mist, vapor or dust. While spraying, sanding or blasting, wear mask or pesticide respirator approved by the National Institute of Occupational Safety and Health. Remove contaminated clothing and wash before reuse.~~

DISCLAIMER:

The performance of any means paint or coating depends on many factors outside the control of Flexel Corp., including environmental conditions. Therefore, Flexel Corp. can not guarantee this product's suitability for your particular purpose of application. Implied warranties of fitness for particular purpose and of merchantability are excluded. Flexel Corp. shall not under any circumstances, be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Flexel Corp.'s option.

EPA Registration No. 9339-22

EPA Est. No. 9339-22-NJ01

NET CONTENTS:
1 Qt. (U.S.)

ACCEPTED
with COMMENTS
in EPA Letter Dated:

NOV 3 2004

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

9339-22

DIREC

It is a violation of Federal Law to use this product in a
Product may cause skin irritation.

PREPARATION:

To prepare the surface for coating, remove all loose or
pressure water, scraping or by disc-sanding. Be sure
or ingestion of the paint dust generated.

APPLICATION:

A clean, dry surface (free of scale, corrosion, dirt, grease
the optimum performance of this coating when used. 1
surface preparation will result in unsatisfactory perform
contaminations that are generated by the cleaning pro
MIX the coating with either a high speed mixer or a pa
plete pigment re-incorporation. In the event the coating
easily. Clean up with water when finished.

USE de-waxer or solvent wash. Surface should be sa
Apply one (1) thin coat of recommended Zinc Chromat
allowing two to four (2-4) hours drying time between co
instructions carefully.

THEN apply two (2) coats of Aquagard II Waterbase A
spray. Be sure to follow mixing instructions, applying 1
minimum of four (4) hours between coats and a minimum

BARE ALUMINUM HULLS: Abrade to bright metal by
blasting residue and immediately apply one (1) thin coat

(2) coats of Aquagard 190 Primer, allowing two to four
and sand lightly. Follow these instructions carefully. Th

Antifouling Paint for Aluminum Hulls, allowing two to fo
dry overnight. Allow a minimum of twenty four (24) ho

PREVIOUSLY PAINTED ALUMINUM HULLS: If the pr
with 80 grit sandpaper. Wipe clean of sanding residue

Antifouling Paint for Aluminum Hulls. If the old paint by
Waterbase Antifouling Paint for Aluminum Hulls to test

Antifouling Paint for Aluminum Hulls cracks or lifts, all
"Bare Aluminum" system specified above. If nothing ap

patch dry for several hours and then scrape this product

adhesion looks good, sand the entire surface through

Aquagard II Waterbase Antifouling Paint for Aluminum

chipping, peeling or flaking) should be stripped to bare
specified above.

Medical Emergencies
MANUFACTURED BY FLEXELABAR
1809 Rutgers University