UNITED STARD DUNY	U.S. ENVIRONMENTAL PROTECTION AGENCY Office of Pesticide Programs Registration Division (7504C) 401 "M" St., S.W. Washington, D.C. 20460	EPA Reg. Number: 9339-24	Date of Issuance: MAR - 1 2000	
THURL PROTECTO	<u> </u>		Term of Issuance: Conditional	
(under FIFRA, as amended)		Name of Pesticide Product: Flexgard VI Waterbase Preservative Copper Paint		
Flexbar Co 1969 Rutge Lakewood,	of Registrant (include ZIP Code): prporation ers University Blvd. NJ 08701 labeling differing in substance from that accepted	in connection with #	is registration must	
be submitted to correspondence c	and accepted by the Registration Division prior to n this product always refer to the above EPA regist	use of the label in co ration number.	ommerce. In any	
	information furnished by the registrant, the above istered under the Federal Insecticide, Fungicide ar		сеby	
In order to prot cancel the regis with the regist	in no way to be construed as an endorsement or reco ect health and the environment, the Administrator, stration of a pesticide in accordance with the Act. ation of a product under this Act is not to be cons- the name or to its use if it has been covered by c	on his motion, may at The acceptance of any strued as giving the re	any time suspend or / name in connection	
	product is conditionally regis . 3(c)(7)(A) provided that you:	tered in acco	rdance with .	
FIFRA sec 1. 3 your produced registrant acceptable		uired for reg en the Agency t such data;	istration of requires all and submit	
FIFRA sec 1. S your produced registrant acceptable under FIF	. 3(c)(7)(A) provided that you: Submit and/or cite all data request under FIFRA sec. 3(c)(5) wh is of similar products to submite responses required for reregi	uired for reg en the Agency t such data; stration of y	istration of requires all and submit	
FIFRA sec 1. 3 your produced registrant acceptable under FIFI 2. 1	. 3(c)(7)(A) provided that you: Submit and/or cite all data request under FIFRA sec. 3(c)(5) wh ts of similar products to submite responses required for reregi RA section 4.	uired for reg en the Agency t such data; stration of y s:	istration of requires all and submit our product	
FIFRA sec 1. 3 your produced registrant acceptable under FIF 2. 1 a.	. 3(c)(7)(A) provided that you: Submit and/or cite all data request under FIFRA sec. 3(c)(5) wh ts of similar products to submite responses required for rereging RA section 4. Make the following label change Revise the EPA Registration Nu	uired for reg en the Agency t such data; stration of y s: mber to read,	istration of requires all and submit our product "EPA Reg.	
FIFRA sec 1. 3 your produced registrant acceptable under FIF 2. 1 a. b.	. 3(c)(7)(A) provided that you: Submit and/or cite all data requet under FIFRA sec. 3(c)(5) wh ts of similar products to submite responses required for rereginal RA section 4. Make the following label change Revise the EPA Registration Nu No. 9339-24". Place the appropriate EPA Esta	uired for reg en the Agency t such data; stration of y s: mber to read,	istration of requires all and submit our product "EPA Reg.	

and the second and the second s

AN CONTRACTOR OF CONTRACTOR

EPA Form 8570-6

6

a contraction of the second se

)

)

page 2 EPA Reg. No.

)

)

3. Submit two copies of the revised final printed label for the record.

The Confidential Statement of Formula dated June 15, 1999, is acceptable.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Marshall Swindell Product Manager 33 Regulatory Management Branch I Antimicrobial Division(7505C)

HAZARDS TO HUMANS(& DOMESTIC ANIMALS) WARNING

IF SWALLOWED: May be fatal if swallowed. Drink promptly a large quantity of water. Do not induce vomiting.Call a physician immediately.

IF INHALED: May be fatal if inhaled. Do not breathe vapor or spray mist while spraying paint or sanding of boat surface. Wear a mask of respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute of Occupational Safety and Health. Remove victim to fresh air if not breathing, give artificial respiration. Preferably mouth-to mouth. Get medical attention.

IF ON SKIN: Harmful if absorbed though skin. Avoid contact with skin, eyes, or clothing Wear protective clothing such as gloves, long -sleeved cotton shirt, long pants and hat. Wash with plenty soap water. Get medical Attention. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

IF IN EYES: Flush with plenty of water. Get Medical Attention.

ENVIRONMENTAL HAZARDS:

Ginnis.

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

"Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility"

STORAGE & DISPOSAL STORAGE

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Store in cool dry area away from heat or open flame.

PESTICIDE DISPOSAL Pesticide spray mixture or rinse water, which cannot be used according to label instructions, must be disposed of according to applicable Federal, State or Local procedures.

CONTAINER DISPOSAL Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary land fill, or by other procedures approved by state and local authorities.



Commercial FLEXGARD VI WATERBASE PRESERVATIVE

ACTIVE INGREDIENT	
Cuprous Oxide	18.00%
NERT INGREDIENT:	82.00%
Copper as metallic 16.29%)	
TOTAL	100%

WARNING:

STATEMENT OF PRACTICAL TREATMENT IF SWALLOWED: Drink promptly a large quantity of water. Do not induce vomiting.Call a physician immediately.

IF INHALED: Remove victim to fresh air, if not breathing, give artificial respiration,

Preferably mouth-to mouth.

Get Medical Attention.

IF ON SKIN: Wash with plenty of soap and water. Get Medical Attention.

TE IN DY/RC EL - h - M. - h-

IF IN EYES: Flush with plenty of water. Get Medical attention.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

Net Contents: EPA Registration No. 9339 EPA Est. No. 9339

ACCEPTE Manufactured by: With COMMENTER FLEXABAR CORPORATION 1969 Rutgers University Blvd. ir. SPA LOTUT Date Lakewood New Jersey, U.S.A. 08701 Phone: 732-901-6500

To prepare the surface for coating remove all old coating and fouling residue by either washing with high pressure water, scraping or by disc sanding. Be sure to use the proper protective equipment to prevent inhalation or ingestion of the paint

dust generated.

painting,

mended dry film thickness.

A clean dry surface, free of scale, corrosion, dirt, grease, oil, marine, fouling, or other foreign matter will provide the optimum performance of this coating or for touch-up. Inadequate surface preparation will result in unsatisfactory performance. Be sure to remove all dust, debris and other surface contamination's that are generated by the cleaning process prior to

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH

LABELING.

This is a cuprous oxide pigmented coating formulated espe-

cially to prevent the attachment of both plant and animal foul-

ing on vessels immersed in both seawater and brackish water.

This coating requires no primer when used directly over fiber-

glass or wood. For optimum performance, two (2) coats are

recommended. The theoretical coverage of this product is at

least 400 square feet per gallon, when applied to the recom-

Mix the coating with either a high speed mixer, or a paint shaker for minimum of five (5) minutes to insure complete pigment reincorporation. This in the event that the coating is too thick to apply easily. this with water. Clean up with water when finished.

Apply by either brush, roller or spray. Be sure to follow mixing instructions and apply the correct thickness. Allow a minimum of four (4) hours between coats and a minimum of twenty-four (24) hours before undocking vessel.

LIMITATION OF WARRANTY STATEMENT

Seller's guarantee shall be limited to the terms set forth on the label and subject thereto. The buyer assumes the risk to persons or property arising from the use or handling of this product and accepts the product on that condition.

Refer to bulletin No. 118 Directions for user for nylon aquaculture nets.

MAR - 1 2000

Under the federal Insection try Disglade, and Lodontingle for an unrended, for the position $d_{1,2}$ rematched under SPA Rog Ma, 9339-24