

9339-31

04/24/2008

1/2

APR 24 2008

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, D.C. 20460



Office of Pesticide Programs

Flexabar Corporation
1969 Rutgers University, Blvd
Lakewood, N. J. 08701

Attention: Hamdi Latif

Subject: Aquaguard Alumi-Koat Clear
EPA Registration No. 9339-31
Your Submission Dated March 13, 2008

The application, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended, is acceptable.

- Updated Label

A stamped copy of the "accepted" label is enclosed for your records.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely

Marshall Swindell
Product Manager (33)
Regulatory Management Branch 1
Antimicrobials Division (7510P)

Enclosure

AQUAGARD

Alumi-Koat CLEAR

Outboard & Lower Unit ANTI-FOULING PAINT

ACTIVE INGREDIENTS:	
Cuprous Thiocyanate	3.71%
N-Cyclopropyl-N-(1,1-dimethylethyl)-6-(methylthio)-1,3,5-triazine-2,4-diamine	80%
INERT INGREDIENTS: 95.49%	
100.00%	
Copper as Metallic	1.98%
Contains Petroleum Distillates	

- Control slime & other fouling organisms!
- For use on aluminum & other non-ferrous materials
- Ideal for use on stern drives and other lower units

EPA Est. No. 9339 NJ01
EPA Reg. No. 9339-31

71310 Clear

12 oz. / 340g

KEEP OUT OF REACH OF CHILDREN

CAUTION: Extremely flammable. Contents under pressure. Harmful if inhaled. See other cautions on back panel.

ACCEPTED
with COMMENTS
EPA Letter Dated:
APR 24 2008

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No.

9339-31

DIRECTIONS FOR USE

APPLICATION: A clean dry surface free of scale, corrosion, dirt, grease, oil, marine fouling or other foreign matter will provide the optimum performance of this paint. Inadequate surface preparation will result in unsatisfactory performance. Be sure to remove all dust, debris and other surface contaminations that are generated by the cleaning process prior to painting. Bring to room temperature (72°) before spraying. Shake can for 3 minutes, listening for mixing ball.

New Outdrive Units: Lightly sand the factory finish with 80 grit sandpaper, wipe clean with Aquagard 180 Solvent Wash, allow to dry. Then apply two (2) coats of Aquagard II Alumi-Koat allowing 2-4 hours drying time between coats. Allow to dry 2-4 hours before launching.

Bare Aluminum: Make sure surface is dry and free of grease, wax, oil and loose paint. Abrade to bright metal by sandblasting, sanding or wire brushing. Wipe clean of any residue, then apply Aquagard 181 Primer or 189 Sandless Primer Spray. Closely follow these instructions, then apply two (2) coats of Aquagard II Alumi-Koat allowing 2-4 hours drying time between coats. Allow to dry 2-4 hours before launching.

Previously Painted Aluminum: Previously painted surfaces in poor condition (chipping of flaking) should be stripped to bare metal, then proceed with the bare aluminum instructions specified above. If the previous antifouling paint is a vinyl type, sand it thoroughly with 80 grit sand paper, wipe clean of sanding residue and apply at least two (2) coats of Aquagard II Alumi-Koat.

PRECAUTIONARY STATEMENTS

CAUTION: HAZARDS TO HUMANS AND DOMESTIC ANIMALS
Causes eye irritation. Harmful if swallowed or absorbed through skin. Avoid contact with skin, eyes or clothing. Wear protective clothing such as gloves, long-sleeved shirt, long pants and hat. May be fatal if inhaled. Do not breathe vapor or spray mist. While spraying paint or sanding or sandblasting boat surfaces, wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash before reuse. Wash thoroughly with soap and water after handling.

FIRST AID: If swallowed: 1.) Call a poison control center or doctor immediately for treatment advice. 2.) Do not give any liquid to the person. 3.) Do not induce vomiting unless told to do so by a poison control center or doctor. 4.) Do not give anything by mouth to an unconscious person. **If on skin or clothing:** 1.) Take off contaminated clothing. 2.) If on skin wash with plenty of water. 3.) Get medical attention if irritation persists. **If inhaled:** 1.) Move person to fresh air. 2.) If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. 3.) Call poison control center or doctor for treatment advice. **If in eyes:** 1.) Hold eye open and rinse slowly and gently with water for 15-20 minutes. 2.) Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. 3.) Call a poison control center or doctor for treatment advice. **Other:** Have the product container or label with you when calling a poison control center or doctor or going for treatment. **Note to Physician:** Contains petroleum distillates. Vomiting may cause aspiration pneumonia.

PHYSICAL OR CHEMICAL HAZARD: Extremely flammable. Contents under pressure. Keep away from heat, sparks and open fire or heated surfaces. Do not puncture or incinerate container. Exposure to temperatures above 130°F may cause bursting.

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public waters unless this product is specifically identified an addressed in a NPDES permit. Do not discharge effluent containing this product to sewer

systems without previously notifying the sewage treatment plant authority. For guidance contact your state water board or regional office of the EPA.

STORAGE AND DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. **PESTICIDE DISPOSAL:** Pesticide wastes are toxic. Paint that cannot be used according to label instructions must be disposed of according to federal, state or local procedures under the Resource Conservation and Recovery Act.

CONTAINER DISPOSAL: Do not puncture or incinerate. A completely empty can, can be disposed of with household trash. Wrap in paper before disposing.

PRODUCT EMERGENCIES: 1-800-424-9300

DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Flexdel Corp. including environmental conditions. Therefore, Flexdel Corp. cannot guarantee this product's suitability or your particular purpose of application. Implied warranties of fitness for particular purpose and of merchantability are excluded. Flexdel Corp. shall not under any circumstances, be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Flexdel Corp., option.



©2007, Manufactured for Flexbar

1969 Rutgers University Blvd., Lakewood, NJ, USA 888.353.9335
aquagard-boatpaint.com Made in U.S.A. Printed in U.S.A.

2/2