**BATCH NUMBER NET CONTENTS ALGICIDE 107L** 1 GALLON 4 x 1 GALLON 5 GALLONS % by weight Poly [oxyethylene (dimethylimino) ethylene (dimethylimino) ethylene dichloride] ...... 12.0% **APPLICATION** Algicide 107L is used to control algae, bacteria and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 5.0 to 12.5 fluid ounces of Algicide 107L per 1000 gallons of water, to provide a concentration of 40 to 100 parts per million of Algicide 107L based on the total weight of water in the system is recommended. Subsequent slug additions of 1.25 to 12.5 fluid

## CAUTION! KEEP OUT OF REACH OF CHILDREN

biological problem. Slug additions should be made in the sump of water cooling towers.

EPA REG. NO. 9420-3

ounces of Algicide 107L per 1000 gallons of water (10 to 100 parts per million of Algicide 107L) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the micro-

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact, flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food. Do not reuse container. Destroy when empty. This product is toxic to fish. Do not add treated effluent to lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label.

**Manufactured By** 

WATER CHEMISTS, INC.

1275 SOUTH BOYLE AVE., LOS ANGELES, CALIF.

N3-6

LOS ANGELES - SAN DIEGO - LAS VEGAS - SAN JOS

## (Center panel)

WEL-CHLOR (Granular)

Net Wt 8 1bs

FOR DISINFECTION OF NEW AND OLD WATER WELLS AND SYSTEMS.

ACTIVE	INGREDIENTSCALCIUM HYPOCHLORIT	E\$	70%
INERT :	INGREDIENTS	•••••	30%

\*70% Available Chlorine

COTEY CHEMICAL CORPORATION
P. O. BOX 2039 Ph 742-2096
LUBBOCK, TEXAS 79408

