

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS
AND DOMESTIC ANIMALS**

DANGER: Highly corrosive. Causes skin and eye damage. May be fatal if swallowed. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Irritating to nose and throat. Avoid breathing dust. Remove and wash contaminated clothing before reuse.

ENVIRONMENTAL HAZARDS: This product is toxic to fish. Do not discharge into lakes, streams, ponds, or public waters unless in accordance with an NPDES Permit. For guidance contact the regional office of EPA.

**PHYSICAL AND CHEMICAL
HAZARDS STRONG OXIDIZING
AGENT:**

Strong Oxidizing Agent. Mix only with water. Use clean dry utensils. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to fire or explosion. Contamination with moisture, organic matter, or other chemicals may start a chemical reaction, with generation of heat, liberation of hazardous gases, and possible generation of fire and explosion. In case of contamination or decomposition, do not resealed container. If possible isolate container in open air or well ventilated area. Flood with large volumes of water, if necessary.

Batch Number

Net Contents

1275 So. Boyle Ave.

Los Angeles, CA

WATER CHEMISTS, INC.

CT 935

Active Ingredients

Sodium
Dichloro-s-triazine
Dihydrate

Inert Ingredients

*available chlorine

0.7%

99.3%

For additional instruction call
(213) 263-6951

KEEP OUT OF REACH OF CHILDREN

DANGER

PRACTICAL TREATMENT: (FIRST AID):

If swallowed feed bread soaked in milk followed by olive oil or cooking oil. Call a physician immediately. If on skin: brush off excess chemical and flush skin with cold water for at least 15 minutes. If irritation persists, get medical attention. If in Eyes: Flush with cold water for at least 15 minutes. Get medical attention.

*SEE ADDITIONAL PRECAUTIONS ON SIDE PANEL

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

Industrial Cooling Tower Water

For badly fouled systems add 1 1/2 or 3 lbs. of CT 935 industrial water biocide daily for each 10,000 gallon of system water. This provides 100 ppm and 20 ppm available chlorine respectively. Repeat each day until the system is free of visible fungi and algal slime. This condition is usually indicated when a free available chlorine residual of at least 1 ppm is found four hours after the treatment. When a system is under control add 5 or 10 oz. of CT 935 industrial water biocide daily per 10,000 gallon of system water to provide 2 or 4 ppm free available chlorine respectively. These amounts may be raised or lowered as required and indicated by water conditions and by test for chlorine residual. Reliable test kits for testing free available chlorine are available and should be used. CT 935 industrial water biocide should be added directly from the container to a place in the system where it will be evenly mixed with the water.

STORAGE AND DISPOSAL: Keep product dry in tightly closed container when not in use. Store in a cool dry, well ventilated area away from heat or open flame. In case of decomposition isolate container, if possible, and flood with large amounts of water to dissolve all material before discarding. Place in trash collection or dispose in approved landfill area, or bury in a safe place.

WATER CHEMISTS, INC.

1275 So. Boyle Avenue
Los Angeles, CA 90023

EPAREG NO 9420 5

EPAEST NO 9420 CA 01

ARIZONA

CALIFORNIA

NEVADA