

WARNING!

CONTAINS XYLOL, BUTYL
ALCOHOL AND
CUPROUS OXIDE

DO NOT USE, POUR, SPILL, OR
STORE NEAR HEAT OR OPEN
FLAMES

Avoid breathing of vapor or spray
mist.

Avoid contact with skin.

Close container after using.

Do not reuse empty container.

Destroy it by perforating or crush-
ing. Bury or discard in a safe place.

Do not contaminate water by clean-
ing of equipment or disposal of
wastes.

FIRST AID: IF SWALLOWED, DO NOT
induce vomiting. CALL A PHY-
SICIAN.

USE WITH

ADEQUATE VENTILATION

DEVVOE

MARINE

PAINTS & COATINGS • WORLD-WIDE

DEVVAN[®] FORMULA 214

EPITOX[®] PERMANENT RED ANTI-FOULING PAINT MD-7061

WARNING!

KEEP OUT OF REACH OF CHILDREN
VAPOR HARMFUL — COMBUSTIBLE
HARMFUL OR FATAL IF SWALLOWED

ACTIVE INGREDIENT	
Cuprous Oxide	38.46%
INERT INGREDIENTS	61.54%
	100.00%

*Equivalent to
Metallic Copper 34.15%

5 U. S. GALLONS
(18.925 LITERS)

Read Carefully Warning on Left Panel

EPA REG. NO. 9461-6

BATCH NO.

DIRECTION FOR USE

Before painting, remove all loose paint
from the surface to be painted with
oil. Remove all scale paint with
wire brush or scraper. Wash thor-
oughly, both by stirring and then
pouring from one clean container
to another several times. Stir from
time to time during application.

Apply one or two coats "as is" on
ship bottoms by brush or roller. For
spraying, thin if necessary with
No. 2 Solvent MD-3630. Do not
add oil or varnishes to this paint.
Allow four hours between coats.

Anti-fouling paints must be applied
over suitable barrier coats and
should not be applied directly to
metal. Launching may be accom-
plished as soon as one hour after
the final application.

FOR INDUSTRIAL USE ONLY

MAF 7061R2/523B 6/28/73

A PRODUCT OF

DEVVOE & RAYNOLDS COMPANY, INC.

NEW YORK, N. Y. 10004
NEW ORLEANS, LA. 70117
SAN FRANCISCO, CALIF. 94105