

DEVORE

MARINE

PAINTS & COATINGS · WORLD-WIDE

MD-3113

VINYL ANTI-FOULING FORMULA 121/63

MIL-P-15931B FOR HOT SPRAY

CAUTION

KEEP OUT OF REACH OF CHILDREN
VAPOR HARMFUL - COMBUSTIBLE
HARMFUL IF SWALLOWED
See carefully cautions on back panel

12/2/63
[Signature]

ANTI-FOULING INGREDIENTS
ACTIVE INGREDIENTS
Cuprous Oxide 70.3%
INERT INGREDIENTS 29.7
100.0%

USDA REG. NO. 9461-14

CONTENTS

5 U. S. GALS.

FOR USE BY PROFESSIONAL APPLICATORS ONLY

G. D. & R. CO. 1963

DIRECTIONS FOR USE

Be sure all surfaces are clean, free of scale, grease or oil. Remove all loose paint with wire brush or scraper. Mix thoroughly.

APPLICATION

Apply by Hot Spray Equipment. Use DEVRAN® MD-1931 Thinner for cleanup. Do not add oil or varnishes to this paint. Anti-Fouling paints must be applied over suitable barrier coats and should not be applied directly to metal. Allow 4 hours between coats. Vessels may be launched anytime after 2 hours at 77 degrees F. under good conditions.

CAUTION

CONTAINS AROMATIC HYDROCARBONS AND KETONES

Keep away from heat and open flame. Avoid breathing of vapor or spray mist. Avoid contact with skin. Do not take internally. Close container after using.

USE WITH ADEQUATE VENTILATION

MUD VAF HS 8 1 69

A Product of

DEVOE & RAYNOLDS CO., INC.

Newark, N. J. — New Orleans, La. — San Francisco, Calif.
07105 70117 94104