

# DEVOE

# MARINE

## PAINTS & COATINGS • WORLD-WIDE

### FORMULA 129

### VINYL BLACK ANTI-FOULING MIL-P-16189

### MD-

### CAUTION

KEEP OUT OF REACH OF CHILDREN

**VAPOR HARMFUL—COMBUSTIBLE**  
**HARMFUL IF SWALLOWED**

Read carefully cautions on left panel  
FOR USE BY PROFESSIONAL APPLICATORS ONLY

ANTI-FOULING INGREDIENTS

ACTIVE INGREDIENTS

Cuprous Oxide  
INERT INGREDIENTS

63.2%\*

36.8%

100.00%

\*Equivalent to 54.1%  
Metallic Copper

BATCH NO.

REG. NO. 9461-

### Directions for Use

Be sure that all surfaces are clean, free of moisture, scale, grease or oil. Remove all loose paint with wire brush or scraper. Mix thoroughly both by stirring and then pouring from one clean container to another several times. Stir from time to time during application.

Apply one or two coats "as is" on ship bottoms by brush or roller. For spraying, thin if necessary with DEVRAN® MD-1931 Thinner. Do not add oil or varnishes to this paint. Allow 4 hours between coats.

Anti-Fouling paints must be applied over suitable barrier coats and should not be applied directly to metal. Vessels may be launched anytime after 2 hours at 77° F. under good conditions.

MAF 693 7/19/71

A PRODUCT OF

**DEVOE & RAYNOLDS  
COMPANY, INC.**

NEWARK, NEW JERSEY 07105

NEW ORLEANS, LA. 70117

SAN FRANCISCO, CALIF. 94104

4/72  
461-16

**GALLONS**

## CAUTION

CONTAINS

**BIS (TRIBUTYL TIN) OXIDE  
AND CUPROUS OXIDE**

DO NOT USE, POUR, SPILL OR STORE NEAR HEAT OR OPEN FLAME.

Avoid breathing of vapor or spray mist.

May be absorbed through skin. Causes skin irritation.

Avoid contact with skin, eyes or clothing.

Do not use for storage of feed and food products.

Close container after using. Do not reuse empty container; destroy it by perforating or crushing and bury or discard in a safe place.

Do not contaminate water by cleaning of equipment or disposal of wastes.

FIRST AID: If swallowed, induce vomiting. CALL A PHYSICIAN.

In case of skin contact remove contaminated clothing and wash skin with soap and water; for eyes, flush with plenty of water and get medical attention. Wash clothing before reuse.

USE WITH ADEQUATE

VENTILATION

# DEVOL

# MARINE

## PAINTS & COATINGS • WORLD-WIDE

### ANTI-FOULING PAINT MD-3693

#### WARNING

KEEP OUT OF REACH OF CHILDREN  
**VAPOR HARMFUL—COMBUSTIBLE**  
**HARMFUL IF SWALLOWED**

Read carefully cautions on left panel  
FOR USE BY PROFESSIONAL APPLICATORS ONLY

E.P.A. REG. NO. 94-181

## 5 U.S. GALLONS

ACTIVE INGREDIENTS  
Cuprous Oxide  
Copper Powder  
Bis (Tributyltin)  
Oxide  
INERT INGREDIENTS

Equivalent to 12.5  
copper in 10.10

# DEVORE

# MARINE

PAINTS & COATINGS • WORLD-WIDE

FORMULA 129  
VINYL BLACK ANTI-FOULING MIL-P-16189  
MD-

CAUTION

KEEP OUT OF REACH OF CHILDREN

VAPOR HARMFUL—COMBUSTIBLE  
HARMFUL IF SWALLOWED

Read carefully cautions on left panel  
FOR USE BY PROFESSIONAL APPLICATORS ONLY

ANTI-FOULING INGREDIENTS  
ACTIVE INGREDIENTS  
Cuprous Oxide  
INERT INGREDIENTS

100.00%

\*Equivalent to  
Metallic Copper

BATCH NO.

5 U. S. GALLONS

REG NO 9461

### CAUTION

CONTAINS METHYL  
ISOBUTYL KETONE  
AND CUPROUS OXIDE

DO NOT USE, POUR, SPILL OR  
STORE NEAR HEAT OR OPEN  
FLAME.

Avoid breathing of vapor or spray  
mist.

Avoid contact with skin.  
Do not take internally.

Close container after using. Do not  
reuse empty container. Destroy it  
by perforating or crushing. Bury  
or discard in a safe place.

FIRST AID: If swallowed, do NOT  
induce vomiting.

CALL A PHYSICIAN

USE WITH ADEQUATE  
VENTILATION

### Directions for Use

Be sure that all surfaces are clean,  
free of moisture, scale, grease or  
oil. Remove all loose paint with  
wire brush or scraper. Mix thor-  
oughly both by stirring and then  
pouring from one clean container  
to another several times. Stir from  
time to time during application.

Apply one or two coats "as is" on  
ship bottoms by brush or roller. For  
spraying, thin if necessary with  
DEVORAN® MD-1931 Thinner. Do  
not add oil or varnishes to this  
paint. Allow 4 hours between  
coats.

Anti-fouling paints must be ap-  
plied over suitable barrier coats  
and should not be applied directly  
to metal. Vessels may be launched  
anytime after 2 hours at 77° F  
under good conditions.

MAF 693 7-19-71

A PRODUCT OF  
**DEVORE & RAYNOLDS  
COMPANY, INC.**  
NEWARK, NEW JERSEY 07105  
NEW ORLEANS, LA 70117  
SAN FRANCISCO CALIF 94104